

**Douglas County Surveyor's Record of
Government Corners Renewed**

32 T.S. 5 R. W. W. M.

✓ $\frac{1}{4}$ CORNER BETWEEN SECTIONS 12 and 13. **CORNER NO. 32 10**
A 3 ft. at Butt S. 73 $\frac{1}{2}$ ° W., 295 lks. *Maple*
An Ash 24" dia. bears N. 56° W., 264 lks.

✓ $\frac{1}{4}$ CORNER BETWEEN 19 and 20. **11**
Corner located from the original B.T. namely **SEE ALSO #29**
A 32" Black Oak S. 29° W., 48 lks. **REN #8**
Tree in good condition - now 48" dia. Post for corner and **#29**
marked new B.T.s. **SEE CORNER NO.**
14" Fir dia. bears N. 62 $\frac{1}{2}$ ° E., 26.0 ft. blazed and
scribed S. C.S.P.T.

SOUTHEAST CORNER OF SECTION 30 **12**
I found a 40" Fir stamp with scribe markings **#(S 29) at 24"**
all other trees gone. from this I set a 1 $\frac{1}{2}$ " x 36" truck
axle S 46° W a distance of 25 lks. (15.0 ft.) for the corner **Geo. Baker**
common to sections 29-30-31-32 S R 5 W From this I **WIT.**
marked the following bearing trees:
14" Fir bears N 20° 32' E 72.7 ft. **1964 GOV'T. BRASS CAP**
15" Fir bears S 46° 13' E 41.8 ft. **SEE ALSO**
15" Ash bears S 24° 07' W 99.4 ft. **#26**
8" Fir bears S 88° W 12.0 ft.

$\frac{1}{4}$ SECTION CORNER BETWEEN SECTIONS 30 and 31 **13**
I found a squared stake scribed (15) B.T.'s o.k. as per
notes. I set 1" pipe in place of stake for corner. **152**

Cor of secs. 14, 15, 22, and 23. **14**
Found remains of an old yew stake. Reference points are:
A concrete monument 12" at top 36" deep with OSHD standard
BM disk centered, bears S 0° 16' 30" W 158.72 ft. **REN #171**
A concrete monument and standard BM disk bears
S 89° 50' 30" E 1440.01 ft. **(144.0) ft. SC**

$\frac{1}{4}$ CORNER BETWEEN 26-27 **15**
Both O. B. T.
18" Pine N 30° W 60.06 ft. **FOUND O.K. 7-6-67 V.R.T.**
20" Fir North 44.88 ft. **C.S. 53/52**
Drove 1 $\frac{1}{2}$ " I. P. for corner.

SEC. COR. 19-30 (R5W) 24-25 (R6W) **16**
Found 2 old B.T. badly rotted, drove 1 $\frac{1}{4}$ " I. P. for cor.
marked 16" W. Oak S 43° E 37.6 ft. (O.B.T.)
16" Pine N 78° 25' E 29.2 ft.
22" Pine N 75° 15' W 39.5 ft.
15" Fir S 25° 42' W 44.9 ft. **SEE ALSO #40**

$\frac{1}{4}$ COR. WEST SIDE SEC. 30 **17**
Set halfway bet. Sec. Corners. Drove 1" I.P. for corner
Scribe 14" Maple S 51° 30' W 399.0 ft. **REN #172**
7" Ash N 65° 30' W 134.8 ft. **- FD. O.K. J.M.P. AUG. 1967**

N. E. COR. DLC 39 **18**
 $\frac{3}{4}$ " Iron Pipe **SAME AS #44**
24" W. Oak S 35° W 34.3 ft.
24" Fir N 41° 30' W 9.2 ft.
8" B. Oak S 78° 15' E 14.1 ft.
This is Corner as found March 1, 1950. **m27-12 2595/45**

N. W. COR. DLC 39 **19**
Placed by measurements.
 $\frac{3}{4}$ " I. Pipe. **SAME AS #98**
10" B. Oak N 68° E 50.7 ft.
24" W. Oak S 64° E 78.8 ft. **C.S. 45/45 m27-12**

WEST $\frac{1}{4}$ CORNER SEC. 19 **20**
Found 24" W. Oak S 19° W 196.7 ft. **8-17-67-Corner OK - J.M.P.**
Center of tree all rotten. **LOCATED IN FENCE CORNER**
40" B. Oak N 38° 30' E 209.8 ft. tree uprooted. **C.S. 53/62**
Drive 1" I. Pipe for Corner. **SEE ALSO #39**
Scribe 12" W. Oak S 78° 20' W 59.2 ft. **C.S. 45/45 m27-12**
14" W. Oak N 12° 45' E 194.0 ft.

C. E. Roberts
Sept. 1909
H. L. Eppstein
Wit.
N. E. Richardson
John Opaten
July 18, 1909.
Geo. Baker
WIT.
R. Asberry
E. DuBell
C.S. 40/3
April 25, 1947
Geo. Baker
WIT.
R. Asberry
E. DuBell
April 25, 1947
Geo. C. Baker
Jan. 22, 1946
C.S. 40/8
Geo. J. Wenderoth
Deputy Cnty. Surv.
C. J. Wenderoth - Surv.
F. J. Loso
C. Smith - Witnesses
Oct. 11, 1945
April 6, 1949
G. J. Wenderoth
Deputy County Surveyor
F. J. Loso - Witnesses
Joe Grey
March 3, 1950