Douglas County Surveyor's Record of Government Corners Renewed

32 T. S. 5 R. W. W. M.

KOKE-CHAPMAN CO., EUGENE, ORE. 21881

C. Corner to Sections 30 & 31. (on E. line T 32 SR 5 W) 128
Found - Madrone (now 13" diam) S. 62° E 24.4 ft. Partial scribing visible on partly rotted face.
Rotten Fir stump N. 48° E. 13.2 ft. Found good reverse scribing "BT" on decayed overgrowth of old face.
Set - Brass Cap mkd: "County Surveyor's Office 1964 T 32 S. R 5 W | S 30 / S 31 | R 4 W" CC
New BTs: 14" Madrone N. 8° E 16.5 ft. Mkd: "T 32 SR 4 W S 30 CC CS BT"
4" Doug. Fir S. 73° E 13.5 ft. Mkd: "CC S 31 CS BT"
19" Live Oak S. 9° W 20.0 ft. Mkd: "CC S 30 S 31 CS BT"
Corner lies directly on top of ridge.

C. Corner to Sections 25 & 36. (on W. line T 32 SR 4 W) 129
Found - Yew wood stake set by Wenderoth. Scribed "CS" (Ren # 85)
Doug. Fir (now 15" diam) N. 38° W. 39.7 ft. (to face) Both axe scars very plain, but healed over. Tree in good condition.
Wenderoth's SW tree is now dead & down. Scribing visible.
Stump of original SW tree & burned remains of original NW tree.
Set - Brass Cap Mkd: "County Surveyor's Office 1964 T 32 SR 5 W CC | S 25 / S 36 | R 4 W" Reset yew post alongside.
New BT: 5" White Fir S. 73° W 14.0 ft. Mkd: "CC S 36 CS BT"

Milo E. Godfrey
Mike Stone
June, 1964
C.S. File No. 53/52

Witness Corner ¼ Sections 25 & 36. 130
Found - 30" Fir N. 46° E 14.5 ft., uprooted, down & dead. Cut open & found good scribing.
No trace found of SW tree.
Position for ¼ corner falls in creek. Set witness corner 10 ft. west of ¼ corner.
Fd. O.K. by: L.D. SMITH MAY 14, 1982 92-34 M
Set - Brass Cap Mkd: "County Surveyor's Office 1964 T 32 SR 5 W WC 10 ft. E to ¼ S 25 / S 36"
New BTs: 42" Doug. Fir S. 60° W. 33.8 ft. Mkd: " WC ¼ S 36 CS BT" Bark Scribed.
36" Doug. Fir N. 33° E. 70.9 ft. Mkd: "WC ¼ S 25 CS BT" In wood

---

Section Corner to Sections 25, 26, 35 & 36. 131
Found - Live Oak (now 12" diam.) S. 70° E 6.6 ft. Scribing visible on partly exposed face.
Live Oak (now 9" diam) S. 75° W. 14.5 ft. Faint scars visible.
Live Oak (now 12" diam) N. 22° W. 15.2 ft. Faint scars visible.
Live Oak (now 20" diam(N. 30° E. 21.8 ft. Faint scars visible.
All distances are slope dist.
Set - 3/4" iron rod.
New BTs: Rescribed:
20" Live Oak N. 30° E 21.8 ft. (slope dist) Mkd: "S 25 CS BT"
9" Live Oak S 75° W 14.5 ft. (slope dist) Mkd:"S 35 CS BT"
12" Live Oak N. 22° W 15.2 ft. (slope dist)Mkd:"S 26 CS BT"
Did not rescribe SE tree.
Corner lies on very steep SW slope.