

**Douglas County Surveyor's Record of
Government Corners Renewed**

T. 32 S. T. S. R. 5 W. R. W. W. M.

KOKE-CHAPMAN CO., EUGENE, ORE. 21881

135

Witness Point (Line Tree) common to Secs. 1 & 6, T32,R5&6W.
Orig.- 36" Sugar Pine Line Tree at 52.08 ch. orig. meas. (now 51" stump, 1 notch exposed on S. side, others probably cut off when logged.
Witnessed- 19" Fir bears N.56°W. 63.1 ft.; scribed WP S1 BT.
11" Fir bears N.24°E. 25.2 ft.; scribed WP S6 BT.
7" Fir bears N.27°E. 10.6 ft.; scribed RS 359.
Ore. St. Forestry Dept. metal location poster on 5" Fir N.60°W. 8.2'.
Refer to C. S. File No. 49/92

Arnold G. Gibson
July 1964
C.S. File No. 51/264

136

C - W 1/16th Corner Section 26.
See information in C. S. File 45/227, 1956 renewal.
Found - Car Axle, from which:
New BT's: 20" Cedar N.39,20'W. 114.4 ft.
14" Fir S. 2,12'E. 61.7 ft.

George J. Wenderoth
For-James G. Wells
C. S. File No. 54/ 5

June 1965

137

Section Corner to Sections 4 - 5 - 8 - 9.
Found - Orig. Madrone, now 25", S.57°W. 75 lks., shows face.
Orig. Fir, now 35", N.11°W. 40 lks., shows rotted face.
1962 BT's. 10" Fir N.66°E. 11.9 ft., full scribing visible.
10" Fir S.12°E. 31.0 ft., full scribing visible. (has been cut)
14" Fir N.13½°W. 70.3 ft., full scribing visible.
No trace of S. W. Tree.
Brass Cap lost in logging operation:
Set - Brass Cap at Cor. Mkd: County Surveyor's Office, 1965

Bruce R. Rogers, Deputy
M. Stone & Wm. Stoffel
C. S. File No. 53/52
June 25, 1965

S 5 | S 4
S 8 | S 9 T32S-R5W

138

Cl. Corner to Sections 5 and 6, only, T32-5W.
Found - Iron Pipe, Ren. #114A & Cadastral Brass Cap, 1962.
30" Fir, now Stump, S. 39° E. 21.8 ft.
8" Yew, now stump, S. 63° W. 25.7 ft.
23" Cedar N. 8° 53' W. 36.0 ft. scribed CC S6 CS BT.
7" Fir S. 70½° W. 38.5 ft. scribed T31S R5W S6 H BT.
New BT: 12" Hemlock S. 78½° E. 27.5 ft. scribed T32S R5W S5 CS BT.
Note - The corner of Sections 31/32 only, T31-5W. bears W. 114.7 ft.
June 3, 1966

John M Powell & Crew
C.S. File No. 54/25

139

Township Corner common to R. S 36 | S 31 R T 31 S
6W S 1 | S 6 5W T 32 S

Orig. - No evidence of Orig. record corner post or BT's. could be identified.
Found- Fir described in Ren. #126, Dep. Co. Surv., George J. Wenderoth, April 11, 1959, stating that a 52" Fir with scribes on N. face was found, near which the Twp. corner was set by a straight line intersection of lines N. & S and E & W. The Sugar Pine line trees N & S were not used for control, nor was the S½ corner of S36, R1 which has been subsequently identified and restored.
The above 52", now 55" Fir has very old bark on top, T32 R6W S1 BT", facing N. 15° E. They are similar in size, shape & style to other Lake & Hyde work in this area.
The Orig. line blazes were found on the E. of this tree. Line blzes were found S. & the dist. to the large top matches the record. The E & W creek at 2.00 ch. is in place. (Approx. 60 ft. W. & on a line N. across the creek to the main ridge numerous blazes were found. None of them were exposed. They appeared very old & ended N. of the Creek. Search at a point S. of these blazes & 2.00 ch. S. of the creek disclosed only a 40" Fir in the NW and a 16" Yew in the SW which did not match each other or the point. No scribes nor axe marks were found on either tree, although both were green.)
Restored - Set 1½" x 36" Gal. Iron Pipe with 3" Br. cap mkd. "Ore. St. Bd. of Forestry T31SR6W R5W S36 S31S6 S1 T32S 1966 RS 359", and from which a:
55" Fir bears S.15° W. 11.5 ft.; scribed T32 R6W S1 BT (Also scribes S6 CS BT by Wenderoth).
6" Fir bears N. 86° W. 54.5 ft.; scribed T31S R6W S36 BT.
4" Hemlock bears S. 58° E. 28.3 ft.; scribed X.
4" Fir bears N. 9° E. 19.0 ft.; scribed X.
4" Pipe bears West 13.3 ft.

Ore. St. Board of Forestry
Arnold G. Gibson
July 15, 1966
C. S. File No. 55/6

RE-RENEWED, SEE CORNER NO. #231

WENDEROTH'S
Wenderoth's