

Douglas County Surveyor's Record of  
Government Corners Renewed

T. 32 S. T. S. R. 5 W. R. W. W. M.

KOKE-CHAPMAN CO., EUGENE, ORE. 21881

Section Corner to Sections 7-8-18-17. 147  
Found - Orig. 24", now 37" D. Fir, S. 45° W. 25.7 ft., good bark scribe.  
Orig. 9", now 21" Laurel, N. 55° E. 38.9 ft., opened tree for scribing, "S".

Tree believed to be 40" Fir S. 45° E. slid down mountain.  
N. Trace of N. W. BT.

Set - Brass Cap at Cor. Mkd: County Surveyor's Office 1967  

T 32 S	R 5 W
S 7	S 8
S 18	S 17

New BT's: 11" D. Fir N. 53° E. 13.6 ft. mkd. T32S R5W S8 CS BT.  
24" D. Fir N. 82° W. 34.6 ft. mkd. T32S R5W S7 CS BT.  
30" D. Fir S. 12° E. 45.2 ft. mkd. T32S R5W S17 CS BT.

RE-RENEWED. CORNER NO. #214

Section Corner to Sections 8-9-16-17. 148  
Found - Axle at Section Corner, See Ren. #101.

18" Alder, now stob, S. 40½° W. 65.5 ft., scribe visible "T".  
10" Yew, now down, S. 32½° E. 32.6 ft., scribe vsible.  
14" Fir, now down, N. 43° E. 84.8 ft., shows scar.  
6", now 9" Fir, N. 15½° W. 33.7 ft., shows good scar.

New BT's: 10" D. Fir N. 9° E. 36.2 ft. mkd. T32S R5W S9 CS BT.  
10" Hemlock S. 85° W. 30.1 ft. mkd. T32S R5W S17 CS BT.  
24" Maple South 41.0 ft. mkd. T32S R5W S16 CS BT.

Note - This corner lies approx. 65.0 ft. N. of creek and 140.0 ft. south of logging road.

3/92 FO. OK  
BY A. RAMBO  
M 114-78

Section Corner to Sections 26-27-34-35. 149  
Found - 1½" Iron Pipe at Corner, See Ren. #34.

24", now 27" Fir, S. 54½° W. 104.8 ft., shows good scar.  
28" Pine, now dead, N. 42° W. 51.6 ft., scribe visible "S27BT".

New BT's: 10" Pine N. 21½° W. 35.8 ft. mkd. T32S R5W S27 CS BT.  
13" Pine N. 33° E. 43.5 ft. mkd. T32S R5W S26 CS BT.  
8" D. Fir S. 50½° E. 10.8 ft. mkd. T32S R5W S35 CS BT.

Note - This corner lies 150.0 ft. west of Quinnes Creek Road & 1.5 ft. North of E.-W. fence line.

Comp. FO. OK  
1/14/11 W. ZIMMERMAN  
M 87-12  
(FO. AS N. 45° E.)

FO OK BY R. Temple  
2/94 M 120-35  
FOR superior Lumber

John M. Powell  
Frank Jones & Joe Brady  
July, 1967  
C. S. File No. 53/52

¼ Corner to Sections 34 and 35. 150  
Found - Orig. 8" D. Fir, now 19" Stump, N. 80° W. 9.2 ft., has been opened, faint scribe visible.

Unrecorded 2" I. Pipe at ¼ corner. See C.S. 45/54  
8" D. Fir, now Stump 12", N. 18° E. 10.6 ft. (Record N. 80° E.)  
Opened Stump for scribe "T". Ring count places this tree approx. 1910.

New BT's: 14" W. Fir S. 30° W. 21.0 ft. mkd. ¼ S34 CS BT.  
6" D. Fir S. 2° E. 10.0 ft. mkd. ¼ S35 CS BT.

Note - This corner lies 25.0 ft. west of power line.

Section Corner to Sections 27-28-33-34. 151  
Found - Orig. 18", now 22" D. Fir, N. 29° E. 41.6 ft., faint bark scribing, "S W 7".  
Orig. 20" Laurel, now down, S. 57° E. 12.5 ft., scribe marks visible but not legible.  
Orig. 40", now 48"-D. Fir, N. 10° W. 25.1 ft., faint bark scribing.  
No trace of S.W. Bearing Tree.

Set - Brass Cap at Cor. Mkd: County Surveyor's Office 1967  

T32S	R 5W
S 28	S 27
S 33	S 34

New BT's: 11" D. Fir S. 48° E. 27.8 ft. mkd. T32S R5W S34 CS BT.  
40" D. Fir Stump S. 27° W. 31.8 ft. mkd. T32S R5W S33 CS BT.  
15" Cedar N. 81° W. 49.9 ft. mkd. T32S R5W S28 CS BT.

¼ Corner to Section 30 and 31. 152  
Found - 1" Axle at Corner, Ren. #13.

11" Cedar, now 20", S. 62½° W. 82.5 ft., shows scribing in bark.  
No trace of N.W. BT.

New BT's: 16" D. Fir S. 41° W. 9.2 ft. mkd. ¼ S30 CS BT.  
12" D. Fir N. 84° E. 39.0 ft. mkd. ¼ S31 CS BT.

Note - Corner lies on top of small spur running N. W.