

Douglas County Surveyor's Record of
Government Corners Renewed

T. 32 S. T. S. R. 5 W. R.W.W.M.

KOKE-CHAPMAN CO., EUGENE, ORE. 21081

153

$\frac{1}{4}$ Corner to Sections 28 and 33.
Found - Orig. 40", now 48" Pine, N. $68\frac{1}{2}^\circ$ E. 68.0 ft., shows scar, Tree burnt out.
Orig. 28" B. Oak, now dead, S. 72° E. 52.8 ft., scribe visible "B".
No trace of Stone at $\frac{1}{4}$ Corner.
Set - Brass Cap at Cor. Mkd: County Surveyor's T32S R5W
Office S 28
1967 S 33
New BT's: 6" D.Fir S. 46° E. 6.1 ft. mkd. $\frac{1}{4}$ S33 CS BT.
7" D.Fir N. 70° W. 7.1 ft. mkd. $\frac{1}{4}$ S28 CS BT.
Note - This corner lies on steep, west slope.

154

Sec. Cor. to Secs. 30 & 31, T32-5W. & Sec. 25 & 36, T22-6W.
Found - Brass Cap, County Surveyor's 1958, See Ren. #115.
25" Cedar, now 27" N. 14° W. 69.5 ft., shows scribe. *Fd 8/90 M110-48*
10", now 12" Cedar, S. 34° W. 72.1 ft., shows scribe.
8", now 11" D.Fir N. 69° E. 80.1 ft., shows good face.
New BT: 18" D. Fir S. 87° E. 72.5 ft. mkd. T32S R5W S31 CS BT.
Note - This corner lies west edge of gas line.

155

Closing Corner to Sections 4 and 5 only, T33S, R5W.
Found - Bedrail at the approx. corner N. 54° E. 6.4 ft. from corner.
48", now 56" D. Fir Stump, S. $34\frac{1}{2}^\circ$ E. 87.1 ft., shows scribing "T".
No trace of other BT's. T 32 S
Set - Brass Cap at C.C. Co. Mkd: County Surveyor's S 5 | S 4 - R5W
Office T 33 S
1967
New BT's: 8" Hemlock S. 78° W. 28.5 ft. mkd. T33S R5W S5 CS BT.
10" Hemlock S. 21° E. 35.0 ft. mkd. T33S R5W S4 CSBT.
Note - This corner lies in middle of old cat road and 40 ft. west of small creek.

John M. Powell
Frank Jone & Joe Brady
July, 1967
C. S. File No. 53/52

156

$\frac{1}{4}$ Corner to Sections 12 and 13.
Found - 50" Dbl. Maple, now 50", S. 73° W. 194.7 ft., scribe visible. #197
36", now 38" Ash, N. 56° W. 173.8 ft., scribing visible, "S". Ren #32
Set - Brass Cap for Witness Corner Mkd: T32S R5W
County Surveyors Wit. Cor.
Office 20 ft. West to $\frac{1}{4}$ S 12
1967 S 13
New BT's: 10" Maple N. 48° E. 8.2 ft. mkd. W.C. $\frac{1}{4}$ S12 CS BT.
28" Ash N. 11° E. 38.7 ft. mkd. W.C. $\frac{1}{4}$ S12 CS BT.
No trees available in south quad.
Note - This true corner falls in Cow Creek 4.0 ft. from E. bank in 4' water.

RE-RENEWED, SEE CORNER NO.

157

$\frac{1}{4}$ Corner to Sections 14 and 13.
Found - 20", now 29" Maple, N. 72° W. 76.6 ft., scribing visible.
30", now 36" Maple, S. 32° E. 92.4 ft., tree opened, faint scribe visible, also new scribing visible "S CS BT". Ren. #4.
No trace of 8"x12"x14" Rock, old stake at $\frac{1}{4}$ Cor. Mkd: " $\frac{1}{4}$ ".
Set - Brass Cap at Cor. Mkd: County Surveyors T32S R5W
Office, 1967 $\frac{1}{4}$ S14 S 13
Bearing Trees are in good condition.
Note - This corner lies 4.0 ft. south of short E-W fence, approx. 100' which is post of corral.

158

Section Corner to Sections 11 - 12 - 13 - 14.
Found - $\frac{3}{4}$ " Iron Pipe at Corner marked., See Ren. #110.
8", now 10" R.Fir S. 51° E. 54.0 ft., shows good face.
10", now 12" D.Fir, N. 65° E. 15.0 ft., shows good face. #227
29", now 24" W.Oak N. 29° W. 29.0 ft., shows good face.
New BT: 8" W. Pine S. 88° W. 28.8 ft. mkd.: $\frac{1}{4}$ S14 CS BT.
Note - This corner lies at a N.E. fence corner in a Oak Grove.
August 9, 1967

RE-RENEWED, SEE CORNER NO.