

Douglas County Surveyor's Record of  
Government Corners Renewed

T. 32 S. T. S. R. 5 W. R.W.W.M.

KOKE-CHAPMAN CO., EUGENE, ORE. 21891

159

Section Corner to Sections 22 - 23 - 26 - 27.  
Found -  $\frac{1}{2}$ " I. Pipe approx. 2" underground. See Ren. #96. #190  
Orig. 8" D.Fir N. 30° E. 18.5 ft., Tree has been opened "8" visible.  
20" Cedar N.72°E. (Record N.81 15 E.) 93.8 ft., shows good scar.  
11" Cedar, now down, in creek.  
Set - Brass Cap at Cor. Mkd: County Surveyors T 32 S R 5 W  
Office S 22 | S 23  
1967 S 27 | S 26  
New BT's: 12" Cedar N. 80° W. 208.7 ft. mkd. T22S. R5W S22 CS BT.  
6" Dbl. Cedar S. 57° E. 86.0 ft. mkd. T32S R5W S26 CS BT.  
No good trees in S.W. Quad.

160

$\frac{1}{4}$  Corner to Sections 18 and 17.  
Found - Orig. 30"D. Fir, now 36" Stump, N.35°W. 5.7 ft., bark scribe vis.  
Orig. 72", now 74" Cedar, East 11.2 ft., no scribe visible.  
Set - Brass Cap at Cor. Mkd: County Surveyors T 32 S R 5 W  
Office, 1967 S 18 | S 17  
New BT's: 8" Cedar S.73 $\frac{1}{2}$ ° W. 38.2 ft. mkd.  $\frac{1}{4}$  S18 CS BT.  
Reblzd. & Rescrbd: 74" Cedar East 11.2 ft. mkd.  $\frac{1}{4}$  S17 CS BT.  
Note - This corner lies in partially cut south of logging road 300 ft.

161

$\frac{1}{4}$  Corner to Sections 3 and 10.  
Found - 25", now 28" D.Fir, N. 13° E. 38.3 ft., shows good scar.  
20" D.Fir, now windfall, S.41 $\frac{1}{2}$ ° W. 15.8 ft.  
G.L.O. Brass Cap, 1955, properly marked.  
New BT: 12" D.Fir S. 74° E. 46.0 ft. mkd.  $\frac{1}{4}$  S10 CS BT.  
Note - This corner lies 175.0 ft. west of ridge on west slope.

162

Sec. Cor. to Secs. 19 & 30, T32-5W. & Sec. 24 & 25, T32-6W.  
Found - 1 $\frac{1}{2}$ " Iron Pipe at Section Corner, See Ren. #40.  
16" W.Oak S.43°E. 37.6 ft., good scar.  
16" Pine N. 78° E. 29.2 ft., pitched-over face.  
22" Pine Stump, N. 75° W. 39.5 ft., scribe visible "BT".  
No trace of S.W. BT, skid road.  
New BT: 14" Laurel S. 87° W. 49.5 ft. mkd. T32S R6W S25 CS BT.  
18" Laurel N. 82° W. 71.8 ft. mkd. T32S R6W S24 CS BT.

163

Sec. Cor. to Secs. 18 & 19, T32-5W. & Secs. 13 & 24, T32-6W.  
Found -  $\frac{3}{4}$ " Iron Pipe, See Ren. #6, T32-6W.  
Orig. 32" D.Fir, now Stob, N.33°E. 19.8 ft., shows scribing.  
14" Cedar N.68 $\frac{1}{2}$ °E. 55.2 ft., scribed S18 with good face.  
34" Cedar S.12°W. 44.8 ft., scribed S24 with good BT face.  
Set - Brass Cap at Cor. Mkd: County Surveyors T32S R S 13 S 18 R  
Office 6 S 24 | S19 5  
1967 W W  
New BT's: 6" D.Fir N. 27° W. 7.0 ft. mkd. T32S R6W S13 CS BT.  
6" Maple S. 34° W. 33.6 ft. mkd. T32S R6W S24 CS BT.  
6" W.Fir S. 11° E. 25.4 ft. mkd. T32S R5W S19 CS BT.

164

$\frac{1}{4}$  Corner to Section 2 only, T33-5W.  
Found - 1 $\frac{1}{2}$ " Iron Pipe, 1 ft. underground and wood stake scribed, Ren. #3, T32-5W.  
20", now 24" D.Fir Stump, South 48.1 ft., opened for scribe #2".  
39" D.Fir S. 58° E. 42.2 ft., shows good scar.  
Set - Brass Cap at Cor. Mkd: County Surveyors T 32 S R 5 W  
Office  $\frac{1}{4}$  S 2 T33W  
1967  
New BT: 8" Laurel S. 69° W. 15.6 ft. mkd.  $\frac{1}{4}$  S 2 CS BT.  
Note - This corner lies at fence corner running south & east.

John M. Powell  
Frank Jones & Joe Brady  
August, 1967  
C.S. File No. 53/52