

Douglas County Surveyor's Record of
Government Corners Renewed

T. 32 S. T. S. R 5 W. R.W.W.M.

KOKE-CHAPMAN CO., EUGENE, ORE. 21881

Gary L. Langlitz, County Surveyors Office
P. Earle
C.S. 56/43
1/30/74

Sec. Cor. Secs. 5 & 4; & Secs. 32 & 33 of T31-5.
Found - HLM Cadastral 1962 Brass cap, lying on ground near uprooted tree. I remove cadastral marker and

189

Set - Brass cap cemented in drill hole at the base of a small rock outcrop at record bearing and distances from an original 12" now 24" D.Fir, bearing S.39°W., 64.7 ft. previously opened with scribing "2S 5W" visible. Brass cap mkd:

Douglas County Surveyors Office
1974

T 31 S R 5 W
S 32 S 33
S 5 S 4

from which:

- 14" D.Fir, bears N.11°E., 41.9 ft. (Rec. N.14½°E., 44.9 ft.) scribing visible in partially healed blaze.
- 16" D.Fir, down, bears S.30°E., 56.8 ft. (srec. S.38°E., 52.8 ft.) scribing T32S R5W S4 BT visible.
- 10" D.Fir, bears S.66°W., 45.3 ft. (rec. S65½°W., 40.9 ft.) with healed blaze.
- 14" D.Fir, down, bears N.50°W., 22.0 ft. (rec. N.41°W., 19.1 ft.) blaze & scribing visible.

New BT & bearing object:

An "X" chiseled in a vertical rock face bears S.24½°E, 58.6 ft. A 22" D.Fir, bears N.74°W., 45.4 ft. scribed "T31S R5W S32 CS BT"
Note: The NW O.B.T. called for in resurvey field notes, now down, bears approx N.38°W., 8 ft. (rec. N.31°W., 8.6 ft.)

JAN 75

Section Corner for Secs. 22, 23, 27 and 26.

190

Found - 1967 County Surveyor's brass cap on top of ground. Ren. #159
Orig. 8" D.Fir, now 21", N.30°E., 18.5 ft. with healed scar.
A 20" Cedar now 26", N.72°E., (Rec. N.81°15'E.) 93.8 ft. with well healed scar.
A 6" Double Cedar, now 8" S.57°E., 86.0 ft. scribe T32S R5W S26 CS BT visible.
A 12" Cedar, now 18", N.80°W., 208.7 ft. scribe T32S R5W S22 visible.

We also find 1/2" I.Pipe buried 1 foot under the surface.

Reset - Brass cap 26" in ground and placed 1/2" I.Pipe alongside, buried 1 foot.

We placed witness post 1 foot to south of cap.

This corner is on outside (east) of slight right hand corner across road from large barn.

Compass declination - 20° E.

March 16, 1975

191

1/4 Corner for Secs. 26 and 27

Found - 1 1/2" x 36" I. Pipe buried 30" in ground. Ren. #15

A 18" Pine now 30", N.30°W., 60.06 ft. Tree has been opened in past now nearly rehealed. No scribe visible.

A 20" Fir, now 28" North 44.88 ft. Scar plainly visible

Set - Brass cap on 1 1/2" x 30" I. Pipe 28" in ground marked:

COUNTY SURVEYORS
OFFICE
1975

T 32 S
R 5 W
S 27 S 26

RE-RENEWED, SEE CORNER NO. #228

We placed old 1 1/2" x 36" I.Pipe 30" in ground beside brass cap.

Compass declination - 20°E.

3/19/75

192

Sec. Corner for Secs. 27 and 28 only. (NE Cor. Sec. 28)

FD. 1983 BLM B.C.

Found - 3/4" I.P. Ren. No. 64

1/91 M112-23

Maple, 13" bears S.20°E., 52.0 ft. Scribe visible.

The northwest tree is down and dead.

New BT - D. Fir, 50", bears S.34°E., 35.0 ft. with a partley healed blaze, with many years of overgrowth. I placed a marked location poster on the North side of the tree.

Next Page

8/10/75

Gary Commons
P. Earle
Surveyors Office
3/16/
C.S. 57/21

Gary E. Commons
P. Earle
/19/75
S. 57/21

Richard L. Templin
For: Rogue Valley
Trees Inc.
Aug. 10, 1975
C.S. 58/64