

Douglas County Surveyor's Record of
Government Corners Renewed

T32

T. S. R 5

R. W. W. M.

KOKE-CHAPMAN CO., EUGENE, ORE. 21881

193

Center 1/4 for Section 28
Set - 5/8" Iron rod.
Scribed - 8" Madrone, N.54°E., 23.35 ft.
20" Y. Pine, N.32°W., 5.0 ft.
9" D. Fir, S.36°W., 30.06 ft.
12" Madrone, S.54°E., 20.07 ft.

FD OK PER HULL
MAY-81 C.S. 63-57

9/26/75

Max H. Hull
For: Allan Stumbo
Sept. 26, 1975
M 58 - 30
C.S. 58/70

Cor. of Section 19,30 T32-5 & Sec.24 & 25 T32-6 REN# 162
Found:-1 1/2" I.Pipe, firmly set at fence corner, fences running N,E,&S.
BT's -an orig. Bt, a 9" now 16" W.Oak bears S43°E,37.6ft.,with faint
scribe marks visible on previously opened blaze.
All other original evidence has been destroyed.
A 16" now 21" pine, now a stump- bears N78°E.,29.2ft.,scribed marks
visible. (REN. # 40)
A 14" now 16" madrone bears S87°W.,49.5ft., all scribes visible.See
Ren.#162
An 18" now 19" madrone bears N 82°W.,71.8ft.,(distance taken to east fork
of Twin-forked madrone.) All scribes visible.
We mark an additional BT:
A 10" madrone bears N 42°E.,13.2 ft.,scribed "T 32 S R5W S 19 CS BT" on
a double blaze. Compass Declination setting: 20° East 11/10/75

194

Gary L Langlit
Clell E Goodwin
A Vic Cangie'
M.Lenora Ladig
11/10/75
CS 57/39

1/4 Corner to Sections 35 and 36 See Ren. #165 and CS 45/54
Found - 1 1/2" I.P. at corner also laying along side I.P., a 1 1/2" X 28"
I.P. with brass cap marked: County Surveyor's Office

195

M. Lenora Ladig
Peter L. Earle
Douglas County
Surveyor's Office
April 8, 1976
CS 59/8

1/4 S35 | S36 *REN #165*
1967

From Which - An Orig. 6" now 9" Yew bears N42° E., 13.9ft. with "1/4 S36"
visible in good blaze. Tree is alive (BT is leaning to the
NE dist. and bearing taken from base of tree).
Found - 15" now 19" D. Fir bears N68°E., 60ft. with three blazes. "S3"
visible in upper blaze. Middle blaze well healed and "B" visible
in lower blaze.
No trace of other BT's.
Note - This corner lies on the East edge of old log deck. Found a 48"
log resting on a 30" log 2ft. over the I.P. making corner
unaccessable. Cut away logs corner is now accessable.
Set - At true corner point the 1967 D.C.S.O. Brass Cap stamped "1976"
above 1967 at bottom of cap.
1 1/2" I.P. on east side of cap
New BT's - A 6" W. Fir bears S70°E., 13.7ft. scribed "1/4 S36 CS BT" in
double blaze.
No suitable trees to the west.
Compass Dec. 20° East.

196

CE 1/16 Corner of Sec. 12.
Found - 5/8" Iron rod with plastic cap marked "Riley RS 705" See M 3 - 9
An I. Cedar, 24" now 29" bears S.66°W., 26.0 ft. to face and 27.2 ft. to
center. Tree blazed, partially opened "BT" visible. (Rec. Dist.
26.0 ft.)
A 10" I. Cedar, bears N.60°W., 38.0 ft. to face, 38.3 ft. to
center. (Rec. 38.3 ft.) Tree double blazed, visible scribing
"1/16 CS BT"

L. E. Monrean
P. L. Earle
Oct. 14, 1976
C.S. 59/24

Note: 1" Iron pipe lost when culvert replaced.

10/14/76

1/4 Corner for Secs. 12 and 13.
Found - A 50" Double Maple bears S.73 1/4°W., 194.7 ft. Tree partially
opened, scribe mark visible.
Ash tree in NW quad. has been pushed out by cat.
BT's scribed by Powell in Ren. #156 are in. As the left bank
of Cow Creek has erroded close to these trees, I do not
renew the corner as witnessed by these trees
Brass cap set by Powell not found.
Set - A witness corner 30.0 ft. east of 1/4 corner stamped:
"Douglas County Surveyor" T 32 S R 5 W
1976 W.C.

197

L.E. Monrean
P.L. Earle
M. Tompkins
Doug. Co. Surveyor
C.S. 59/24
Oct. 18, 1976

West 30.0 feet
To 1/4 S12