

**Douglas County Surveyor's Record of
Government Corners Renewed**

T. 32 S. T.S. R. 5 W. R.W.W.M.

KORE-CHAPMAN CO., EUGENE, ORE. 21881

<p>C O N T. - - - Gregory Quibell John Powell July 8, 1982 C.S. 61/36</p>	<p>(1/4 Cor. Secs. 11 & 14) 211 Accessories: P.P. & L. power pole #E3859 bears N.45°W., 42.1 ft. BT tags put on both new Bts. Sketch in C.S. file. 7/7/82</p>
<p>Lloyd D. Smith L.S. 1101 For: Or.State Forestry May 14, 1982 M 92 - 34</p>	<p>South 1/4 Section Corner for Sec. 36. 212 Set - Oregon State Bd. of Forestry 1-1/2" x 36" galv. I.P. with a 3" Bronze Cap, 32" in ground. New BTs - 36" x 3-ft. high stump bears N.46-1/2°E., 18.7-ft. 25" fir bears N.57°W., 80.9-ft. 4" Canyon Live Oak bears N64°E., 3.0-ft. 7/14/82</p>
<p></p>	<p>Center 1/4 Corner for Sec. 36. 213 Set - OSBF 1-1/2" x 36" galv. I.P. w/ 3" Bronze Cap, 30" in grnd. New BTs - 35" Sugar Pine bears N.29°E., 56.7-ft., YMLP. 29" fir bears N.67°W., 42.3-ft. 4" x 4" x 72" white painted cedar post bears S.48°E., 1.7-ft. Note: BT distances measured to face of BTs. 7/14/82</p>
<p>805 Gregory Quibell Deputy, Doug. Co. Surveyors Office Randy Smith John Powell November 29, 1982 C.S. 62/1</p>	<p>Section corner for Secs. 7, 8, 17 and 18 214 Found - 1967 County brass cap, properly mkd., buried by road fill. Cap was lying horizontal and out of place. Ren. #147 Orig. 24" now 37" fir which shows good bark scribe. 30" fir, Ren. #147, now 30" stump with good healed over blaze. 11" fir, Ren. #147, now stump which is out of place by approx. 30 ft. due to logging. Set - Using record distances from the fd. orig. BT and the 30" fir stump I reset the found brass cap. Found trees now bear: Orig. 24" now 37" fir bears S.43°W., 25.1 ft. (rec. S.45°W.) 30" fir stump bears S.11°E., 45.2 ft. (Rec. S.12°E.) Corner lies on very steep slope approx. 100 ft. below new road. I add marks "Reset" 1982" to brass cap. New BT's- 12" fir scribed "T32S R5W S7 CS BT" in double blaze bears N.9°W., 83.7 ft. 11" fir scribed "T32S R5W S8 CS BT" in double blaze bears N.82°E., 67.9 ft. Douglas County Surveyor Office Tags on all trees. 11/29/82</p>
<p>Larry E. Monrean, Deputy, Doug. Co. Surveyors Office J. Lundeen R. Smith Nov. 7, 1984 C.S. 62/21</p>	<p>1/4 Corner for Section 1; and Sec. 6 of T.32-4. 215 Found - 3/4" iron pipe with metal tag stamped "RE 3024". Ren. #114 12" fir, now 19" diam. fir snag 4 ft. tall, bears N.52 1/2°W., 34.1 ft. Scribing is visible, "1/4 2". (Rec. N.54°W., 34.3 ft.) 22" fir, now 24" diam. stump (tree down with scribing "RE 3024"), bears S.15 1/2°W., 44.0 ft. (rec.) Set - We reference iron pipe and replace with 2 1/4" brass cap on 1" x 30" pipe and mound rocks around monument. 3/4" iron pipe is buried alongside. Brass cap marked: Douglas County Surveyor T32S R5W 1/4 S1 S6 R4W 1984. New BTs - 11" incense cedar, center of base bears N.23 1/2°W., 57.6 ft. scribed "1/4 S.1 CS BT" on a double blaze. 12" maple, center of base bears S.58°W., 35.9 ft. and scribe "1/4 S.1 CS BT" on a double blaze. 12" maple, center of base bears S.34 1/2°E., 13.2 ft. and scribed "1/4 S6 CS BT" on a double blaze. 10" fir, center of base bears S.83°E., 25.0 ft. and scribed "1/4 S6 CS BT" on a double blaze. 11/7/84</p>
<p>Howard Johnstone L.S. #498 For: Roseburg Lbr. Co. March 13, 1985 C.S. 58/296</p>	<p>1/4 Corner for Sections 5 and 4 216 Found - 1962 Cadastral brass cap on iron pipe, OK. 8" fir, N.88 1/2°W., 11.9 ft. OBT rotten snag, scribe visible. 22" fir, N.65°W., 55.4 ft., resurvey BT, stump. 17" W. fir, N.18°E., 58.4 ft., resurvey BT, good scar. New BT - 10" W. fir, S.76°W., 17.0 ft. scribed "1/4 S5 BT" Corner is 150 ft west of road running N & S. 3/13/85</p>