

Douglas County Surveyor's Record of
Government Corners Renewed

T. 32 T. S. R. 5 R. W. W. M.

KOKE-CHAPMAN CO., EUGENE, ORE. 21881

Arthur Rambo LS 1086
For: Medford Corp. and
Silver Butte Timber Co.
March 1992
M 114 - 78
C.S. 63/141

1/4 Corner for sections 9 and 16. 232
Set - 5/8" x 30" rebar with 2" dia. alum. cap exposed 4" above ground
marked 'T.32SR5W S9 1/4 S16 LS1086'
Fd BTs- An indeterminate size heart of fir tree bears S.55°W., 3.3 ft.
to chaining notch, tree marked 1/4S BT (original tree)
An indeterminate size fir stump hole bears N.12°33'E., 43.3 ft.
to the center of stump hole. (original tree)
New BTs- 10" Fir bears N.0°14'W., 43.9 ft. marked '1/4S9' in upper face,
'BT' in lower face with 3/4" washer marked LS1086 Nailed to face.
10" Fir bears N.35°58'E., 28.2 ft. marked '1/4S9' in upper face
and 'BT' in lower face with a 3/4" washer marked LS1086
nailed to face.
9" Fir bears S.31°40'E., 22.4 ft. marked '1/4S16' in upper face,
and 'BT' in lower face with a 3/4" washer marked LS1086
nailed to face.
13 1/2" Fir bears S.12°52'W., 17.7 ft. marked '1/4S16' in upper face,
and 'BT' in lower face with a 3/4" washer marked LS1086
nailed to face.

4/28/92

233

1/4 COR TO SECS 22 & 23

Found - 3 1/4" Brass cap on a 2 1/2" O.D. Iron pipe protruding 5" above ground
(1983 BLM). U.S. DEPT. OF THE INTERIOR

T 32 S R 5 W

1/4

S22|S23

1983

BUR. OF LAND MANAGEMENT

BTs - 16" W. Oak now 32" dia., B. Oak with a fully healed single blaze,
bears N.63°W. 46.5', (agrees with rec) Ren #97.
18" Balm now 36" dia., 15' high cottonwood stump with a fully healed
blaze, bears S.82°E., 115.5' (agrees with rec) to be cut down
to ground in near future. Ren #97.
New Accessories -
7" dia., Chinese Elm double blazed & scribed "X BT", bears S.64 1/2°E.
12.2'.
Power Pole # "E 643", bears N.30 1/2°E. 53.4'.
14" dia., B. Oak double blazed & scribed "1/4 S22 CS BT", bears
N.11°W 79.5'.

Douglas Co. Surveyors
Randall Smith
Stephen Flause
7/13/94
CS 64/52