

Douglas County Surveyor's Record of
Government Corners Renewed

32 T. S. 6 R. W. W. M.

THESE CORNERS ARE IN T32S R4W

10

1/4 CORNER BETWEEN SECTIONS 7 and 18.
Set stake with Brick for corner. Found two O.B.T.s marked
An 18" Pine S.27°W., 20.0 ft. (O.B.T.)
An 18" Pine N.43°E., 45.6 ft.

THESE COR'S IN T32S R4W

11

1/4 CORNER BETWEEN 6 and 7.
Set Iron Pipe at location of original stake as pointed out and agreed upon in writing by Robert Payne, B. Neff, H. J. Wilson, K. H. Cooper and G. A. Pickett. Marked
A 12" Cedar S.51 1/2°W., 9.0 ft.
A 10" Cedar N.7 1/2°W., 178.7 ft.
No O.B.T.s to be found.

12

1/4 CORNER ON SOUTH SIDE OF SECTION 33.
Old stake in place. Set 1 1/2" x 48" Gal. Iron Pipe.
Marked new witness trees
A 30" Maple N.44°15'W., 584 lks.
A 12" Cedar S.31°00'W., 70 lks.

RE-RENEWED, SEE CORNER NO. 25-417

13

1/4 CORNER OF SECTION 32 and 33.
Old stake 2" iron pipe for corner. Marked new witness trees
An 8" Apple N.60°30'W., 56 lks.
An 8" Apple N.81 1/2°E., 60 lks.
The 24" Fir for section 4 and 5 bears S.79 1/2°E., 191 lks.

RE-RENEWED, SEE CORNER NO. 102

14

SECTION CORNER BETWEEN 14, 13, 23 and 24.
Location identified from two original B.T.s one dead and other partially so. Set 2" iron pipe for corner and visible, as described in original notes. 1 1/2" dia. and scribed O.B.T. N.55°W., 23 lks, Laurel 2 1/2" dia. T.32S., R.6W., S.14 C.S.B.T.
Chinquapin N.55°W., 59 lks. T.32S., R.6W., S.23.
Set Iron pipe for corner in mound of rock.

RE-RENEWED, SEE CORNER NO. 7

15

1/4 CORNER ON SOUTH SIDE OF SECTION 32.
Found 1 1/2" x 48" Galv. Iron Pipe at location of original
A 28" Fir N.54°18'W., 51.8 ft.

RE-RENEWED, SEE CORNER NO. 29

16

N.E. EXTERIOR "L" CORNER OF JOHN REDFIELD D.L.C. # 36.
Renewed from old B.T. which is in good shape. Set Iron Pipe 2" x 48" and remarked Original tree with B.T.

RE-RENEWED, SEE CORNER NO. #31

###(note)

1/4 COR. S. SIDE OF SEC. 33
1" I. Pipe set for cor. with the following B. T.'s marked.
24" Maple bearing N 44° 45' W 101.6 ft. dist.
20" Cedar bearing S 31° 47' W 46.2 ft. dist. (See Also #12)

RE-RENEWED, SEE CORNER NO. 25 17

1/4 COR. BET. SECS. 28-27
No B. T.'S. to be found. 1" I. P. said to be corner by J. K. Howard
Mkd. 28" W. Oak, S 87° 17' W 58.6 ft.
14" Madrone S 23° 15' E 53.0 ft.

RE-RENEWED, SEE CORNER NO. # 99 18

1/4 COR. BET. SECS. 26-27
Find 22" Oak with old blaze burnt out, use bearing N 58° W 39.6 ft. set temp. stake, find 10" stump N 49° W 9.9 ft., site of old B.T. Also measure North from top of ridge as per Govt. notes, 528 ft. Drive 3/4" I. Pipe for corner.
Marked 24" B. Oak, S 39° 08' E 51.6 ft.
10" W. Oak, S 29° 07' W 36.0 ft.

RE-RENEWED, SEE CORNER NO. # 99 18

SEC. COR. 19-30(R5W) 25-24 (R6W)
Found 2 old B. T. badly rotted, drove 1 1/4" I. P. for cor. marked 16" W. Oak, S 43° E 37.6 ft. (O.B.T.)
16" Pine N 78° 25' E 29.2 ft.
22" Pine N 75° 15' W 39.5 ft.
15" Fir S 25° 42' W 44.9 ft.

RE-RENEWED, SEE CORNER NO. # 92A

20

45/186
G. C. Stewart
L. Jenks
G. A. Pickett
B. Neff
W. Damewood
D. C. S.
H. Payne
T. Damewood
B. Neff
K. Cooper

H. I. Epstein
Co. Sur.
Wit.
B. A. Lane
J. H. Wolford
June 12, 1929.
OLD COR. REM.
Vol. 1 Pg 172

Ben B. Irvine
11-14-29
Wit.
T. E. Richardson
O. S. Henninger

G. Wenderoth
T. Richardson
Apr. 1942

F. C. Frear
W. E. Richardson
Jim Wolford
Aug. 1942.
G. Wenderoth
Dep. Cnty. Sur

George J. Wenderoth -
Deputy County Surveyor
September 1948

Same Surv.
Frank Loso -
Witness
Apr. 6, 1949

Fd 1/89
M. Hull
M107-49