

Douglas County Surveyor's Record of
Government Corners Renewed

32

T. S.

6

R. W. W. M.

South $\frac{1}{4}$ corner Sec. 33. 25
Found old B. T. 30" maple N.44°45'W., 154 lks. (see Ren.#s 12 & 17)
We reset $\frac{1}{4}$ corner by measure from old B.T. & by measuring from N. $\frac{1}{4}$ cor.
sec. 4, T 33 S, R 6 W., 219.12 feet.
Set Brass Cap mkd. $\frac{1}{4}$ S 33 on east fill slope.
Cross and B. O. scribed on conc. curb 4' North of end of West curb of
south bridge app. N.13°W., 74.8 feet dist.
Cross scribed on S.E. cor. of south pier. N.7°E., 100.5 feet.
Set witness corner on straight line between S. $\frac{1}{4}$ cor. of sec. 33, T 32 S,
R 6 W., and N. $\frac{1}{4}$ cor. of sec. 4, T 33 S, R 6 W., and 40.00 feet from
S. $\frac{1}{4}$ cor. of sec. 33.

RE-RENEWED, SEE CORNER NO. #171

10-3-67 - Cor. FOUND OK. J.M.P. 4/4/72 - See M 44-59
CS. 54/53

NW cor. of sec. 32. 26
Found $\frac{3}{4}$ inch iron rod in Md of rock. (see Ren #36)

NE corner of sec. 32. 27
Found Cedar plst, 2 BT's.
18 inch Fir, S. 30° E., 28.2 feet.
Madrone, N. 3° E., 41.6 feet.

N $\frac{1}{4}$ corner section 32. 28
Set by proportiona measurement.
Set B. O. post - 4 inches X 4 inches by 36 inches.
Scribed 2 BT's.
12 inch Fir, S. 2° E., 16.7 feet, mkd $\frac{1}{4}$ S 32 RE 2807.
14 inch B.O. N. 21 $\frac{1}{2}$ ° E., 13.6 feet, RE 2807.

South $\frac{1}{4}$ cor. Sec. 32. 29
Found $\frac{1}{2}$ inch iron rod and 2 B T's. See #s 1 & 15
28 inch Fir N. 24° 12' W., 31.8 feet.
Blazed and Scribed
6 inch Fir, N. 70° E., 10.2 feet.

$\frac{1}{4}$ cor. secs. 26 and 35. 30
Found 18 inch W. Oak - O. B. T. blazed and scribed, set by Briggs in 1873,
N. 28° 52' W., 293.9 ft. REN.#4
Set 1" iron pipe with brass cap marked $\frac{1}{4}$ S 26/35 Co. Surveyor's office 1953.
Blazed and scribed two trees
18" W. Oak, S. 78° 13' W., 35.4 feet, mkd $\frac{1}{4}$ S 26/35 CSBT.
18" W. Oak, S. 43° 38' E., 102.2 feet, mkd $\frac{1}{4}$ S 26/35 CSBT.

N. E. corner John Redfield D. L. C. No. 38. 31
Found 2" iron pipe. REN.#16
Found blazed O. B. T. - 36" W. Oak, N. 82° 39' E., 332.6 feet.
Blazed and scribed two new trees -
12" S. Oak, N. 88° 04' W., 48.7 feet, mk'd N.E. Cl 38 CSBT. FD. O.K. 3/73
12" W. Oak, N. 12° 06' W., 92.6 feet, mk'd N.E. Cl 38 CSBT. SEE RM 2-43

Int. L. corner of D.L.C. No. 38. 32
Found Yew wood post -
Set geared axle alongside.

Ext. corner DLC. No. 38. 33
Set 1" iron pipe with brass cap m'k'd D.L.C. 38 Co. Sur. Office.
Blazed and scribed 24" Maple, N. 82° 03' W., 63.8 ft. mkd Ex. cor. DLC 38 CSBT.
Set 5/8 inch iron rod in line on west edge of old pacific highway 57.05 ft.
from DLC corner.

S. E. corner D. L. C. 38. 34
Set 1" iron pipe on side of fill of relocated pacific highway for corner
mkd S. E. corner D.L.C. 38.
Found 5/8 inch iron rod on R/W P.O.C. 452+64.36, N. 5° 03' W., 337.3 feet.
Found 5/8 inch iron rod on R/W P.O.C. 455+97.75, N. 89° 14' 30" W., 263.0 feet.
Found 3" x 3" squared post N. 89° 14' 30" W., 59.4 feet.

B. Irving
J. Byron
R. Irving
Dec. 17, 1953
Sur. File 45/232

A. R. Evans
File 41/241

Corrs.
Found
BUT NOT
SET
BY
A.R. EVANS.

R. C. Grant
Wit:
A. R. Evans
M. E. Godfrey
F. S. Harris
For Claude Drake
File 41/241-244

A. R. Evans
File -
41/241

Ben B. Irving
James Byron
Ray Irving
December 21, - 24, 1953
Surveyors file 45/249

Douglas County Surveyor