

Douglas County Surveyor's Record of
Government Corners Renewed

32S T. S. 6W R. W. W. M.

KONE-CHAPMAN CO., EUGENE, ORE. 97196

THIS IS THE
N 1/4 COR
SEC 1
T33-7
RESERVED
1-19-95
J.C. DUSO

1/4 COR. BET. SECS. 36-1, T 32, 33 S

At corner set 2" iron pipe by proportional measurement, from which
11" Fir bears N 37° E 1.0 ft.
12" Fir bears S 69° E 27.8 ft.

Common?
NOT COMMON -
WHICH COR.?

35

(C.S. 401274)

Section corner to secs. 29, 30, 31 and 32.

This corner is monumented with an iron rod, 3/4 in. diam., firmly set in a mound of stone, it is locally used and accepted but there is no remaining evidence of the original corner monument. (See Plan #24)

36

At the corner point over the iron rod,
Set an iron pipe, 3 ft. long, 2 ins. diam., 28 ins. in the ground, mkd. RS33; and mark new bearing trees as follows:

- A madrona, 6 ins. diam., bears N.39°E., 73 lks. dist., mkd. T 32 S, R 6 W., S 29 RS33 BT.
- A fir, 6 ins. diam., bears S.8°E., 38 lks. dist., mkd. T32S, R6W., S32 RS33 BT.
- A fir, 11 ins. diam., bears S.64°W., 24 lks. dist., mkd. T32S, R6W S31 RS33 BT.
- A fir, 18 ins. diam., bears N.67°W., 29 lks. dist., mkd. T32S, R6W., S30 RS33 BT.

The geographic position of this corner is latitude 42°45'13"N., and longitude 123°26'50"W. The observed magnetic declination is 20°57'E.

1/4 sec. corner of sections 29 and 30.

Corner set at proportionate distance; there is no remaining evidence of the original corner.

Set an iron pipe, 3 ft. long, 1 1/2 ins. diam., 28 ins. in the ground, marked RS33; from which

- A fir, 16 ins. diam., bears N.13°E., 32 lks. dist., mkd. 1/4 S29 RS33 BT.
- A fir, 12 ins. diam., bears S.45°W., 19 lks. dist., mkd. 1/4 S30 RS33 BT.

37

Section corner to secs. 19, 20, 29 and 30.

The locally recognized and accepted cor. of sections 19, 20, 29, and 30 at corner of burned fences extending N., E., and S. The fence corner post is marked with incomplete burned scribe marks. There is no evidence of the original corner monument. I accept this position as the most acceptable evidence of the original corner.

38

Against the E. side of fence corner post, set an iron pipe, 3 ft. long, 2 inches diam., 28 ins. in the ground, mkd. RS33.

I mark new bearing trees as follows:

- A madrona, 6 ins. diam., bears N.84 1/2°E., 102 lks. dist., mkd. T32S, R6W S20 RS33 BT.
- A chinquapin, 6 ins. diam., bears S.57°E., 69 lks. dist., mkd. T32S, R6W., S 29 RS33 BT.
- A chinquapin, 6 ins. diam., bears S.48°W., 30 lks. dist., mkd. T32S, R6W S30 RS33 BT.
- A madrona, 6 ins. diam., bears N.38 1/2°W., 42 lks. dist., mkd. T32S, R6W S19 RS33 BT.

1/4 section corner to secs. 20 and 29.

Determined at the record bearing and distance from both old bearing trees.

At the corner point,

Set an iron pipe, 3 ft. long, 1 1/2 ins. diam., 28 ins. in the ground, mkd. RS33; from which the original bearing trees:

- A fir, 18 ins. diam., bears N.80°E., 48 lks. dist. with blaze burnt.
- A madrona, 18 ins. diam., bears S.54°E., 18 lks. dist. with blaze decayed.

39

And new bearing trees:

- An incense cedar, 14 ins. diam., bears N.17°E., 76 lks. dist., mkd. 1/4 S20 RS33 BT.
- A fir, 10 ins. diam., bears S.23°E., 46 lks. dist., mkd. 1/4 S29 RS33 BT.

Norman D. Price, Registered Surveyor No. 33.
Nov. 18, 1954 to May 7, 1955.
Done for Dollar and Patterson Co. Inc.
C. S. File No. 41/375.