

Douglas County Surveyor's Record of
Government Corners Renewed

32

T. S.

6

R. W. W. M.

KOKE-CHAPMAN CO., EUGENE, ORE. 97196

40

Center $\frac{1}{4}$ section corner to section 29.
Set an iron pipe, 3 ft. long, $1\frac{1}{2}$ ins. diam., 28 ins. in the ground at the intersection of the North & South and East & West centerlines, mkd. RS33; from which

A madrona, 8 ins. diam., bears N. $46\frac{1}{2}^{\circ}$ E., 51 lks. dist.,

mkd. C $\frac{1}{4}$ S29 RS33 BT.

A fir, 6 ins. diam., bears S. $36\frac{1}{2}^{\circ}$ E., 18 lks. dist.,

mkd. C $\frac{1}{4}$ S29 RS33 BT.

Norman D. Price - Registered Surveyor No. 33.
Nov. 18, 1954 to May 7, 1955.
Done for Dollar and Patterson Co. Inc.
C. S. File No. 41/375.

41

$\frac{1}{4}$ section corner to secs. 28 and 29.

Determined at the record bearing and distance from each old original bearing tree.

At the corner point,

Set an iron pipe, 3 ft. long, $1\frac{1}{2}$ ins. diam., 28 ins. in the ground, mkd. RS33; from which the original bearing trees:

The badly decayed stump of a black oak bears N. 89° E., 56 lks. dist.

An incense cedar, 28 ins. diam., bears S. 66° W., 57 lks. dist., with partial scribe marks on charred face of old blaze.

And new bearing trees:

A fir, 36 ins. diam., bears S. 38° E., 18 lks. dist.,

mkd. $\frac{1}{4}$ S28 RS33 BT.

A chinquapin, 6 ins. diam., bears S. 28° W., 49 lks. dist.,

mkd. $\frac{1}{4}$ S29 RS33 BT.

$\frac{1}{4}$ corner between secs 25 and 26.

Found original B. Oak, S. 31° W., 13.2 feet with scribe showing. #147

Set 1 inch Iron pipe. (Feb. 1966 - Set Brass Cap in place of Iron Pipe)

Marked:

22 inch B. Oak, S. $57^{\circ}33'$ W., 39.3 feet.

26 inch Cedar, N. $23^{\circ}39'$ W., 23.7 feet.

George J. Wenderoth
May, 1955.
C. S. File No. 46/141.

42

Witness corner for section corner to secs. 25, 26, 35 and 36.

Set by Lawrence No. 1543, 331.0 feet North of Corner.

Found $\frac{1}{2}$ inch Iron Rod and 20 inch Ash, S $59^{\circ}50'$ W., 20.9 feet marked 1543 B.T.

I Drive $\frac{3}{4}$ inch Iron Pipe over rod.

Mark:

8 inch Ash, N. $33^{\circ}40'$ W., 28.6 feet.

Section corner falls in deep water of Cow Creek. Witness corner is on bank above gravel bar.

N.F. 4/23/74 C.S. 56/49

43

Section corner to secs. 35 & 36. (Only)

Found both O. B. Ts.

Drive 1 inch iron pipe.

Scribe two trees:

An 18" Fir, N. $60^{\circ}33'$ E., 65.8 feet.

A 24" Fir, N. $33^{\circ}50'$ W., 33.9 feet.

This corner is 201.4 feet West of the corner to secs. 1 and 2, T 33 S,

R 6 W., which is also renewed. (See renewal under T 33 S, R 6 W).

George J. Wenderoth
August, 1955.
C. S. File No. 47/7.

44

Center $\frac{1}{4}$ corner to Section 32.

Set at intersection of lines run from S $\frac{1}{4}$ corner to N. $\frac{1}{4}$ corner and E $\frac{1}{4}$ corner to W $\frac{1}{4}$ corner.

Set witness corner since Center $\frac{1}{4}$ corner falls in Blevins yard. 126

Set iron pipe with brass cap for witness corner, 40.5 feet North of true center $\frac{1}{4}$ corner and Marked Wit. cor. C $\frac{1}{4}$ cor. S 32 40.5' S to C $\frac{1}{4}$ cor.,

T 32 S R 6 W County Surveyors Office 1956.

Blazed and Scribed two trees:

48 inch W. O., S. 47° E., 40.2 feet marked wit. cor C $\frac{1}{4}$ S 32 CS BT.

20 inch Cedar, North 87.8 feet marked wit cor C $\frac{1}{4}$ S 32 CS BT.

James W. Byron, Dep.
County Surveyor
December, 1955
C. S. File 47/42.

45

$\frac{1}{4}$ corner to secs. 31 and 32.

Found original BTs: 18" R. Fir, scribed $\frac{1}{4}$ S bears N. $21^{\circ}45'$ W., 23.1 feet and 18" Fir bears S. $62^{\circ}05'$ E., 8.6 feet. #110

An 18" R. Fir bears N. $15^{\circ}05'$ W., 27.8 feet.

Set an iron pipe with brass cap mkd. $\frac{1}{4}$ S 31/32 T32S R6W County Surveyors Office 1956.

46