

Douglas County Surveyor's Record of
Government Corners Renewed

T. 32 S. T. S. R. 6 W. R.W.W.M.

KOKE-CHAPMAN CO., EUGENE, ORE. 21881

65

Section Corner to Secs. 19 & 30, T32-6W. & Secs. 24 & 25, T32-7W.
Found - 14" Laurel N.20°W. 44 lks., had been prev. opened but found faint definite traces of scribe.
10" Laurel N.85°E. 23 lks., had been prev. opened but could find no scribing. Tree is down.
36" Fir Stump S.15°E. 28 lks., very badly rotted.
14" Laurel S.10°W. 38 lks., had been prev. opened & scribe removed. Found edge of old face. Location tag on this tree dated "1939".
Set - 1 1/2" x 36" Iron Pipe at Corner.
New BT's: 8" Madrone bears N.16 1/4°E. 30.4 ft. scribed S19 T32S R6W B.T.
8" Chinq. bears S.51 1/4°E. 36.5 ft. scribed S30 T32S R6W BT.
6" Madrone bears S.11 1/2°W. 49.0 ft. scribed S25 T32S R7W BT.
6" Chinq. bears N.88 1/4°W. 12.0 ft. scribed S24 T32S R7W B.T.

(SEE 1974 Blm Resurvey)

Wm. B. Paulin
Wit: Robert Kischel
Jan. 6, 1962
C. S. File No. 51/227

July 1962
M 23 - 14

66

North 1/4 Corner to Section 30.
After diligent search, I set corner by Prop. measurement.
Set - 1" x 36" Iron Pipe at Corner.
Mkd. 2 BT's: 6" Chinq. bears N.21°W. 16.4 ft. dist. mkd: 1/4 S19 T32S R6W BT.
8" Madrone bears S.27 1/2°E., 29.4 ft. Mkd: 1/4 S30 T32S R6W BT.

67

West 1/4 Corner to Section 30.
Found - Mound of Stone at corner. Also find 38" Fir bearing West 39 lks., very good scribe although core of tree rotten.
Burnt Pine Stump bearing N.42°E. 76 lks.
Find 1/4 marked on Set Stone in mound of stones.
Set - 2" x 36" Iron Pipe and Mkd:
New BT's: P. Pine 24" diam. bears S.88°30'W. 64.6 ft. mkd: 1/4 S25 T32S R7W BT.
Madrone 10" diam., bears N.72 1/2°E. 24.5 ft. dist. mkd: 1/4 S30 T32S R6W BT.

68

South 1/4 Corner to Section 30.
Found - 1 1/2" Iron Pipe at corner described by D. F. Thenno. Ren. #24
26" Sugar Pine Stump bears N.32°E. 9.2 ft. distance
12" Laurel Stump N.3°W. 34 lks. dist.
3" Canyon Live Oak bears S.32°E. 5.0 ft. scribed "1/4".
New BT's: 10" Fir bears N.4°W. 13.3 ft. dist. Mkd: 1/4 S30 T32S R6W BT.
8" Madrone bears S.15 1/2°E. 33.8 ft. dist. mkd: 1/4 S31 T32S R6W BT.

Wm. B. Paulin #552
For - Holly A. Hough
July 1962
C. S. File No. 51/239
Map File M 24 - 1

69

Center 1/4 Corner to Section 30.
Set - 1 1/2" x 36" Iron Pipe at Corner & Mkd:
New BT's: 11" Fir bears S.41°W. 8.8 ft. Mkd: C 1/4 S30 B.T.
6" Fir bears N.42°E. 20.9 ft. dist. mkd: C 1/4 S30 B.T.

70

1/4 Corner (Wit. Corner) North Side Section 4, T33S R6W.
(Corner washed away)
Set - 1" I. Pipe 38.8 ft. West on Twp. Line.
Scribed - 26" Maple S.35°04'W. 33.1 ft.
12" Maple S.32°45'E. 31.6 ft.
Set - 1" I.P. 76.8 ft. South on centerline of Section 4. FD. OK 1/64 N. ARMSTRONG 11/17-4
Scribed - 36" Maple S.24°06'E. 76.5 ft.
36" Cedar S.58°05'W. 84.8 feet.
Found - 12" Maple S.21°E. 27.1 ft. for the 1/4 corner, the only tree left. 10-3-67 - Cor. FOUND O.K. J.M.P. 5/1/63

Geo. J. Wenderoth
Dec. 21, 1962
C. S. 52/137
Map File M 24-44

TOWNSHIP CORNER
R6W S 36 S 31 R5W
S 1 S 6
T32S
RENEWED CORNER NO. 88

70-A

Set - lynch Iron pipe from which: Scribed - 52" Fir S.35°35'E. 13.6 ft.
12" Hemlock S.46°12'W. 32.2 ft.
16" Yew N.79°40'W. 97.4 feet.

Geo. Wenderoth
For C. & D. Lumber
Reported 2/14/64
C.S. File 49/92