

Douglas County Surveyor's Record of
Government Corners Renewed

T. 32 S. T. S. R. 6 W. R. W. W. M.

KOKE-CHAPMAN CO., EUGENE, ORE. 21881

Milo E. Godfrey, Deputy
Wm. Stoffel - Stone - Darby
May 6, 1964
C. S. File No. 49/91

Section Corner to Secs. 27 - 26 - 34 - 35.

Found - Black Oak dead Snag N.69°E. 63.4 ft., previously opened,
fragmentary scribing visible on rotted old face.

29" Bl. Oak N.85°W. 82.5 ft., shows good scar, tree nearly dead.

22" Bl. Oak S.61°W. 75.7 ft., good scribing visible.

33" Bl. Oak S.40°E. 61.4 ft. Opening at base of tree facing
corner, tree hollow.

Set - Brass Cap at Cor. Mkd: County Surveyor's T32S R6W $\frac{S27}{S34} \frac{S26}{S35}$
Office, 1964

New BT's: 21" D.Fir S.48°E. 9.0 ft. Mkd: T32S R6W S35 CS BT.

16" D.Fir N.21°W. 11.4 ft. Mkd: T32S R6W S27 CS BT.

19" D.Fir N. 3° E. 17.0 ft. Mkd: T32S R6W S26 CS BT.

16" D.Fir S.45°W. 2.1 ft., Mkd: T32S R6W S34 CS BT.

80

Arnold G. Gibson, Ore.St. Bd. of Forestry
Wit: M. Pounds
July 29, 1964
C. S. File No. 51/264

Wit. Point (Line Tree) common to Secs. 1 & 6, T32S; R5 & 6W.

Orig. - 36" Sugar Pine Line Tree at 52.08 Ch. orig. meas. (now 51" stump,
one notch exposed on S. side, other probably cut off when logged.

Witnessed - 19" Fir bears N.56°W. 63.1 ft.; scribed WP S1 BT.

11" Fir bears N.24°E. 25.2 ft.; scribed WP S6 BT.

7" Fir bears N.27°E. 10.6 ft.; scribed RS 359.

Ore.St.Forestry Dept. metal location poster on 5" Fir N.60°W. 8.2 feet.

81

$\frac{1}{4}$ Corner for Section 31 (south side).

Orig. - Post (missing, point is 3100 ch. W. of N. $\frac{1}{4}$ Sec. 6, from which a:

4" Laurel (Madrone) bears N.55°W. 59 lks.; now 15", cater rotter out.

4" Live Oak bears N.52°E. 27 lks. p now 14" stub with sprouts coming
up around edge.

Restored - Set 3" round by 5 ft. alum. painted Fir Post 18" in ground, from which:

13" Sugar Pine bears N.86°W. 49.5 ft.; scribed $\frac{1}{4}$ S31 BT.

4" Live Oak bears N.33°E. 67.0 ft.; scribed $\frac{1}{4}$ S31 BT.

12" Sugar Pine bears S.89°E. 25.8 ft.; scribed RS 359.

Ore.St.Forestry Dept. metal location poster on 12" Sugar Pine.

FD OK 8/90 M 112-14

82

$\frac{1}{4}$ Corner for Section 6 (north side), T33S R6W.

Orig. - Post (now missing, found recent post in place) from which a:

15" Fir bears S.59°W. 117 lks; now 49", scribes 14 visible.

3" Laurel (Madrone) bears S.33°E. 97 lks.; now 14" burnt stub,
log down hill.

Restoration by R.L.Templin (RE 3024) date unknown, Refer Map M 26 - 17.

Post (above) from which a:

12" Fir bears N.39°W. 5.0 ft.; scribes $\frac{1}{4}$ S6 RE 3024 BT visible.

Restored - Set $1\frac{1}{2}$ " x 36" galv. iron pipe with 3" br. cap mkd: "Ore.St. Bd. of
Forestry $\frac{1}{4}$ S6 1964 RS359", 33" in ground, & from which a:

15" Fir bears S.2° W. 35.8 ft.; scribed $\frac{1}{4}$ S6 BT.

12" Fir bears N.49°E. 12.3 ft.; scribed RS 359.

FD OK 8/90 M 112-14

83

George J.
Wenderoth, Dep.
C. S. File
No. 49/8

$\frac{1}{4}$ Corner between Sections 32 and 33.

Find - Ledge Rock N.45°W. 11.2 ft., "X" and "CS" cut in Rock.

Ledge Rock N.21°30'E. 40.8 ft., "E" cut in Rock. See Ren. #2 & #21

1 $\frac{1}{2}$ " I. Pipe badly bent. Remove & Replace with:

Set - Brass Cap at Cor. Mkd: County Surveyor's Office

$\frac{1}{4}$ Sec. 32 & 33 L.S.5

December 6, 1964

RE-RENEWED

84

Vernon "Ray"
Tracy
T. Connell
June 1965
C. S.
File
No. 49/91

$\frac{1}{4}$ Section Corner to Sections 6 and 7.

Found - Orig. 18", now 19" Pine, down. N.10°E. 35.6 ft., shows
" $\frac{1}{4}$ S BT" scribe on unhealed scar.

No trace of other Orig. BT.

Set - Brass Cap at Cor. Mkd: County Surveyor's T32S $\frac{1}{4} \frac{S 6}{S 7}$ R6W
Office, 1965

New BT's: 7" D.Fir N.20°W. 30.2 ft. Mkd: $\frac{1}{4}$ S 6 CS BT.

32" D.Fir S.58°E. 7.2 ft. Mkd: $\frac{1}{4}$ S 7 CS BT.

June 22, 1965

85