

Douglas County Surveyor's Record of  
Government Corners Renewed

T. 32 S. T. S. R. 6 W. R. W. W. M.

ROKE-CHAPMAN CO., EUGENE, ORE. 21881

86

Section Corner to Sections 5 - 6 - 7 - 8.

Found - Orig. 36" Fir, now 50", N.85°E. 19.8 ft., bark scribe visible.  
Orig. 36", now 58" Fir S.70°W. 21.1 ft., bark scribe visible.  
Tree blown down at N.12°W. 58.1 ft., but could not find any scribing.

Set - Brass Cap at Cor. Mkd: County Surveyor's Office, 1965

T32S	R6W	S 6	S 5
		S 7	S 8

New BT's: 50" Fir N.85°E. 22.6 ft. scribed T32S R6W S5 CS BT.  
53" Fir S.70°W. 22.5 ft. scribed T32S R6W S7 CS BT.  
48" Fir N.83°W. 64.4 ft. scribed T32S R6W S6 CS BT.

Note - No tree in S. E. Quad., clear cut. Corner is now cutting corner and about 300.0 ft. south of old cabin.

John M. Powell  
Joe C. Brady  
Sept. 24, 1965  
C. S. File No. 49/91

87

Sec. Cor. to Secs. 7 & 18, T32-6W. & Secs. 12 & 13, T32-7W.  
Found - 15" D.Fir, now 24" N.63°W. 47.0 ft., faint bark scribe.  
(Good Tree)

24" D. Fir, now 40" S.8°E. 11.9 ft., good bark scribe,  
"R6 S18". Tree is windfall.

No trace of other trees.

Set - 6" D. Fir S.76°W. 55.6 ft. scribed S13 CS BT.  
24" D. Fir N.63°W. 47.0 ft. scribed T32S R7W S12 CS BT.  
30" D.Fir S.85°E. 38.8 ft. scribed T32S R6W S18 CS BT.  
16" D.Fir N.72°E. 91.6 ft. scribed T32S R6W S7 CS BT.

Set - Brass Cap at Cor. Mkd: County Surveyor's Office, 1965

T32S

R7W	S 12	S 7	R6W
	S 13	S 18	

*Fd. OK 8/88  
G. LANG  
M106-64*

Sept. 24, 1965

88

Township Corner common to R. S 36 S 31 R T 31 S  
6W S 1 S 6 5W T 32 S

Orig. - No evidence of original record corner post nor bearing trees could be identified.

Found - Fir described in Ren. #70-A, C.S. File No. 49/92 by George J. Wenderoth, April 11, 1959, stating that a 52" Fir with scribes on N. face was found, near which the Township corner was set by a straight line intersection of lines N & S and E & W. The Sugar Pine Line trees N & S were not used for control, nor was the S $\frac{1}{2}$  Corner of Sec. 31, which has been subsequently identified and restored.

The above 52" (now 55") Fir has very old bark scribes "132 S6W S1 BT", facing N. 15° E. They are similar in size, shape and style to other Lake and Hyde work in this area.

Orig. line blazes were found on line East of this tree. Line blazes were found S. & the distance to the ridge top matches the record. The E & W creek at 2.00 ch. N. is in place. Approx. 60 ft. W. & on a line N. across the creek to the main ridge numerous blazes were found. None of them were exposed. They appeared very old & ended N. of the creek. A search at a point S. of these blazes and 2.00 ch. S. of the creek disclosed only a 400" Fir in the NW and a 16" Yew in the SW which did not match each other or the point. No scribes or axe marks were found on either tree, although both were green.)

Restored - Set 1 $\frac{1}{2}$ " x 36" Galv. iron pipe with 3" bronze cap mkd. "Ore. St. Bd. of Forestry T31S R6W S5W S3S1 S6S1 T32S 1966 Rs359", and from which a:

55" Fir bears S.15°W. 11.5 ft. scribed T32 R6W S1 BT (Also scribes S6 CS BT by Wenderoth).

6" Fir bears N. 86° W. 54.5 ft.; scribed T31S R6W S36 BT.

4" Hemlock bears S. 58° E. 28.3 ft.; scribed X.

4" Fir bears N. 9° E. 18.0 ft.; scribed X.

Wenderoth's  $\frac{3}{4}$ " Pipe bears West 13.3 ft.

Set - 4"x4"x72" white painted Cedar Post 2.0 ft. south of corner piep.

Oregon St. Forestry Dept. metal location poster on 55" Fir BT.

Also BLM poster on 36" Fir 150.0 ft. North on N. side of creek.

Oregon St. Bd. of Forestry  
Arnold G. Gibson  
Wit. Marvin Pounds  
July 15, 1966  
C. S. File No. 55/6

CORNER RENEWED