

Douglas County Surveyor's Record of
Government Corners Renewed

T. 32 S. T. S. R. 6 W. R. W. W. M.

see next pg.
for "A" #5

KOKE-CHAPMAN CO., EUGENE, ORE. 21891

89

John M.
Powell &
Crew
10/11/66
C. S.
File
No. 54/31

Sec. Cor. to Secs. 2 and 3, T32-6W. & Secs: 34 & 35, T31-6W.
Found - Org. 24", now 32" D. Fir, S. 41° E. 77.9 ft., shows good scar.
Orig. 30" D. Fir, now Snag, S. 38° W. 38.3 ft., scribe visible @ 2 S".
Orig. 20", now 34" D. Fir, N. 54° W. 31.0 ft., opened for scribe "BT".
No trace of N.E. BT.

Set - Brass Cap at Cor. Mkd: County Surveyors
Office
1966

T 31 S	R 6 W
S 34	S 35
S 3	S 2
T 32 S	R 6 W

New BT's: 15" D. Fir N. 28° W. 23.8 ft. mkd. T31S R6W S34 CS BT.
24" D. Fir N. 43° E. 30.5 ft. mkd. T31S R6W S35 CS BT.
16" D. Fir S. 25° W. 18.0 ft. mkd. T32S R6W S 3 CS BT.

FD. ok 2/85
O. Freeman
M 90-67
O.S. 2/11

90

1/4 Corner to Sec. 33, T31-6W. & Sec. 4, T32-6W.
Found - 12" Fir, now down & rotten, S. 55° W. 3.3 ft. found old scribe marks.
8" Fir, now 11", N. 60° E. 31.0 ft., shows very good face.

Set - Brass Cap at Cor. Mkd: County Surveyors
Office
1966

T31S	R6W
S 33	
S 4	T32S

New BT: 26" D. Fir S. 88° W. 49.4 ft. mkd. 1/4 S & CS BT.
P.K. Nail in rock, west 3.6 ft.

Note - This corner lies on very steep, north slope, 2.5 ft. west of
rocky point about 12 ft. high.

FD. ok 2/85
O. Freeman
M 90-67
O.S. 2/11

91

Sec. Cor. to Secs. 32 & 33, T31-6W. & Sec. 5 & 4, T32-6W.
Found - Orig. 5", now 9" Laurel, N. 42° E. 21.1 ft., shows old scar.
Orig. 18, now 47" Fir, S. 34° E. 21.7 ft. Tree has been opened
but badly burned.

24" D. Fir, N. 6° W. 35.0 ft., pitched over, scribing visible.)
16" D. Fir, S. 63° E. 38.0 ft., pitched over, scribing visible) **Rewn. #63**
14" D. Fir N. 54° E. 87.3 ft., pitched over, scribing visible)
Mound of Stone at Section Corner.

Set - Brass Cap at Cor. Mkd: County Surveyors
Office
1966

T31S	R6W
S 32	S 33
S 5	S 4
T32S	R6W

All BT's. in good condition.

1/4 Corner to Sec. 36, T31-6W. & Sec. 1, T32-6W.
Found - Sq. Stake at 1/4 Corner. See Ren. #54.
8" Live Oak N. 5° W. el. 1 ft., scribe visible "1/4 S CS BT".
12" Live Oak N. 64° W. 17.3 ft., scribe visible "1/4 S CS BT".

Set - Brass Cap at Cor. Mkd: County Surveyors
Office
1966

T31S	R6W
S 36	
S 1	
T32S	R6W

Note - BT's. all O.K. Corner lies E. of ridge,
top about 297.0 ft. & W. of new road 150 ft.

92

1/4 Corner to Sec. 32, T31-6W. & Sec. 5, T32-6W.
Found - 16", now 21" Fir, N. 11° E. 27.7 ft. Tree had been opened,
scribe visible "B". Broken Top.

5", not 7" Fir, S. 42° W. 23.1 ft., scribe visible "1/4 S".
Set - Brass Cap at Cor. Mkd: County Surveyors
Office
1966

T31S	R6W
S 32	
S 5	
T32S	R6W

New BT's: 22" D. Fir N. 19° E. 38.0 ft. mkd. 1/4 S32 CS BT.
17" D. Fir S. 27° W. 41.3 ft. mkd. 1/4 S 5 CS BT.

93

John M. Powell
Frank Jones & C. Stone
November, 1966
C. S. File No. 54/31