

Douglas County Surveyor's Record of
Government Corners Renewed

T. 32 S. T. S. R. 6 W. R.W.W.M.

KOKE-CHAPMAN CO., EUGENE, ORE., 21881

107

Section Corner to Sections 7 - 8 - 17 - 18.
Found - Orig. 40", now 48" D. Fir, S. 50° E. 21.8 ft., shows no scribe.
Orig. 40", now 58" D. Fir, N. 25° W. 15.2 ft., shows bark scribe.
No trace of N. E. or S. W. Bearing Trees.
Set - Brass Cap at Cor. Mkd: County Surveyor's Office 1967
T32S R 6W
S 7 S 8
S 18 S 17
Rescribed BT: 48" D. Fir S. 50° E. 21.8 ft., scribed "T32S R6W S17 CS BT".
New BT's: 42" D. Fir S. 72° W. 27.5 ft. mkd. T32S R6W S18 CS BT.
6" Tan Oak N. 35° E. 17.3 ft. mkd. T32S R6W S8 CS BT.
Note - This corner lies 150.0 ft. north of a creek.

*Fd. OK
3/8/89
G. Lane
M108-16*

MICROFILM TO HERE 10/67 - -

108

1/4 Corner to Sections 2 and 3.
Found - 14", now 31" D. Fir, East 21.8 ft., shows scar.
12", now 28" D. Fir, N. 80° W. 13.2 ft., Tree had been opened, "B" and part of "T" visible.
Set - Brass Cap at 1/4 Cor. Mkd: County Surveyor's Office, 1967
T32S R 6W
1/4 S 3 S 2
Reblazed & Rescribed: 28" D. Fir N. 80° W. 13.2 ft. mkd. 1/4 S3 CS BT.
31" D. Fir East 21.8 ft. mkd. 1/4 S 2 CS BT.
Note - This corner lies on south side of a sharp ridge running East and approx. 230.0 ft. north of creek running N.E.

RE-RENEWED SEE CORNER NO. #165

109

1/4 Corner to Section 28 and 33. *FND OK 1-91 M111-34*
Found - Opened base of 27" D. Fir to find R.R. Spike which is on north side of 27" D. Fir. See Ren. #9.
30", now 32" B. Oak S. 42 1/2° W. 39.3 ft., opened for scribe "T".
No trace of W. Oak S. 52° W. in S.W. nor in any other quad.
New BT: 18" D. Fir N. 18° E. 9.5 ft. mkd: 1/4 S28 CS BT.
Note - This corner lies S.W. of fence corner running S. & W. about 15.0 ft.

110

1/4 Corner to Sections 31 and 32.
Found - County Surveyor's Brass Cap, 1955, properly marked. *REN. #46*
18" D. Fir, now stob 12' high, N. 21 1/2° W. 23.1 ft., Tree has been opened, scribe visible "4 S".
18", now 19" D. Fir, N. 15° W. 27.8 ft., pitched over, scribe visible
Orig. 9", now 20" D. Fir, S. 63° E. 8.6 ft. (Record S. 67° E. 9.2 ft.) shows scar.
Reblazed & Rescribed: 20" D. Fir S. 63° E. 8.6 ft. mkd. 1/4 S32 CS BT.

111

Section Corner to Sections 35 and 36 only, T32-6W.
Found - 1" Iron Pipe at Corner. See Ren. #44.
18" D. Fir, now snag, N. 60 1/2° E. 65.8 ft. scribe visible "S BT".
24", now 25" D. Fir, N. 34° W. 33.9 ft., shows good scar.
New BT: 18" D. Fir N. 84° E. 34.3 ft. mkd. T32S R6W S36 CS BT.
Note - This corner lies on north slope approx. 20.0 ft. above old skid road. Also 201.4 ft. west of C.C. of Sections S 2/S 1 T33S R6W.

RE-RENEWED SEE CORNER NO. #176

112

Township Corner
R T 31 S R
7 S 36 S 31 6
W S 1 S 6 W
T 32 S
Set - 5/8" x 30" Rod & Alum. Cap by double proportionate distance.
Scribed: 16" D.F. S 28° W. 42.3 ft - 8" D.F. S. 43° E. 44.6 ft.
9" D.F. N. 57° W. 10.2 ft. - 9" D.F. N. 72° E. 56.2 ft.

RE-RENEWED SEE CORNER NO. #172

113

1/4 Corner to Sec. 31, T32-7W. and Sec. 6, T32-6W.
Found - Original Bearing Trees. Set - 1" x 30" I. Pipe.
Scribed: 5" D.F. N. 88 1/2° E. 26.7 ft. and 5" D.F. N. 81° W. 42.7 ft.

114

1/4 Corner to Sec. 6, T32-6 and Sec. 31, T31-6W.
Set - 1 1/2" I. Pipe in Rock Mound.
Scribed - 18" I. C. S. 65° W. 22.3 ft.
14" D. F. N. 43° W. 9.9 ft.

John M. Powell
Frank Jones & Joe Brady
October, 1967
C. S. File No. 54/53

Howard W. Johnstone
For Roseburg Lbr.
February, 1969
Map File M 33 - 49