

Douglas County Surveyor's Record of  
Government Corners Renewed

T. 32 S. T. S. R. 6 W. R. W. W. M.

KOKE-CHAPMAN CO., EUGENE, ORE. 21881

1/4 Corner to Section 18 and Section 19.

115

Found - Unrecorded 5/8" I. Rod.

Orig. 14", now 28" Fir, alive, S.62°W. 14.5 ft., old bark scribe "1/4 SBT", recent bark scribe "1/4 S19 BT", we add C.S.

Live Oak Stool at approx. locus of N. E. BT.

Set - Brass Cap at Cor. Mkd: County Surveyor's Office 1969 T32S R6W 1/4 S 18 S 19

*pd. ok 3/89  
M100-16  
G. Lane*

Reset I. R. alongside Brass Cap, this corner lies on very steep, rocky, southerly slope with scattered large fir & dense live oak.

New BT: 7" D. Fir N.58°E. 19.6 ft. mkd: "1/4 S18 CS BT".

4/4/69

116

1/4 Corner to Sec. 31, T32-6W. and Sec. 36, T32-7W.

Found - Unrecorded 1" Iron Rod 1.0 ft. south of Brass Cap.

"+" on log for 1/4 Corner.

10" Pine, now 34" Stob, N.70°E. 16.5 ft., opened at a different time for scribe, scribe found, "S" 1/".

36" D. Fir, now burnt stump, N.52°W. 17.2 ft.

Set - Brass Cap at Cor. Mkd: County Surveyor's Office, 1969 R T 32 S R 7W S 36 S 31 6W

New BT's: 11" Laurel N.16°W. 10.9 ft. mkd: "1/4 S36 CS BT".

17" S. Pine N.78°E. 34.6 ft. mkd: "1/4 S31 CS BT".

This corner lies about 50 ft. south of Robert Dollar Road.

Vernon "Ray" Tracy and Crew  
Buzz Pounds, State Forestry  
C. S. File No. 54/53

John M. Powell & Crew  
June 25, 1969  
C.S. File 54/53

1/4 Corner to Sections 7 and 18.

117

Set - Ore. St. Bd. of Forestry 1 1/2"x36" Galv. I. Pipe with 2" Bronze Cap.

12" Fir S.47 1/2°W. 27.6 ft. to face (RS) 359)

38" Fir N. 2 3/4° E. 64.0 ft. to face (yellow metal location poster in ground)

4x4x72" white painted cedar post S.W. 1.0 ft.

May 15, 1969

*pd. ok 8/88  
M100-16  
G. Lane*

Arnold G. Gibson  
C.S. File No. 55/122

1/4 Corner to Sec. 12, T32-7W. and Sec. 7, T32-6W.

118

Set - 5/8" Iron Rod & Alum. Cap by proportionate measurement.

Bearing Trees: 12" D. Fir N. 69 3/4° W. 24.1 feet.

8" D. Fir N. 43 1/4° E. 9.5 feet.

Sec. Cor. to Secs. ~~7 & 18~~ <sup>7-6</sup> T32-6W. and Secs. ~~12 & 7~~ <sup>12-7</sup> T32-7W.

119

Set - 5/8" Iron Rod with Alum. Cap.

Bearing Trees: 10" D. Fir N. 68° E. 7.0 feet.

10" D. Fir S. 7 3/4° E. 37.2 feet.

9" D. Fir S. 45° W. 6.2 feet.

21" D. Fir N. 35 1/2° W. 27.7 feet.

Howard W. Johnstone  
For Rsbrg. Lumber  
Feb. 1970 M 39 = 14

~~1/4 Corner to Sections 29 and 30. Wrong Twp. & Range.~~

120

~~Found - Cast-iron Brass Cap on this corner is intact.~~

~~28" D.F., N. 88°45'E. 39.5 ft., in good condition, now slightly covered with road fill.~~

~~46" D.F., S. 04°W. 59.0 ft., removed for road construction.~~

Scribed: ~~7" D.F., N. 10° W., 34.9 feet., mkd: 1/4 S T32S R6W RS841 BT.~~

7/27/70

Ronald A. Brandt  
For: Robert Dollar  
C.S. File No. 55/129

1/4 Corner to Sections 16 and 21.

121

Found - 36" Incense Cedar, S.20°E. 25.74 ft. mkd: 1/4 S (partly visible) & BT (visible), bark scribed.

36" I. Cedar, N.56°W. 30.40 ft., no scribing, burned out by ground fire.

Monumented: 1 1/2" x 32" Galv. Iron Pipe.

Scribed: 20" W. F., N. 52°30'E. 23.5 ft. mkd: 1/4 S, S16 T32S R6W RS841 BT.

Tree measurements are current at breast height.

7/27/70

Brandt, Ronald A.  
For: Robert Dollar Co.  
C. S. File No. 55/129