

Douglas County Surveyor's Record of
Government Corners Renewed

T. 32S. T. S. R. 6 W. R.W.W.M.

KOKE-CHAPMAN CO., EUGENE, ORE. 21881

Section Corner, Sections 2-3 (33-6)

130

Set - 1" I. Rod 4" high from which bears -
7.5" Madrone, South, 9.10 ft. mkd. S2 33-6 PS841 BT.
6.8" D. Fir, S. 87°02'W. 38.08 ft. mkd. S3 33-6
PS 841 BT.

and fenceline is 1.5 ft. No. of Iron Rod.

May, 1973

North 1/4, Sec. 3 (33-6)

131

Set - 1"x36" I. Rod 12" deep in Sether field from which
bears -

1"x36" I. rod 4" high, N. 46°55'34"E. 63.90 ft.

1"x36" I. rod 4" high, N. 45°47'26"W. 49.59 ft.

both set in a fence line.

1 1/2" I. Pipe (c.s. 42/327) N. 89°31'26"W. 196.15 ft.

Fence Line 38.50 cft. IN. of I. rod at corner.

May, 1973

Sec. Corner, Sec. 3 - 4 (33-6) Sether Field.

132

Set - 1"x60" I. Rod, 12" deep from which bears -

1"x36" I. rod 4" high, N. 61°32'27"W. 22.96 ft. at South
side of small cherry tree and

1"x36" I. rod 4" high, N. 44°15'33"E. 56.26 ft. at South
side of a cedar fence post and

1" I. pipe 15" deep, N. 89°30'59"W. 209.68 ft. set by
Nelson, 1933.

May, 1973

~~1/4 Corner, Sec. 3 - 4 (33-6) in corner of Tunnel Road.~~

133

~~Set - 12"x1/2" sq. shank bridge spike, 1 1/16" Rd. head,
flush in asphalt surface from which bears~~

~~1"x36" I. rod 4" high at SE side of 19.4" P. Pine,
N. 33°59'W. 34.5 ft. and~~

~~10" white oak, N. 62°20'E. 29.75 ft. mkd.~~

~~1/4 PS 841 B.T.~~

May, 1973

~~Center 1/4 Corner.~~

134

~~Set - 1"x36" I. rod 4" high from which bears -~~

~~20.5" D. fir, N. 80°09'39" W. 41.57 ft.~~

~~mkd. C 1/4, S 4 PS 841. B.T. T. 33-6 W.~~

~~13.0 D. fir, N. 08°19'21"E. 39.86 ft.~~

~~Mkd. C 1/4, S 4 PS 841 B.T.~~

Section Corner for Secs. 4, 5, 8 and 9

135

Found - 1967 County Surveyors brass cap properly mkd. out of the
ground. Ren. No. 101

I add - the markings "1974" to the brass cap and set it at the rec-
ord bearing and distance from an orig. 36" now 46" pine
snag BT with scribing "2 S 5 T" visible on previously
opened blaze.

Note - corner Ren. #101 calls for bearing to this NW orig. pine
BT to be N. 48°W. The orig. survey notes call for N. 40°W.
I set the brass cap at the orig. bearing and distance of
N. 40°W., 23.1 ft. from this pine BT.

Found - 36" now 46" pine snag bears N. 40°W., 23.1 ft. with marks
showing as noted above.

5" now 6" Madrone bears S. 74°W., 20.0 ft. (S. 74°W., 24.2 ft.
Ren. #101) with scribing "S 8 BT" visible.

6" now 7" chinquapin bears S. 59 1/2°E., 14.2 ft. (S. 52 1/2°
E., 12.2 ft. Ren. #101) with scribing "T32S R6W S9 CS BT"

16" now 18" D. Fir bears N. 62°E., 23.6 ft. (N. 58°E., 21.8 ft.
Ren. 101) with scribing "2 6 W S4 BT" visible.

New BT - 22" D. Fir, bears N. 29 1/2°W., 62.2 ft. scribed "T32S R6W
S5 CS BT"

Ronald A. Brandt
For: Robert Dollar Co.
C.S. 55/294 Map File M 49 - 21

Gary Langlitz, Surveyors Office
P. Earle
C.S. 56/49
3/28/74