

Douglas County Surveyor's Record of
Government Corners Renewed

T 32 T. S. R 6 R. W. W. M.

KOKE-CHAPMAN CO., EUGENE, ORE. 21881

140

Center 1/4 Corner for Section 8
Set - Oregon State Board of Forestry 1 1/2" x 36" Gal. I.P. with
3" Bronze cap.
BT's - 20" Fir N.13°E., 109.0 ft. with yellow metal location poster
RS 359
5" Fir S.23°E., 55.3 ft.
4"x4"x72" White painted cedar post N.31°W., 3.7 ft.

Arnold G. ...
State of Oregon, Department of
Forestry
October 15, 1974
M 54 - 60

141

1/4 Corner for Sections 5 and 8.
Set - Oregon State Board of Forestry 1 1/2" x 36" Gal. I.P. with
3" Bronze cap 34" in ground, Mound of Rock.
BT's - 14" Fir S.36°W., 155.8ft
36" Fir, N.02°E., 20.1 ft. with yellow metal location poster.
4" x 4" x 72" White painted cedar post, S.26°E., 8.0 ft.

JULY 25

142

Cor. of Sec. 19,30 T32-5 & Sec.24 & 25 T32-6
Found: - 1 1/2" I.Pipe, firmly set at fence corner, fences running N,E,
& S. REN #192A & 20
BT's- an orig. BT, a 9" now 16" W.Oak bears S43°E., 37.6 ft., with faint
scribe marks visible on previously open blaze.
All other original evidence has been destroyed.
A 16" now 21" pine, now a stump bears N78°E., 29.2 ft. scribed marks
visible. (REN.#20)
A 14" now 16" madrone bears S87W., 49.5., all scribes visible. See Ren#162
An 18" now 19" madrone bears N82°W., 71.8 ft. (Distance taken to east fork
of Twin-Forked madrone.) All scribes visible. We mark a Additional
BT- A 10" madrone bears N 42E., 13.2 ft., scribed "T 32 S R 5W S 19 CS BT"
on a double blaze. Compass Declination setting 20° East 11/10/75

T32-5
9/86 - FO OK PER M-102-39
By DON BENTZ

Gary L Langlitz
Clell Goodwin
A Vic. Cangie
M Lenora Ladig
11/10/75
CS 57/39

143

Section Corner common to Secs. 31 and 32 only.
Rod missing. Ren. #64B
Set - 2" x 2" Hub at corner from found B.T.'s as follows:
A 6" Laurel, Now 10", bears N.26 1/2°W., 18.1 ft. (Scribes
partially visible.)
A 5" Laurel, Now 9", bears N.28 1/2°E., 32.3 ft. (Scribes
partially visible.)

RE-RECORDED, SEE CORNER NO. 181

Victor McL...
For: John C...ver
Nov. 1975
M 58 - 57

Nov. 1975

144

Section Corner For Secs. 25, 26, 35 and 36.
Set - 1" x 36" I. Rod, 6" high from which bears
11" Cottonwood, N.10°30'E., 27.87 ft. scribed S 25 PS 841 BT.
12" Cottonwood, S. 59°W., 57.37 ft. scribed S 26 PS 841 BT.
9.4" Cottonwood, N. 60°W., 56.46 ft. scribed S 35 PS 841 BT
Bent 3/4" I.P., N.00°25'37"E., 330.20 ft. Witness corner.
SE quadrant VOID of trees except very small willow and cottonwood.

FD 1" I.R. 8/90 M110-48

Ronald A. Brandt
For: Haggard, Webber
Williamson, et al
August 6, 1977
M 66 - 26
C.S. 58/125

145

Center 1/4 Corner for Sec. 26
Set - 1" x 36" I. Rod, 6" high from which bears:
20" D. Fir, N.10°30'E., 14.41 ft., scribed C 1/4 S 26 PS 841 BT
8" Madrone, S.02°W., 18.74 ft. scribed C 1/4 S 26 PS 841 BT.
Lays near intersection of old blazed lines.

8/6/77

146

1/4 Corner for Secs. 23 and 26.
Set - By single proportion, A 1" x 36" I. Rod, 6" high in rock pile.
BT's- 8" Maple, S.72°30'E., 9.51 ft. scribed 1/4 S26 PS 841 BT.
10" D. Fir, N.74°W., 30.23 ft. scribed 1/4 S23 PS 841 BT.
Evidence of the orig. 1881 survey not found. corner area not logged but
old burn left only burned stobs ans snags which have since become
totally rotted out.

Robert A. Bra...t
For: Robert Dollar
Company
July 6, 1977
C.S. 58/149

7/6/77