

Douglas County Surveyor's Record of
Government Corners Renewed

T32 T. S. R 6 R.W.W.M.

KOKE-CHAPMAN CO., EUGENE, ORE. 21001

9/86 - FD OK PER BENTZ, M102-39 147

1/4 Corner for Secs. 25 and 26.
Found - A 1" Iron pipe set 10" above ground with brass cap facing east marked: "County Surveyors Office" 1/4 cor 26 25 T32S R6W LS 5.
A 15" now 19" Black Oak bears S.31°W., 13.2 ft. with partially healed rotted out single blaze. Ren. #42
A 22" Black oak bears S.60°W., 40.2 ft. (Rec. S.57°33'W., 39.3 ft.) with partially healed rotted out single blaze.
A 26" dead incense cedar bears N.23°30'W., 23.7 ft. with partially healed double blaze and visible scribing "1/4 CS BT".
New BT - A 9" D. Fir bears N.70 1/2°E., 12.5 ft. double blazed and marked "1/4 S25 T32S R6W CS BT".
Note - From brass cap fence runs west. N-S fence is 12 ft. west of B.C.
8/17/77

R. B. Kimberling
M. Cline
Do Co. Surveyors
Office
Aug 17, 1977
C.S. 59/38

1/4 Corner for Secs. 32 and 33.
Found - A 1" I.P. with brass cap set 0.1' below ground and marked: "County Surveyors Office" 33 32 1/4c Dep LS 5. Ren. #84
Brass cap is at corner of old wire fence, N-S and E-W.
Rock outcropping bears N.45°W., 11.2 ft. with chisled "+" and "CS".
Rock outcropping bears N.21 1/2°E., 40.3 ft. (Rec. 40.8 ft.) with chisled "+".
NO NEW MONUMENT SET.
New BT's- 10" D. Fir bears N.17°W., 33.1 ft. double blazed and scribed "1/4 S32 CS BT".
A fence post which is at the end of a wire fence to the north bears N.77°W., 6.3 ft.
2/21/78

R. B. Kimberling
P. L. Earle
Doug. Co. Surveyors
Office
Feb. 21, 1978
C.S. 59/46

Section corner common to Secs. 18 and 19; and 13, 24 of T32-7
Original: Fir Post (missing) from which a:
8" Laurel bears N.85°E., 30 lks.; now 14" x 3" high hollow root crown in Laurel clump N.81°E., 20.0 ft.
6" Laurel bears S.30°E., 61 lks.; now Laurel clump S.14 1/2° E., 37.2 ft.
24" Pine bears S.70°W., 100 lks.; now 28" x 50 ft. high snag S.70°W., 60.3 ft. horz. measurement. Slope measurement is 100 lks. to predetermined face and 103 lks. to center of tree. Only pine in area on steep and rocky SE. slope.
5" Live Oak bears N.45°W., 31 lks.; now Live Oak clump in place.
Set - 1 1/2" x 36" Gal. I.P. with 3" bronze cap mkd. "Oregon State Board of Forestry T32S R7W R6W S13 S18 S24 S19 1978 RS1101", 20 ins. in ground, in mound of rock, and from which a:
14" Fir bears S.62°W., 10.9 ft. to face; scribed T32S R7W S24 BT, B.L.M. face on SE side of tree; marked T32S R7W S13 BT.
38" Fir bears N.01°W., 59.9 ft. to face; scribed T32S R7W S13 BT.
28" Fir bears N.74 1/2°E., 85.9 ft. to face; scribed T32S R6W S18 BT RS1101.
19" Fir bears S.25°E., 48.7 ft. to face, on B.L.M.scribed tree; marked T32S R6W S19 BT.
Set 4" x 4" x 72" white painted Cedar Post N.73°W., 3.6 ft. from corner pipe. Oregon State Forestry Dept. metal location poster on 14" Fir, S.62°W., 10.9'. BLM pipe and cap S.3°21'W., 23.6 ft. to be obliterated by BLM.
3/13/78

1/4 Corner for Sec. 19; and Sec. 24 of T32-7
Original - Laurel Post (remains of point found) from which a:
36" Fir bears S.48°E, 45 lks.; now 52" x 25 ft. high burnt and shattered snag in place, 48 lks. to center, exposed axe work at top of face and chaining notch at bottom of face.
38" Fir bears N.52°W., 30 lks.; now stump hole with portions of roots remaining,
Set - 1 1/2" x 36" Galv. I.P. with 3" bronze cap marked "Oregon State Board of Forestry T32S 1/4 R7W R6W S24 S19 1978 RS1101", 34 ins. in ground, and from which a:
27" Fir bears S.35°W., 23.8 ft. to face; scribed 1/4 S24 BT RS1101.
10" Madrone bears S.72°E., 21.1 ft. to face; scribed 1/4 S19 BT RS1101.
Set 4" x 4" x 72" white painted Cedar post, N.58°E., 2.9 ft. from corner pipe. Oregon State Forestry Dept. metal location poster on 11" Madrone N.40°W., 3.2 ft.
BLM pipe and cap N.06° 53'W., 21.3 ft. to be obliterated by BLM.
3/13/78

State of Oregon-Department of Forestry

Lloyd D. Smith

Restored by James M. McIntosh, Engineer

Witnesses: David B. Buchholz & Christopher Hughes

March 13, 1978

C.S. 58/164 SEE M 71-79