

Douglas County Surveyor's Record of  
Government Corners Renewed

T. 32

T. S.

R 6

R. W. W. M.

KOKE-CHAPMAN CO., EUGENE, ORE. 91881

166

c o n t -----

(Sec. Cor. for Secs. 2, 3, 10, 11)

There being no other suitable trees available within limits:

I Set - 5/8" x 30" iron rebar with LS 1987 plastic cap as follows:

For Sec. 2: N.19°08'., 28.68 ft. - On road cut bank.

For Sec. 3: N.67°23'W., 34.32 ft. - Edge of road.

For Sec. 10: S.84°04'W., 26.41 ft. - Edge of road.

Corner lies approx. 10 ft. southerly of Rd. #32-6-3.

167

1/4 Corner for Sections 3 and 10.

Found - 1959 County brass cap monument firmly set, exposed 7". Ren. #55

40" fir snag bears S.25°W., 29.7 ft. - scribing visible.

32" fir stump bears S.44°E., 33.6 ft. - 1/4 S visible.

18" cedar stump bears N.85°E., 71.3 ft. - scribing visible.

48" rotted fir stump bears NW. - no scribing visible.

New BTs - 7" fir bears S.83°18'E., 2.80 ft. - mkd. 1/4 S10 LS 1987 BT.

7" fir bears N.17°33'W., 20.33 ft. - mkd. 1/4 S3 LS 1987 BT.

Corner lies on gentle southerly slope approx. 150 ft. above Rd. #32-6-9.

168

1/4 Corner common to Sections 8 and 9.

Found - 1974 Oregon State Board of Forestry brass cap monument firmly set  
exposed 3" with RS 359 stamp. Ren. #138

45" fir stump bears N.60°W., 25.7 ft. - S8 BT bark scribe visible.

24" fir bears N.5 1/2°E., 53.9 ft. - healed blaze.

New BT - 19" sugar pine bears S.87°W., 66.02 ft. mkd. 1/4 S8 BT.

Corner lies on southwest slope in predominately brushy area.

2/21/85

169

Center 1/4 Corner for Section 4

Set - 5/8" x 30" iron rod with alum. cap mkd. LS 1987.

BTs - 13" cedar bears N.59°45'E., 11.24 ft. mkd. C 1/4 S4 LS 1987 BT.

5" S. pine bears N.59°W., 13.02 ft. mkd. C 1/4 S4 LS 1987 BT.

170

Center 1/4 Corner for Section 3

Set - 5/8" x 30" iron rod with alum. cap mkd. LS 1987

BTs - 5" Fir bears N.59°45'W., 15.50 ft. mkd. C 1/4 S3 LS 1987 BT.

8" cedar bears S.21°30'W., 41.04 ft. mkd. C 1/4 S3 LS 1987 BT.

171

South 1/4 Corner for Section 33

Found - A DCSO brass cap/I.P. 6" below ground (Ren. #25) with a 3/4" inside dia. I.P. 3" North of brass cap, 2" below ground. R. #17

"+" B0" scribed in concrete on southwest end of bridge curbing

bears N.13°W., 74.8 ft. (agrees with record.) Ren. No. 25

"±" scribed in concrete on southeast corner of south bridge pier

bears N.5 1/4°E., 100.5 ft. (Rec. N.7°E. 100.5 ft.)

W.C. 3/4" I.R. top bent slightly northeast 2" below ground

bears east, 40.0 ft. (agrees with record)

No orig. BTs found. No BTs per Ren. No. 12 found.

New B.O.- 5/8" I.R. with DCSO alum. cap stamped "C104 A 1985" bears

N.6 1/4°E., 60.19 ft.

Corner lies in shoulder of Co. Rd. No. 12B, 1 1/2 ft. east of east edge of pavement. Approx. 65 ft. south of bridge over Cow Creek. Corner is tied into State Plane Coordinates.

Township corner for Secs. 6; Sec. 1 of T32-7; Sec. 36 of T.31-7 ;S. 31 of T.31-6

172

Found - 5/8" Iron rod with al. cap properly marked. Ren. 112

9" D. fir now 15" bears N.57°W., 10.2 ft. has good scar and in good condition.

16" D. fir now 25" bears S.28°W., 42.2 ft. has good scar and in good condition.

8" D.F. now 12" bears S.43°E., 44.6 ft. has good scar and in good condition.

9" D.F. now a 13" stump with 10" above ground, bears N.72°E., 56.2'

New BT - 15" madrona bears N.15°E., 65.10 ft. mkd. T. 31 S. R 6 W. S 31 BT.

Orrin K. Frederick  
LS 1987  
For: Boise Cascade  
Timberlands of  
Oregon  
February 21, 1985  
M 90 - 67  
C.S. 63/11

Douglas Co.  
Surveyors Office  
Randall Smith  
Stephen Flause  
Deputies  
Feb. 14, 1986  
C.S. 62/31

John H. Markham Jr.  
L.S. 1261  
For: C & D Lumber  
Ray Brown Party Chief  
Jim Jenks, Witness  
Jan. 6, 1986  
C.S. 62/30

Ed.  
M 112-3  
7/90