

Douglas County Surveyor's Record of  
Government Corners Renewed

T 32

T. S.

R 6

R.W.W.M.

ROKE-CHAPMAN CO., EUGENE, ORE. 31881

175

Standard Section Corner for Sections 1 and 2 of T.33-6

- Found - 1" iron pipe projecting 6" above ground. (See Ren. #10, T.33-6)
- A 30" (15") fir stump bears S.75°E., 21.8 ft. with a badly decayed face and backcast, no marks visible (Original).
- A 10" stump bears S.33°W., 13.2 ft. to face with illegible partial scribe marks. (Orig.)
- A 16" fir snag bears N.83°20'E., 78.8 ft. mkd. "S 1-BTS 8 BT".
- A 16" maple bears S.10°50'W., 57.0 ft. with healed blaze.
- Set - Plastic cap in 1" existing iron pipe. mkd. Oregon State Parks
- New BT - A 11" fir bears S.83°E., 21.6 ft. mkd. "T33SR6WS1BT"
- Set orange carsonite post with decal marked "Property Boundary State Park Land Behind this Sign" 2 ft. SW.

*fd. 3/4 I.P. 8/90  
M110-48*

6/27/88

176

Standard Corner for Sections 35 and 36 only.

- Found - 1" iron pipe projecting 6" above ground. Ren. No. 111
- A 46" fir bears N.56°W., (N40°W) 9.0 ft. (9.2) to illegible scribe marks in partially healed blaze. (Original)
- NE original BT falls in a skid road.
- A 14" (18") fir snag bears N.60°30'E., 65.8 ft. with "36 BT" visible in partially healed double blaze.
- A 22" fir bears N.82°E., (N.84°E) 38.0 ft. (34.3) ft. with healed blaze.
- A 30" fir bears N.36°W., N.33°50'W) 33.9 ft. with healed blaze.
- Set - Plastic cap in existing 1" iron pipe. mkd. "Oregon State Parks".
- Set - Orange carsonite post with decal mkd. "Property Boundary State Park Land Behind This Sign, 2 ft. South.

*fd. 3/4 I.P. 8/90  
M110-48*

6/23/88

177

North 1/4 Corner for Section 2 of T.33-6

(No original evidence found)

- Found - 1" iron rod set by Brandt in 1973 and references as per Ren. #129. I do not agree with the method of proportioning used to set this corner and I therefore set a new monument for the corner.
- Set - 1" x 30" iron post with a 2 3/8" brass cap at single proportioned distance between the North Standard 1/4 corner Section 4 and the Standard corner Sections 35 and 36 on a latitudinal curve. Cap mkd. "Oregon State Parks T32S R6W 1/4 S2 T33S R6W 1988 LS 691".

New measurements to existing bearing trees:

- A 16" fir bears S.47°E., 28.9 ft. with healed blaze.
- A 15" fir bears S.23°W., 16.6 ft. with healed blaze.
- A 1" iron rod bears N.37°40'E., 2.6 ft.

Set orange carsonite post with decal marked "PROPERTY BOUNDARY STATE PARK LAND BEHIND THIS SIGN", 2 ft. southeast.

8/23/88

178

Center 1/4 Corner for Section 27

- Set - 5/8" x 30" iron rod with yellow plastic cap marked "Hull RS 901".

Scribed BTs:

- 14" fir, west 22.40 ft.
- 14" fir, S.35°W., 30.50 ft.
- 18" fir, N.30°E., 1.80 ft.
- 15" madrone, S.6°E., 23.50 ft.

Found a 3/4" gal. iron pipe, N.67°11'E., 11.60 ft.

Max Hull, LS #901  
For: Gregory  
Forest Products  
Jan. 1989  
M 107 - 43  
C.S. 63/24

179

Center 1/4 Corner for Section 20

- Set - 5/8" x 48" iron rod with alum. cap marked "C 1/4 LS 498".

Scribed BTs:

- 8" Fir N.69°E., 23.4 ft.
- 6" Fir, S.10°W., 20.4 ft.

6/28/89

Howard Johnstone  
For: Roseburg  
Resources Co.  
June, 1989  
M 101 - 56