

Douglas County Surveyor's Record of
Government Corners Renewed

32

T. S.

7

R. W. W. M.

KOYE-CHAPMAN CO., EUGENE, ORE. 97196

Milner L. Larsen, Reg. Prof. Engineer
No. 3642.
August 11, 1954.
See County Surveyor's file No. 41/289.

Section corner to secs. 27, 28, 33, and 34,
Found a 12" Fir bearing N. 60° W., 57 lks., marked T32S, R7W, S 28B.T. This
tree later destroyed in road construction. From this tree I set the cor.,
a 2" iron pipe 30" long, 24" in the ground, from which a Fir, 24" diam.,
bears N. 64½° E., 92.4 ft., marked 3642 B.T.
A Fir, 30" diam., bears S. 42° E., 117.1 ft., marked 3642 BT.
A Tan Oak, 6" diam., bears S. 54½° W., 119.6 ft., marked 3642 B.T.
A Tan Oak, 5" diam., bears N. 42° W., 86.1 ft., marked 3642 B.T.
REF. OUT FOR RD. WORK - J. POWELL - 5/12 12-4-67 - FOUND O.K. J.M.P. C.S. 54/36

¼ sec. corner to secs. 19 and 20.
I find a 40" Yellow Pine windfall (broken off just above the ground) marked
¼ S on West face, from which a Yellow Pine, 48" diam., bears N. 30° E,
75 lks., no scribing remainson this tree, a Yellow Pine, 32" diam.,
bears S. 30° W., 8 lks., this tree is also a windfall, no scribing
remaining. On the West side of the stump of the tree marked for the ¼
corner, I drive a 1 inch steel bolt, 24" long, 18" in the ground,
from which a Laurel, 8" diam., bears N. 24½° W., 19.3 ft., marked
2968 B.T., a Laurel, 6" diam., bears S55° E., 15.3 ft., mkd. 2968 B.T.
Va. 19°30' E.

¼ sec. corner of secs. 33 and 34.
Determined at the record distance from each old bearing tree.
At the corner point,
Set an iron pipe, 3 ft. long, 1½ ins. diam., 28 ins. in the ground,
mkd. RS33;
From which the original bearing trees:
A sugar pine, 42 ins. diam., bears S.40° E., 8 lks.
dist., with blazes healed.
An incense cedar, 24 ins. diam., bears N.42° W., 30 lks.
dist., mkd. on bark ¼ S BT.

Center
¼ sec. corner of sec. 33 at intersection with E. and W. center line.
Set an iron pipe, 3 ft. long, 1½ ins. diam., 28 ins. in the ground
mkd. RS33;
From which:
A chinquapin, 10 ins. diam., bears N. 24° E., 38 lks.
dist., mkd. C ¼ S33 RS33 BT.
A chinquapin, 8 ins. diam., bears S.26° W., 7 lks.
dist., mkd. C ¼ S33 RS33 BT.

¼ sec. corner of secs. 28 and 33.
Determined at the record bearing and distance from each of the old
bearing trees.
At the corner point,
Set an iron pipe, 3 ft. long, 1½ ins. diam., 28 ins. in the
ground, mkd. RS33;
From which the original bearing trees:
A Douglas fir, 20 ins. diam., bears S.22° E., 32 lks.
dist., mkd. on bark ¼ S BT.
A Douglas fir, 28 ins. diam., bears N. 15° W., 48 lks.
dist., mkd. on bark ¼ S BT.

¼ sec. corner of secs. 32 and 33.
Determined at the record bearing and distance from the original SE.
bearing tree.
At the corner point,
Set an iron pipe, 3 ft. long, 1½ ins. diam., 28 ins. in the
ground, mkd. RS33;
From which an original bearing tree:
A madrona, 17 ins. diam., bears S.31° E., 19 lks.
dist., with the scribe marks ¼ S visible.
Find no evidence of the original NW. bearing tree.
And new bearing trees:
A madrona 9 ins. diam., bears S.85° E., 48 lks. dist.,
mkd. ¼ S33 RS33 BT.
An incense cedar, 19 ins. diam., bears N. 70° W., 49 lks.
dist., mkd. ¼ S32 RS33 BT.

12-13-67 - FOUND O.K. J.M.P. C.S. 54/36

Norman D. Price, Registered Professional Land Surveyor.
Survey done from March 30, to August 18, 1954.
See County Surveyor's file No. 41/301.
Work done on survey for Dollar and
Patterson Lumber Co., Glendale, Ore.

RENEWED, SEE CORNER NO. #102
RENEWED, SEE CORNER NO. #105

1

2

3

4

5

6