

Douglas County Surveyor's Record of
Government Corners Renewed

32 T. S. 7 R. W. W. M.

KORE-CHAPMAN CO., EUGENE, ORE. 97196

Standard corner of sections 34 and 35.

Determined at record bearing and distance from the remains of original SW. and NW. bearing trees. No evidence of original NE. bearing tree is found.

At the corner point, which is located in an old E. and W. fence line, and on old E. and W. blazed line,

Set an iron pipe, 3 ft. long, 2 ins. diam., 28 ins. in the ground, mkd. RS33;

From which the original bearing trees:

A badly burnt and decayed fir stump bears S.72°W., 47 lks. dist., on which no marks remain.

A madrona stool bears N.26°W., 30 lks. dist., on which no marks remain.

And new bearing trees:

A Douglas fir, 6 ins. diam., bears N. 9¼°E., 68 lks. dist., mkd. T32S R7W S35 SC RS33 BT.

A madrona, 12 ins. diam., bears N. 24 3/4°W., 27½ lks. dist., mkd. on bark T32S R7W S34 SC RS33 BT.

The geographic position of this cor. is lat. 42°44'24"N., and long. 123°30'10"W. The observed magnetic decl. is 20°12'E.

12-18-67 - FOUND O.K. J.M.P.

F.D. O.K. 8

Standard corner of sections 33 and 34.

Determined at record bearing and distance from the only extant original bearing tree.

At the corner point,

Set an iron pipe, 3 ft. long, 2 ins. diam., 28 ins. in the ground mkd. RS33;

From which an original bearing tree:

An incense cedar, 24 ins. diam., bears N.55°E., 56 lks. dist., with the scribe marks S34 SC visible.

And a new bearing tree:

12-5-67 FOUND O.K. J.M.P. C.S. 54/56

An incense cedar, 14 ins. diam., bears N. 34½°W., 15½ lks. dist., mkd. T32S R7W S33 SC RS33 BT.

Standard

¼ sec. corner of sec. 33 at proportionate distance.

There is no remaining evidence of the original corner.

Set an iron pipe, 3 ft. long, 1½ ins. diam., 28 ins. in the ground, mkd. RS33;

From which:

A Douglas fir, 52 ins. diam., bears N. 59½°E., 58 lks. dist. mkd. ¼ S33 SC RS33 BT.

A red cedar, 24 ins. diam., bears N.42½°W., 115 lks. dist., mkd. ¼ S33 SC RS33 BT.

DEC. 1967 - SEARCHED FOR, NOT FOUND J.M.P.

Point for standard corner of secs. 32 and 33.

Determined at the record bearing and distance from the original SW. bearing tree; all other evidence of the original corner monument has disappeared.

Set an iron pipe, 3 ft. long, 2 ins. diam., 28 ins. in the ground, mkd. RS33;

From which the only original bearing tree:

A Douglas fir, 20 ins. diam., bears S.58°W., 19 lks. dist., mkd. on bark T33S R7W S5 SC BT.

And a new bearing tree:

A Douglas fir, 14 ins. diam., bears N.41½°E., 46 lks. dist., mkd. T32S R7W S33 SC RS33 BT.

SEARCHED FOR - NOT FOUND 12-13-67 - J.M.P.

Norman D. Price, Registered Professional Land Surveyor.
Survey done from March 30, to August 18, 1954.
See County Surveyor's file No. 41/301.

Work done on survey for Dollar and Patterson Lumber Co.,
Glendale, Oregon.

9

10