

Douglas County Surveyor's Record of  
Government Corners Renewed

32

T. S.

7

R. W. W. M.

KORE-CHAPMAN CO., EUGENE, ORE. 97198

11

Section corner to secs. 22, 23, 26, and 27.

Locus of corner determined by the record bearing from original NE bearing tree, and record bearings and distances from the original SE., SW., and NW. bearing trees.

At the corner point,

Set an iron pipe, 3 ft. long, 2 ins. diam., 28 ins. in the ground marked RS33; from which the original bearing trees:

A Douglas Fir, 54 ins. diam., bears N.33°E., 68 lks. dist., mkd. on bark T32S R7W S23 BT.

A Douglas Fir, 26 ins. diam., bears S.40°E., 22 lks. dist., mkd. on bark T32S R7W S 26 BT.

A Douglas Fir stump, 30 ins. diam., bears N.40°W., 14 lks. dist., on which no marks remain.

A sugar pine, 48 ins. diam., bears S.35°W., 30 lks. dist., with blazes healed.

The geographic position of this corner is lat. 42°46'05"N., and longitude 123°30'14"W. The observed magnetic declination is 20°09'E.

75

12

1/4 sec. corner to secs. 22 and 23.

Determined at the record bearing and distance from both original bearing trees.

At the corner point,

Set an iron pipe, 3 ft. long, 1 1/2 ins. diam., 28 ins. in the ground, mkd. RS33; from which the original bearing trees:

A Douglas fir, 28 ins. diam., bears East, 50 lks. dist., mkd. on bark 1/4 S BT.

An incense cedar, 36 ins. diam., bears S.55°W., 16 lks. dist., mkd. on bark 1/4 S BT.

76

13

Section corner to secs. 14, 15, 22 and 23.

Determined at the record bearing and distance from each original bearing tree.

At the corner point,

Set an iron pipe, 3 ft. long, 2 ins. diam., 28 ins. in the ground, mkd. RS33; from which the original bearing trees:

A madrona, 16 ins. diam., bears N.65°E., 59 lks. dist. with partial scribe marks on decayed old blaze.

A madrona, 16 ins. diam., bears S.60°E., 16 lks. dist. with partial scribe marks on decayed old blaze.

A madrona, 12 ins. diam., bears S.40°W., 8 lks. dist., with old blaze decayed.

A madrona, 11 ins. diam., bears N.42°W., 25 lks. dist., with old blaze decayed.

And new bearing trees:

A madrona, 12 ins. diam., bears S.85°E., 46 lks. dist., mkd. T32S R7W S23 RS33 BT.

A yellow pine, 12 ins. diam., bears S.14°W., 27 lks. dist., mkd. T32S R7W S22 RS33 BT.

A Douglas fir, 10 ins. diam., bears N.67°W., 29 lks. dist., mkd. T32S R7W S15 RS33 BT.

59

14

1/4 sec. corner to secs. 22 and 27.

Determined at the record dist. from each orig. bearing tree.

At the corner point,

Set an iron pipe, 3 ft. long, 1 1/2 ins. diam., 2 ins. in the ground to bedrock, and in a mound of stone to top, mkd. RS33; from which the original bearing trees:

A madrona, 20 ins. diam., bears N.18°E., 82 lks. dist., with old blaze burnt.

A Douglas fir, 34 ins. diam., bears S.75°E., 45 lks. dist., with the scribe marks 1/4 on charred bark blaze.

And new bearing trees:

An incense cedar, 8 ins. diam., bears N.86°E., 66 lks. dist., mkd. 1/4 S22 RS33 BT.

An incense cedar, 36 ins. diam., bears South, 54 lks. dist., mkd. 1/4 S27 RS33 BT.

Norman D. Price, Registered Prof. Land Surveyor  
Glendale, Oregon

Work done for Dollar and Patterson Lumber Co.  
Survey done Sept. 16, 1954 to April 27, 1955.  
See County Surveyor's File No. 41/373.