

Douglas County Surveyor's Record of
Government Corners Renewed

32

T. S.

7

R. W. W. M.

KORE-CHAPMAN CO., EUGENE, ORE. 97196

Section corner to secs. 21, 22, 27 and 28.

15

Determined at record bearing and distance from original NE., SW., and NW. bearing trees:

At the corner point,

Set an iron pipe, 3 ft. long, 2 ins. diam., 28 ins. in the ground, mkd.

RS33; from which the original bearing trees:

A Douglas fir, 32 ins. diam., bears N.25°E., 34 lks. dist., mkd. on bark T32S R7W S22 BT.

A Douglas fir, 30 ins. diam., bears S.62°W., 30 lks. dist., mkd. on bark T32S R7W S28 BT.

A madrona, 12 ins. diam., bears N.50°W., 43 lks. dist., dist., with blaze healed.

There is no remaining evidence of the original SE. bearing tree.

$\frac{1}{4}$ sec. corner to secs. 21 and 22.

16

Determined at the record bearing and distance from the only extant original bearing tree.

At the corner point,

Set an iron pipe, 3 ft. long, $1\frac{1}{2}$ ins. diam., 28 ins. in the ground, mkd. RS33 from which the extant original bearing tree:

A Douglas fir, 30 ins. diam., bears N.55°E., 31 lks. dist. mkd. on bark $\frac{1}{4}$ S BT.

And a new bearing tree:

A Douglas fir, 9 ins. diam., bears N.77 $\frac{1}{2}$ °W., 8 $\frac{1}{2}$ lks. dist. mkd. $\frac{1}{4}$ S21 RS33 BT.

Section corner to secs. 15, 16, 21 and 22.

17

Determined at the record bearing and distance from each original bearing tree.

At the corner point,

Set an iron pipe, 3 ft. long, 2 ins. diam., 28 ins. in the ground, mkd.

RS33; from which the original bearing trees:

A yellow pine, 10 ins. diam., bears N.28°E., 21 lks. dist., with the scribe marks W S15 uncovered.

A yellow pine, 16 ins. diam., bears S.20°E., 32 lks. dist., with partial scribe marks visible.

A yellow pine, 40 ins. diam., bears S.75°W., 135 lks. dist., with blaze healed.

A sugar pine, 28 ins. diam., bears N.25°W., 36 lks. dist., with blaze healed.

$\frac{1}{4}$ sec. corner to secs. 15 and 22.

18

Determined at the record bearing and distance from each original bearing tree.

At the corner point,

Set an iron pipe, 3 ft. long, $1\frac{1}{2}$ ins. diam., 28 ins. in the ground, mkd. RS33; from which the original bearing trees:

A Douglas fir, 50 ins. diam., bears N.75°W., 56 lks. dist., mkd. on bark $\frac{1}{4}$ S BT.

A Douglas fir, 16 ins. diam., bears S.65°E., 9 lks. dist., with blaze healed.

Center $\frac{1}{4}$ sec. corner of section 22.

19

Point for center $\frac{1}{4}$ corner of sec. 22 at intersection with the N. and S. and E. and W. center lines.

Set an iron pipe, 3 ft. long, $1\frac{1}{2}$ ins. diam., 28 ins. in the ground, mkd. RS33; from which

A fir, 20 ins. diam., bears N.46°E., 44 lks. dist., mkd. C $\frac{1}{4}$ S22 RS33 BT.

A fir, 20 ins. diam., bears S.66°W., 148 lks. dist. mkd. C $\frac{1}{4}$ S22 RS33 BT.

Norman D. Price, Registered Prof. Land Surveyor
Survey done Sept. 16, 1954, to April 27, 1955.
See C. S. File No. 41/373.

Surveyed for Dollar and Patterson Co. Inc.
Glendale, Oregon