

Douglas County Surveyor's Record of
Government Corners Renewed

32 T. S. 7 R. W. W. M.

KOYE-CHAPMAN CO., EUGENE, ORE. 97196

Surveyed for Dollar and Patterson Co., Inc.
Glendale, Oregon.
1955

Norman D. Price RS 33.
Survey executed December 16, 1954 to May 15, 1956.
Filed in C. S. File No. 42/142.

$\frac{1}{4}$ sec. corner to secs. 27 and 28.
Corner determined at the record bearing and distance from each original bearing tree. **SEE CORNER NO. 69**
Set an iron pipe, 3 ft. long, $1\frac{1}{2}$ inches diam., 28 ins. in the ground, mkd. RS33;
From which the original bearing trees:
A Douglas Fir, 70 ins. diam., bears S.3°E., 28 lks. dist. with old blaze burnt.
A madrona, 40 ins. diam., bears N.15°W., 20 lks. dist., with partial scribe marks visible on mutilated old blaze.
And a new bearing tree:
A madrona, 16 ins. diam., bears S.73°W., 39 lks. dist. mkd. $\frac{1}{4}$ S28 RS33 BT.

20

$\frac{1}{4}$ sec. corner to secs. 28 and 29.
Corner determined at the record bearing and distance from the only extant bearing tree.
Set an iron pipe, 3 ft. long, $1\frac{1}{2}$ ins. diam., 28 ins. in the ground, mkd. RS33.
From which the only extant original bearing tree:
A chinquapin, 15 ins. diam., bears S.78°E., 58 lks. dist., mkd. on bark $\frac{1}{4}$ S BT. **126**
And new bearing trees: **11/30/67 FOUND O.K. J.M.P. C.S. 54/36**
A chinquapin, 8 ins. diam., bears S.72°E., 11 lks. dist., mkd. $\frac{1}{4}$ S28 RS33 BT.
A chinquapin, 12 ins. diam., bears N.72°W., 6 lks. dist., mkd. $\frac{1}{4}$ S29 RS33 BT.

21

Section corner to secs. 20, 21, 28 and 29.
Determined at the record bearing and distance from each extant original bearing tree. **SEE CORNER NO. 55**
Set an iron pipe, 3 ft. long, 2 ins. diam., 28 ins. in the ground, mkd. RS33.
From which the extant original bearing trees:
A madrona, 18 ins. diam., bears S.10°E., 37 lks. dist., badly burnt.
A dead yellow pine, 40 ins. diam., bears S.25°W., 84 lks. dist., with partial scribe marks on bark and lower blaze healed.
And new bearing trees:
A yellow pine, 30 ins. diam., bears N.53°E., 94 lks. dist., mkd. T32S R7W S21 RS33 BT.
A madrona, 5 ins. diam., bears S.74°E., 26 lks. dist., mkd. on bark T32S R7W S28 RS33 BT.
A yellow pine, 24 ins. diam., bears N.62°W., 101 lks. dist., mkd. T32S R7W S20 RS33 BT.

22

$\frac{1}{4}$ sec. corner to secs. 21 and 28. **FR. O.K. SEE RESURVEY NOTES Vol. 42 P. 16511**
Determined at the record distance from each original bearing tree.
Set an iron pipe, 3 ft. long, $1\frac{1}{2}$ ins. diam., 28 ins. in the ground, mkd. RS33.
From which the original bearing trees:
A dead yellow pine, 28 ins. diam., bears N.44°W., 17 lks. dist., with blazes mutilated. **125**
A dead yellow pine, 24 ins. diam., bears S.33°W., 22 lks. dist., with blazes mutilated.
And new bearing trees:
A tan oak, 5 ins. diam., bears N.60°E., 18 $\frac{1}{2}$ lks. dist., mkd. $\frac{1}{4}$ S 21 RS33 BT.
A tan oak, 5 ins. diam., bears S.5°W., 26 lks. dist., mkd. $\frac{1}{4}$ S28 RS33 BT.

23

Center $\frac{1}{4}$ sec. corner of Section 28. **12-13-67 - FOUND O.K. J.M.P. C.S. 54/36**
Point for corner determined by intersection of N-S and E-W centerlines of section 28. **SEE CORNER NO. 127e**
Set an iron pipe at point of intersection, 3 ft. long, $1\frac{1}{2}$ ins. diam., 42 ins. in the ground, mkd. RS33.
From which:
A Dougl. fir, 14 in. diam., brs. N.27°E., 95 lks. mkd. C $\frac{1}{4}$ S28 RS33 BT.
An incense cedar, 14 in. diam., S.26°E., 209 lks. mkd. C $\frac{1}{4}$ S28 RS33 BT.

24