

Douglas County Surveyor's Record of  
Government Corners Renewed

32 S T. S. 7 W R. W. W. M.

KOKE-CHAPMAN CO., EUGENE, ORE. 97196

$\frac{1}{4}$  sec. corner to secs. 16 and 21. *FD. OK. SEE RESURVEY NOTES Vol. 42 Pg. 16512* **25**  
Determined at the record bearing and distance from each of the original bearing trees, both of which will be destroyed during construction of logging roads.

Set an iron pipe, 3 ft. long,  $1\frac{1}{2}$  ins. diam., 28 ins. in the ground, mkd. RS33.

From which new bearing trees:

A Douglas fir, 10 ins. diam., bears S.73°E., 98 lks. dist., mkd.

$\frac{1}{4}$  S21 RS33 BT.

A Douglas fir, 10 ins. diam., bears N.77°W., 184 lks. dist., mkd.

$\frac{1}{4}$  S16 RS33 BT.

$\frac{1}{4}$  sec. corner to secs. 14 and 15. **26**

Determined at the record bearing and distance from each original bearing tree.

Set an iron pipe, 3 ft. long,  $1\frac{1}{2}$  ins. diam., 28 ins. in the ground, mkd. RS33. *FOUND O.K. Nov. 1967 J.M.P. C.S. 54/36*

From which the original bearing trees:

The badly decayed remains of a Douglas fir stump bears S.58°E., 98 lks. dist. on which no marks remain.

A sawed Douglas fir stump, 22 ins. diam., bears S.1°W., 84 lks. dist., mkd. on bark BT.

And new bearing trees:

A Douglas fir, 10 ins. diam., bears N.71 $\frac{1}{2}$ °E., 17 lks. dist., mkd.

$\frac{1}{4}$  S14 RS33 BT.

A Douglas fir, 9 ins. diam., bears N.68 $\frac{1}{2}$ °W., 12 lks. dist., mkd.

$\frac{1}{4}$  S15 RS33 BT.

Standard  $\frac{1}{4}$  sec. corner on the S. bdy. of sec. 32. **27**

Determined at the record bearing and distance from the extant original bearing tree.

Set an iron pipe, 3 ft. long,  $1\frac{1}{2}$  ins. diam., 28 ins. in the ground, mkd. RS33.

From which the original bearing tree:

A Douglas fir, 36 ins. diam., bears S.20°W., 20 lks. dist., mkd. on bark SC  $\frac{1}{4}$  S BT.

And a new bearing tree:

An incense cedar, 10 ins. diam., bears N.75°E., 28 lks. dist., mkd. SC  $\frac{1}{4}$  S32 RS33 BT. *FOUND O.K. 4/1/68 J.M.P.*

$\frac{1}{4}$  Corner common to Sections 8 and 9. **28**

Found to be in very poor condition. Both Orig. BT's had fallen over but the scribing was still visible.

I scribed 2 new BT's. & marked the corner as follows: **50**

Mkd: with a  $1\frac{1}{2}$ " (O.D.) Iron Pipe driven 20" in the ground.

12" Cedar S.89 $\frac{1}{2}$ °W. 33.7 ft. was referenced & scribed

S 8  $\frac{1}{4}$  S 4186 BT.

6" Cedar N.61 $\frac{1}{2}$ °E. 13.1 ft. scribed S 9  $\frac{1}{4}$  S, 4186 BT.

Center  $\frac{1}{4}$  Corner of Section 27.

Set - Corners monumented with 5/8" x 30" Drill Steel. **29**

Bearing Trees: 8" Madrone N.53°30'E. 6.7 ft.

8" Madrone S.53°30'W. 15.5 ft.

Oct. 13, 1961

By Lorne Van Swearingen

For Robert Dollar Co.  
Map File M 21 - 61

Norman D. Price RS 33.  
May, 1956.  
C. S. File 42/143.

Work done for Dollar and Patterson Co.,  
Glendale, Oregon  
Inc.

Robert Dollar Co.  
By Lorne Swearingen  
Wlt. R. Harris &  
M. Larson  
April 15, 1960  
C.S. File 51/63