

Douglas County Surveyor's Record of
Government Corners Renewed

T 32 S T. S. R 7 W. R.W.W.M.

KOKE-CHAPMAN CO., EUGENE, ORE. 21881

Wm. B. Paulin
Wit: Robert Kischel
Jan. 6, 1962
C. S. File No. 51/227

Section Corner to Secs. 24 & 25, T32-7 and Secs. 19 & 30, T32-6. 30
Found - 14" Laurel N.20°W. 44 lks. Had been previously opened, but found faint, definite traces of scribe.
10" Laurel N.85°E. 23 lks. Had been previously opened but could find no scribing, tree is down.
36" Fir Stump S.15°E. 28 lks., very badly rotted.
14" Laurel S.10°W. 38 lks. Had been previously opened & scribe removed. Found edge of old face.
Location tag on this tree dated "1939".
Set - 1 1/2" x 36" Iron Pipe at Corner.
New BT's: 8" Madrone bears N.16 1/4°E. 30.4 ft. scribed S19 T32S R6W B.T.
8" Chincquapin bears S.51 3/4°E. 36.5 ft. scribed S30 T32S R6W B.T.
6" Madrone bears S.11 1/2°W. 49.0 ft. scribed S25 T32S R7W B.T.
6" Chincquapin bears N.88 1/4°W. 12.0 ft. scribed S24 T32S R7W B.T.

By Hoard W.
Johnstone
For Roseburg
Lumber Co.
May 28, 1962
C.S. File No.
51/163

Section Cor. for Secs. 2 & 3, T32-7W. & Secs. 34 & 35, T31-7W. 31
Found - 26" Fir N.54°W. 71.9 ft. (now 46", good condition)
8" Laurel N.12°E. 46.9 ft.
14" Laurel S.60°W. 4.0 ft. (stump)
Set - 1" by 36" Iron Pipe
Scribed - 16" D. Fir S.35°E. 44.4 ft.
14" D. Fir S.78°W. 65.0 ft.
12" D. Fir N.36°E. 53.6 ft.

RE-OPENED CORNER NO. #34

Wm. B. Paulin
For Holly a Hough
July 1962
C.S. 51/239
Map M 24 - 1

1/4 Corner to Section 25, T32-7W. & Sec. 30, T32-6W. 32
I find mound of stone at corner. I also find a Fir 38" diam. bearing West 39 lks., very good scribe although core of tree rotten.
I find burnt pine stump bearing N.42°E. 76 lks. Also find 1/4 Marked on set Stone in mound of stone.
I Set 2" x 36" Iron Pipe at Corner. Marked two new Trees:
A P. Pine 24" bears S.88,30°W. 64.6 ft. mkd: 1/4 S25 T32S R7W B.T.
A Madrone 10" bears N.72 1/2°E. 24.5 ft. mkd: 1/4 S30 T32S R6W B.T.

James W. Byron
& Crew
May 31, 1963
C. S. File
No. 49/109

Section Corner to Secs. 5 & 6, T32-7W. & Secs. 31 & 32, T31-7W. 33
Found - Orig. 36", now 38" Fir S.32°W. 25.1 ft., shows bark scribing.
Orig. 15", now 20" Fir N.10°E. 38.3 ft., shows bark scribing.
Also find Stump of Orig. S.E. Bearing Tree. S.W. BT. not found.
Set - Brass Cap at Cor. Mkd: County Surveyor's Office, 1963
T31S S31 | S32
T32S R9W S 6 | S 5
New BT's: Rescribe, now 20" R. Fir N.11°E. 38.8 ft. CS BT.
6" Live Oak bears S.76°W. 32.0 ft. scribed S6 CS BT.
12" Laurel bears S.17°E. 19.2 ft. scribed S5 T32S R7W CS BT.
6" Laurel bears N.37°W. 18.0 ft. scribed S31 CS BT.

Vernon R.
Tracy
and Crew
Sept. 1964
C. S. File
No. 49/109

Sec. Cor. to Secs. 3 & 2, T32-7W. & Secs. 34 & 35, T31-7W. 34
Found - Cadastral Brass Cap & 4 Bearing Trees, as follows:
20" D. Fir S.35°E. 44.4 ft. - 11" D. Fir N.36°E. 53.6 ft.
Orig. 43" D. Fir N.54°W. 72.0 ft. - 15" D. Fir S.78°W. 65.0 ft. REN. #31
Set - Witness Corner 100.0 ft. South, Brass Cap Mkd: T31S S 34 | S 35
County Surveyor's Office, 1964 T32S S 3 | S 2 R7W
New BT's: 11" D. Fir N.80°W. 14.6 ft. Mkd: WC T31S R7W S34 CS BT.
9" D. Fir S. 1°E. 20.4 ft. Mkd: WC T32S R7W S2 CS BT.
10" Cedar S.15°W. 31.2 ft. Mkd: WC T32S R7W S3 CS BT.
11" Laurel N.51°E. 15.0 ft. Mkd: WC T31S R7W S35 CS BT.
Note - The Witness Corner lies on top of small spur.

Marvin C. Ramsey
For J. H. Baxter & Co.
February 4-12, 1965
C. S. File No.
51/310

Sec. Cor. to Secs. 1 & 2 only, T33-7W. determined from Orig. BT's: 35
36" Cedar sawed stump bears S.32°E. 20 lks., with axe marks, scribe marks burned out.
32" D. Fir sawed stump bears S.45°W. 28 lks. with partial scribe mk. exposed.
56" D. Fir snag bears N.60°W. 21 lks. with axe face; marks obltd. from decay.
Set - I Pipe, 3' long, 2" diam., 28" in the gr. mkd. RS404, from which:
An unmarked I. Pipe, 1" diam., 6" above gr., bears S.53°E. 6 lks.
New BT's: 10" D. Fir bears S.57°E. 36 lks. mkd. T33S R7W S1 RS404 BT.
16" D. Fir bears S.10°W. 10 lks. mkd. T33S R7W S2 RS404 BT. 67

RE-OPENED CORNER NO. #35