

Douglas County Surveyor's Record of
Government Corners Renewed

T. 32 S. T. S. R. 7 W. R.W.W.M.

ROKE-CHAPMAN CO., EUGENE, ORE. 21881

36

Sec. Cor. to Secs. 12 & 13, T32-7W. &
Secs. 7 & 18, T32-6W.
Found - 15" D.Fir, now 24" N.63°W. 47.0 ft., faint bark scribe.
Good Tree.
24", now 40" D. Fir S.8°E. 11.9 ft., good bark scribe,
"R6 S18". Tree is windfall.
No trace of other BT's.

Set - Brass Cap at Cor.Mkd: County Surveyor's
Office, 1965

	T32S	
R7W	S 12 S 7	R6W
	S 13 S 18	

New BT's: 6" D.Fir S.76°W. 55.6 ft. scribed S13 CS BT.
24" D.Fir N.63°W. 47.0 ft. scribed T32S R7W S12 CS BT.
30" D.Fir S.85°E. 38.8 ft. scribed T32S R6W S18 CS BT.
16" D.Fir N.72°E. 91.6 ft. scribed T32S R6W S7 CS BT.

Sept. 24, 1965

FD. OK 8/88
 G. LANGRISH
 M. 10-2-67

John M. Powell
 Joe Brady
 Sept. 1965
 C. S. File No. 49/91

37

1/4 Corner to Sec. 6, T32-7W. & Sec. 1, T32-8W.
Found - Both Orig. BT's., each cheeks bearing & distance.
Orig. 14", now 22" Fir N.70°W. 6.6 ft., shows good bark
scribing, "1/4 S BT".
Orig. 14", now 22" Fir S.55°E. 6.6 ft., shows good scars.

Set - Brass Cap at Cor.Mkd: County Surveyor's Office, 1965

T32S 1/4 R8W S 1 / S 6 R7W

Rescribe Now 22" Fir N.70°W. 6.6 ft. "1/4 S1 CS BT".

August 27, 1965

Powell and
 Crew
 August
 1965
 C.S. File
 No. 49/91

38

TOWNSHIP CORNER: T.31S.-Rs. 7 & 8W. & T.32S.-Rs. 7 & 8 W.
Found - 8", now 13" Live Oak, S. 78° E. 40.3 ft., opened for scribe.
12" D. Fir, now rotten stob, N. 45° W. 64.0 ft.
No trace of N. E. nor S. W. Bearing Trees

Set - Brass Cap at Township Corner Mkd:

	T 31 S	
R8W	S 36 S 31	R7W
	S 1 S 6	
	T 32 S	

New BT's: 10" D. Fir S. 72° W. 33.6 ft. mkd. T32S R8W S 1 CS BT.
12" D. Fir S. 48 1/2° E. 24.4 ft. mkd. T32S R7W S 6 CS BT.
8" Live Oak N. 53° E. 46.6 ft. mkd. T31S R7W S31 CS BT.
6" Live Oak N. 48° W. 4.6 ft. mkd. S 36 CS BT.

Note - This corner lies about 33.0 ft. E. of creek on steep, W. slope.
12/1/66

John M. Powell
 Frank Jones &
 Cliff Stone
 C. S. File No. 54/36

39

1/4 Corner to Sec. 4, T32-7W. and Sec. 33, T31-7W.
Found - GLO Brass Cap S. 82° E. 19.1 ft.
Orig. 15", now 38" D. Fir, S. 70° E. 29.7 ft., bark scribed,
Faint "BT".

Orig. 15", now 32" D.Fir, N. 70° W. 34.3 ft., bark scribed.

Set - Brass Cap at 1/4 Cor. mkd. County Surveyor's
Office, 1966

	T 31 S	
	S 33	R7W
	S 34 S	
	T 32 S	

Reblzd. & Resc'd. below Original Scribe:
38" D. Fir S. 70° E. 29.7 ft. mkd. 1/4 S 4 CS BT.
7" D. Fir N. 42° E. 18.8 ft. mkd. 1/4 S 33 CS BT.

This corner lies in small draw about 400.0 ft. west of creek.

12/21/66

40

1/4 Corner to Sections 11 and 12.
Found - 5", now 10" D. Fir, Corner Tree, shows good face on W. side.
36", now 48" D. Fir, S. 4° W. 21.8 ft., shows bark scribe.
No trace of S. W. Bearing Tree.

Set - Brass Cap at Cor. Mkd: County Surveyor's
Office, 1966

	T 32 S	R7 W
	1/4 S 11	S 12

New BT's: 14" D.Fir N. 65 1/2° W. 3.2 ft. mkd. 1/4 S 11 CS BT.
16" D. Fir S. 31 1/2° E. 17.8 ft. mkd. 1/4 S 12 CS BT.

Note - Creek bears North 20 feet.

RE-NEWED SEE CORNER NO #115