

Douglas County Surveyor's Record of
Government Corners Renewed

T. 32 S. T. S. R. 7 W. R.W.W.M.

KOKE-CHAPMAN CO., EUGENE, ORE. 21881

47

Section Corner to Secs. 30 & 31, T32-7W. and
Secs. 25 & 36, T32-8W.

Found - 28" Corner Tree, now rotten stob.

Orig. 20" Fir, now Stob, S.70°E. 48.8 ft., no scribing.

Orig. 18" Fir, now burnt stub, S.10°W. 47.5 ft., bark scribe found.

Orig. 10" Fir, now stob, N.82°W. 66.0 ft., scribe marks but
not legible.

Distances to bearing trees appear to be slope distance.

Set - Brass Cap at South Edge of Corner Tree Stob Mkd:

County Surveyor's	R	T 32 S	R
Office	8	S 25 S 30	7
1967	W	S 36 S 31	W

New BT's: 8" D. Fir East 13.4 ft. mkd. T32S R7W S30 CS BT.

8" D. Fir S.78°E. 16.1 ft. mkd. T32S R7W S31 CS BT.

9" D. Fir N.34°W. 3.5 ft. mkd. T32S R8W S25 CS BT.

10" Laurel S.4°W. 25.2 ft. mkd. T32S R8W S36 CS BT.

Note - This corner lies approx. 30 ft. south of high rock point.

FO. O.K. MAR. 1968 J.M.P.

RE-RENEWED CORNER NO. #123

48

FD 10/90
M111-4

1/4 Corner to Sec. 30, T32-7W. and Sec. 25, T32-8W.

Found - 38" D. Fir Corner Tree, now 43", faint bark scribe visible
on west side.

No trace of Laurel or Chinquapin BT.

Set - Brass Cap on W. side of Corner Tree Mkd:

County Surveyor's	R	T 32 S	R
Office	8 1/4	S 25 S 30	7
1967	W	1967	W

New BT's: 12" D. Fir N. 7° W. 56.4 ft. mkd. 1/4 S25 CS BT.

13" D. Fir N.35°E. 84.5 ft. mkd. 1/4 S30 CS BT.

John M. Powell
Frank Jones & Joe Brady
November, 1967
C. S. File No. 54/36

49

Section Corner to Sections 3 - 4 - 9 - 10.

Found - U.S. Cadastral Brass Cap, 1964.

32" D. Fir N. 81° W. 38.3 ft., pitched over scribe marks visible.

Orig. 16" D. Fir, now dead, N.32°E. 16.5 ft., shows scar.

Orig. 16" D. Fir, now dead, S.70°E. 13.2 ft., faint scribing visible.

Orig. 20" D. Fir, now dead, S.54°W. 13.2 ft., scribe visible, T32SR7WS9 BT.

New BT's: 8" D. Fir S. 48° E. 20.8 ft. mkd. T32S R7W S10 CS BT.

22" D. Fir N. 11 1/2° E. 42.3 ft. mkd. T32S R7W S3 CS BT.

13" D. Fir S. 30° W. 30.0 ft. mkd. T32S R7W S9 CS BT.

RE-RENEWED CORNER NO. #118

50

1/4 Corner to Sections 8 and 9.

Found - No trace of 1 1/4" Iron Pipe, See Ren. #28.

12", now 13" Cedar, S.89 1/2°W. 33.7 ft. mkd. scribe visible S8 1/4 S4186 BT.

6" Cedar, now down, N.61 1/2°E. 13.1 ft. scribe visible S9 1/4 S 4186 BT.

Area logged, pipe evidently pushed out.

Set - Brass Cap at 1/4 Cor. Mkd: County Surveyor's

T 32 S	R 7 W
1/4 S 8	S 9

New BT: 13" Cedar N. 38° E. 76.8 ft. mkd. 1/4 S9 CS BT.

51

1/4 Corner to Sections 10 and 15.

Found - Orig. 40" D. Fir, now stump, N.35°E. 9.2 ft., bark scribe visible.

Orig. 40" D. Fir, now stump, S.1°W. 14.5 ft., stump pushed out of ground.

Set - Brass Cap at 1/4 Cor. Mkd: County Surveyor's

T 32 S	R 7 W
1/4 S 10	S 15

New BT's: 15" Laurel N.51°W. 15.4 ft. mkd. 1/4 S10 CS BT.

8" D. Fir S. 44° E. 3.5 ft. mkd. 1/4 S15 CS BT.

Note - This corner lies approx. 260' East of creek & old logging road.

52

Section Corner to Sections 15 - 16 - 21 - 22.

Found - 2" I. Pipe at Corner, See Ren. #17.

Orig. 10" Yellow Pine, now stob, N.28°E. 13.4 ft., scribe visible "W S15".

Orig. 16" Y. Pine, now down, S.20°E. 21.1 ft.

Orig. 40" Y. Pine, now snag, S.75°W. 89.1 ft., shows old axe work.

Orig. 28" now 39" S. Pine, N. 25° W. 23.8 ft., shows scar.

New BT's: 5" Cedar S.71 1/2°W. 47.7 ft. mkd. S21 CS BT.

7" D. Fir N.86°W. 332.0 ft. mkd. T32S R7W S16 CS BT.

7" Laurel N.54°E. 41.5 ft. mkd. T32S R7W S15 CS BT.

30" D. Fir S.81 1/2°E. 11.9 ft. mkd. T32S R7W S22 CS BT.