

Douglas County Surveyor's Record of
Government Corners Renewed

T. 32 S. T. S. R. 7 W. R. W. W. M.

KOKE-CHAPMAN CO., EUGENE, ORE. 21881

59

Section Corner to Sections 14 - 15 - 22 - 23.
Found - 2" Iron Pipe at Section Corner, See Ren. #13.
12", now 14" Laurel S.87½°E. (Record S.85°E.) 30.4 ft.,
shows bark scribing.
12", now 14" Pine, S.14°W. 17.8 ft., shows pitched over scribing.
10" D.Fir, now down, N. 67° W. 19.1 ft.
New BT's: 5" Chinquapin N. 54°E. 35.5 ft., scribed S14 CS BT.
22" D. Fir N. 13° W. 54.1 ft., scribed T32S R7W S15 CS BT.
Note - This corner lies on top of ridge running NW - SE.

60

Section Corner to Sections 8 - 9 - 16 - 17.
Found - Orig. 24" D.Fir, now snag, N.55°E. 83.2 ft., no scribing.
Orig. 40" D.Fir, now down, S.88°E. 58.7 ft., no scribing.
Orig. 10", now 38" Pine, S.28°W. 49.5 ft., opened for scribe "T".
Orig. 36" Pine, now snag, N.24°W. 60.1 ft., tree opened, prev.,
no scribing found.
Set - Brass Cap at Cor. Mkd: County Surveyor's T 32 S R 7 W
Office S 8 | S 9
1967 S 17 | S 16
New BT's: 8" D.Fir S. 60° W. 7.9 ft. mkd. T32S R7W S17 CS BT.
13" Y. Pine N. 45° W. 13.0 ft. mkd. T32S R7W S8 CS BT.
13" D.Fir N. 51° E. 32.5 ft. mkd. T32S R7W S9 CS BT.
14" Y. Pine S. 78° E. 34.0 ft. mkd. T32S R7W S16 CS BT.

61

Section Corner to Sections 9 - 10 - 15 - 16.
Found - Orig. 5", now 27" D.Fir, N.17°E. 40.9 ft., tree opened
before, scribe visible.
Orig. 48" D.Fir, now rotten stump, S.48°E. 56.4 ft.
No trace of S.W. or N.W. Laurel BT's.
Set - Brass Cap at Cor. Mkd: County Surveyor's T 32 S R 7 W
Office S 9 | S 10
1967 S 16 | S 15
New BT's: 26" D.Fir S. 45° E. 28.4 ft. mkd. T32S R7W S15 CS BT.
10" D.Fir S. 23½°W. 12.6 ft. mkd. T32S R7W S16 CS BT.
27" D.Fir N. 5° W. 15.7 ft. mkd. T32S R7W S9 CS BT.
Nov. 22, 1967

John M. Powell
Frank Jones
November, 1967
C. S. File No. 54/36

62

¼ Corner to Sections 4 and 9.
Found - Orig. 5" Cedar, now down, S.48°E. 33.0 ft., no trace of scribing.
Orig. 30", now 35" Fir, N.35°W. 7.3 ft., bark scribe visible, "S".
Set - Brass Cap at ¼ Cor. Mkd: County Surveyor's T 32 S R 7 W
Office ¼ S 4 | S 9
1967 S 9
New BT's: 8" D.Fir S.57°E. 17.3 ft. mkd. ¼ S9 CS BT.
Rescribed: 35" D.Fir N.35°W. 7.3 ft. mkd. ¼ S4 CS BT.
(This dist. is Orig. dist. from face.)

63

¼ Corner to Sections 4 and 5.
Found - Orig. 15", now 18" D.Fir, N.40°E. 15.8 ft., shows faint bark scribe.
Orig. 18" D.Fir, now 8' stob, S.65°W. 14.5 ft., shows bark scribe.
Set - Brass Cap at ¼ Cor. Mkd: County Surveyor's T 32 S R 7 W
Office ¼ S 5 | S 4
1967 S 4
New BT's: 14" D.Fir S. 48° W. 16.8 ft. scribed ¼ S5 CS BT.
Rescribed: 18" D.Fir N.40°E. 15.8 ft. mkd. ¼ S4 CS BT.

64

Section Corner to Sections 4 - 5 - 8 - 9.
Found - Orig. 30", now 35" S.Pine, N.60°E. (Rec. N.64E) 44.9 ft., faint scribe marks visible.
Orig. 36", now 37" S.Pine, S.5°E. (Rec. S.10E) 67.3 ft., faint scribe visible.
Orig. 36", now 36" D.Fir, N.30°W. 23.8 ft., faint scribe visible.
Orig. 36" S.Pine, now stump, S.28°W. 50.6' (Rec. S.22W. 53.5')
By using 1 bearing & 3 distances, I renew section corner.
Set - Brass Cap at Cor. Mkd: County Surveyor's T 32 S R 7 W
Office S 5 | S 4
1967 S 8 | S 9
New BT's: 9" D.Fir S.56°E. 34.5 ft. mkd. T32S R7W S9 CS BT.
26" Y. Pine N.74°E. 38.4 ft. mkd. T32S R7W S4 CS BT.
18" D.Fir N.49½°W. 29.4 ft. mkd. T32S R7W S5 CS BT.
7" Madrona S.72½°W. 53.0 ft. mkd. T32S R7W S8 CS BT.

11/28/67