

Douglas County Surveyor's Record of
Government Corners Renewed

T. 32 S. T. S. R. 7 W. R.W.W.M.

KOKE-CHAPMAN CO., EUGENE, ORE. 21881

65

¼ Corner to Sections 10 and 11.
Found - Orig. 12", now 30" D.Fir Windfall, S.50°W. 23.1 ft., scribe visible.
Orig. Laurel, down, S.40°E. 25.7 ft., down, all but gone.
Set - Brass Cap at ¼ Cor. Mkd: County Surveyor's Office, 1967 T 32 S R 7 W
¼ S 10 | S 11
New BT's: 10" Yew S. 68° E. 23.0 ft. mkd. ¼ S11 CS BT.
14" Fir N. 86° W. 25.0 ft. mkd. ¼ S10 CS BT.
Note - This corner lies 100 ft. north of draw running E. & W.

66

Section Corner to Sections 19 - 20 - 29 - 30.
Found - Orig. 10", now 24" Cedar, N.5°W. 19.1 ft., bark scribe visible "BT".
Orig. 16", now 22" Laurel, S.15°E. 38.3 ft., burnt out.
Orig. 14", now 16" Laurel S.55°W. 25.1 ft., burnt out.
Orig. 36" D. Fir, now burnt stump, N.55°E. 46.2 ft.
Set-Brass Cap at Cor. Mkd: County Surveyor's Office, 1967 T 32 S R 7 W
S 19 | S 20
S 30 | S 29
New BT's: 30" D.Fir S. 23° W. 26.6 ft. scribed T32S R7W S30 CS BT.
8" D.Fir N. 56° W. 22.2 ft. mkd. T32S R7W S19 CS BT.
6" Live Oak N. 71° E. 15.6 ft. scribed T32S R7W S20 CS BT.
12" D.Fir S. 25°E. 26.5 ft. scribed T32S R7W S29 CS BT.

67

Cl. Corner Corner to Sections 1 and 2 only, T33-7W.
Found - 2" I. Pipe with 4" flange at section corner, See Ren. #35.
1" I. Pipe S.53°E. 4.0 ft.
10" D.Fir, now stob, S. 57° E. 23.8 ft., shows pitched over scribing.
16" D.Fir, now 16", S.10°W. 6.6 ft., shows pitched over scribing.
New BT's: 12" D.Fir S. 82° E. 22.3 ft. mkd. T33S R7W S1 CC CS BT.
12/5/67

68

Section Corner to Sections 28 - 29 - 32 - 33.
Found - 18"(?), now 51" D.Fir, N.18°E. 58.1 ft., faint bark scribe "B",
other marks not legible. (Orig.)
Orig. 30", now 51" D.Fir, N.54°W. 85.8 ft., no scribe visible.
No trace of 24" Laurels (Originals) SE & SW.
Set - Brass Cap at Cor. Mkd: County Surveyor's Office, 1967 T 32 S R 7 W
S 29 | S 28
S 32 | S 33
New BT's: 10" Laurel S.26°E. 2.7 ft. mkd. T32S R7W S33 CS BT.
14" Laurel S. 9°W. 20.0 ft. mkd. T32S R7W S32 CS BT.
9" Laurel N.44°W. 12.8 ft. mkd. T32S R7W S29 CS BT.
13" Laurel N.45°E. 33.2 ft. mkd. T32S R7W S28 CS BT.
Note - This corner hits call of 495.0 ft. N. of top of ridge.

69

¼ Corner to Sections 27 and 28.
Found - I. Pipe at ¼ Corner, 1½" diam., See Ren. #20. 128
Orig. 70" D.Fir, burnt out, S.3°E. 18.5 ft., faint bark scribe "S".
Orig. 40" Laurel N.15°W. 13.2 ft., tree opened, very faint marks.
16" Laurel, now 14", S.73°W. 25.7 ft., shows good scar.
New BT's: 4" Chinquapin N.60°E. 19.8 ft. mkd. ¼ S27 CS BT.
Replazed & Rescribed: 40" Laurel N.15°W. 13.2 ft. mkd. ¼ S28 CS BT.

70

¼ Corner to Sections 33 and 34.
Found - 1½" Iron Pipe at ¼ Corner, See Ren. #3.
Orig. 42" S.Pine, now 24" Stob, S.40°E. 5.3 ft., shows old scars.
Orig. 24", now 25" Cedar, N.42°W. 19.8 ft., shows faint scribe marks,
not legible.
New BT's: 14" D.Fir N. 56° W. 23.9 ft. mkd. ¼ S33 CS BT.
6" D.Fir N.38°E. 16.3 ft. mkd. ¼ S34 CS BT.

71

Section Corner to Sections 5 and 4 only, T33-7W.
Found - 2" Iron Pipe at Sec. Cor., See Ren. #5, T33-7
Orig. 9" Y.Pine, now 18", S.47½°W. 93.7 ft., Tree opnd. scribe visible.
6" S.Pine, now dead, S.78°E. 16.3 ft., scribe visible.
New BT's: Chinquipin S.30°E. 17.3 ft. mkd. T33S R7W S4 CC CS BT.
Note - This corner lies on top of ridge running NE-SW about 60' S. of old
road intersection.

FD 10/70
M 111-4

FD. OK
Dec. 50.
10/14/92
C.S. 64/32

John M. Powell
Frank Jones
December, 1967
C. S. File No. 54/36