

Douglas County Surveyor's Record of
Government Corners Renewed

T. 32 S. T. S. R. 7 W. R.W.W.M.

Standard Corner of Sections 35 and 36.

Found - Orig. 30" Fir Stump N.35°E. 10.0 ft., old hack marks outline face.
Orig. 16" Fir Stump N.47½°W. 24.0 ft., only root collar remains.
Orig. 28" Fir Stump S. 7°E. 13.0 ft., bark scribing reads "BT".
Set - 1½" ID iron pipe for the corner, and scribed following BT's:
16" Doug. Fir N. 33° W. 17.5 ft.
12" Doug. Fir N. 27° W. 15.0 ft.
17" Live Oak S. 0° 30' E. 32.0 ft.
Note - All bearings were taken with a staff compass; Var. 19°00'E.
Distances were measured with a steel tape.
This corner was renewed in 1954; information was verified
by T. H. Mehl III, RS 749, Dec. 21, 1967. - FOUND O.K. 12/67 JMP.

Milner L. Larson
Robert Dollar Co.
Dec. 21, 1967
C. S. File No. 55/15

¼ Corner to Sec. 19, T32-7W. and Sec. 24, T32-8W.

Found - Orig. 38" Pine, now dead stob, S.70°E. 46.2 ft., old axe work, no scribing.
Orig. 30", now 40" D. Fir, N.85°W. 28.4 ft., bark scribe visible, "S BT".
Set - Brass Cap at ¼ Cor. Mkd: County Surveyor's Office 1967
R T 32 S R
¼ 8 S 24 S 19 7
W W
New BT's: 12" D. Fir N.24½° E. 27.7 ft. mkd. ¼ S19 CS BT.
6" Y. Pine S.78° W. 26.2 ft. mkd. ¼ S24 CS BT.
Note - This corner lies approx. 250 ft. south of old dead end logging road, location tag on road.

John M. Powell & Crew
Dec. 15, 1967
C. S. File No. 54/36

Closing Corner to Sections 3 and 4, T33-7W.

Found - 2" I.Pipe at Sec. Corner, See Ren. #23, T33-7W.
30" D. Fir S. 47°E. 64.7 ft., shows scar.
10" Chinquapin, now dead, S.20°W. 25.2 ft., scribe visible.
New BT: 9" D.Fir S.28°W. 28.2 ft. mkd. T33S R7W S4 CC CS BT.

John M. Powell & Crew
March, 1968
C. S. File No. 54/36

Section Corner to Sections 22 - 23 - 26 - 27.

Found - 1½" I. Pipe at corner, See Ren. #11.
Orig. 36", now 54" D.Fir, N.33°E. 44.9 ft. (Rec. 11.9), faint bark scribe.
Orig. 14", now 26" D.Fir, S.40°E. 14.5 ft., faint bark scribe.
Orig. 36", now 48" S.Pine, S.35°W. 19.8 ft., nothing visible.
Orig. 30" D.Fir, now stump, N.40°W. 9.4 ft.
New BT's: 13" D.Fir N.82°W. 74.0 ft. mkd. T32S R7W S22 CS BT.
Reblzd. & Rescbd: 54" D.Fir N.33°E. 44.9 ft. mkd. T32S R7W S23 CS BT.
26" D.Fir S.40°E. 14.5 ft. mkd. T32S R7W S26 CS BT.
48" S.Pine S.35°W. 19.8 ft. mkd. T32S R7W S27 CS BT.

FD. By: R. Quimby
MAY, 1983
M 94-27
FD BY Smalley
M 7/93
M 117-43

¼ Corner to Section 22 and 23.

Found - 1½" Iron Pipe at ¼ corner, See Ren. #12.
Orig. 22", now 28" D.Fir, East 33.0 ft., shows good bark scribe.
Orig. 24", now 36" Cedar, S.55°W. 10.6 ft., no marks visible.
Reblzd. & Rescbd: 36" Cedar S.55°W. 10.6 ft. mkd. ¼ S22 CS BT.

Section Corner to Sections 25 - 26 - 35 - 36.

Found - Unrecorded I.Pipe at corner.
Orig. 15", now 20" S.Pine, N.45°E. 33.0 ft., no marks visible.
Orig. 20", now 38" D.Fir, N.15°W. (Rec. N.20W) 11.2 ft., bark scribe visible.
Orig. 16" D.Fir, now down, S.6°W. 40.7 ft. (Rec. 36.3), bark scribe visible.
Orig. 18" D.Fir, now down, S.5°E. 40.0 ft. (Rec. 33.7), marks visible.
Set - Brass Cap at Cor. Mkd: County Surveyor's Office 1968
T 32 S R 7 W
S 26 S 25
S 35 S 36
New BT's: 14" D.Fir S.49½°E. 53.0 ft. mkd. T32S R7W S36 CS BT.
16" Laurel S.32°W. 77.5 ft. mkd. T32S R7W S35 CS BT.
Reblzd. & Rescbd: 20" S.Pine N.45°E. 33.0 ft. mkd. T32S R7W S25 CS BT.

72

73

74

75

76

77