

Douglas County Surveyor's Record of
Government Corners Renewed

T. 32 S. T. S. R. 7 W. R.W.W.M.

KOKE-CHAPMAN CO., EUGENE, ORE. 21881

78

1/4 Corner to Sections 26 and 35.
Found - 6", now " D.Fir, S.10°W. (Rec.S.15W) 19.8 ft., tree opened
for "S". Open more for "4".

Orig. 12" Laurel, now down, N.50°W. 20.5 ft., tree burnt out.
Set - Brass Cap at Cor.Mkd: County Surveyor's Office 1968

T32S R7W
1/4 S 26
S 35

Ed. by:
R. Quimby
MAY 1983
M 94-27
3/13/68

New BT's: 22" D.Fir N.61 1/2°E. 17.8 ft. mkd. 1/4 S26 CS BT.
14" D.Fir S.59°E. 26.5 ft. mkd. 1/4 S35 CS BT.

79

1/4 Corner to Sections 28 and 33.

Found - 1 1/2" Iron Pipe at 1/4 Corner, See Ren. #5.
20" D.Fir, now stob, S.22°E. 21.1 ft., no evidence of scribing.
28" D.Fir, now 30" N.15°W. 31.7 ft., faint bark scribe "1/2 S".

Reblazed & Rescribed: 28" D.Fir, now 29" N.15°W. 31.7 ft. mkd: 1/4 S28 CS BT.
New BT: 24" D.Fir S.33°W. 21.0 ft. mkd. 1/4 S33 CS BT.

Note - This corner lies approx. 80 ft. W. of deep ravine, running N.W.

129

80

Section Corner to Sections 29 - 30 - 31 - 32.

Found - Orig. 24", now 25" D.Fir, N.20°E. 31.7 ft., bark scribe visible.
Orig. 30", now 32" D.Fir, S.65°E. 16.5 ft., bark scribe visible.
Orig. 30" D.Fir, now stob, S.55°W. 20.5 ft., No trace of N.W. BT.

Set - Brass Cap at Cor.Mkd: County Surveyor's Office 1968

T32S R7W
S 30 | S 29
S 31 | S 32

New BT's: 16" D.Fir N.17°W. 19.2 ft. mkd. T32S R7W S30 CS BT.
40" Pine S.82°W. 28.4 ft. mkd. T32S R7W S31 CS BT.
Reblzd. & Rescrbd: 25" D.Fir N.20°E. 31.7 ft. mkd. T32S R7W S29 CS BT.
32" D.Fir S.65°E. 16.5 ft. mkd. T32S R7W S32 CS BT.

Note - This corner lies approx. 40 ft. W. of large rock outcrop on top of small spur running West.

81

1/4 Corner to Sections 30 and 29.

Found - Orig. 50", now 50" D.Fir, S.40°E. 11.2 ft., shows bark scribe.
No trace of 5" Laurel, S.W. BT.

Set - Brass Cap at Cor. Mkd: County Surveyor's Office, 1968

T32S R7W
1/4 S 30 | S 29

New BT: 25" D.Fir S.80°E. 27.2 ft. mkd. 1/4 S30 CS BT.
Other BT O.K., tagged same.

82

Corner to Sections 31, T32-7W. & Sec. 36, T32-8W.

Found - Orig. 28" Pine, now stob, N.57°E. 33.9 ft.
Orig. 36" Pine, now stob, N.20°W. 52.8 ft.
Orig. 34" Fir, now stob, S.15°E. (Rec. S.20°E) 40.9 ft.

Old Stone set with 6 grooves on the N-E-W faces for corner (Orig.??)
I find no good orig. evidence of this corner. However, by carefully chaining between the closing corner of S1/S6 T33S R7 & 8W. which is 417.1 ft. and find the trees of the right type & size hitting good for bearing & distance.

Set - Brass Cap at Cor. Mkd: County Surveyor's Office 1968

R T T32S R
8 S 36 | S 31 7
W S 1 W

New BT: 6" S.Pine W. 2.0 ft. mkd. S36 CS BT.
6" S.Pine N.60°E. 17.5 ft. mkd. S31 CS BT.
10" Y.Pine S.13°E. 37.5 ft. mkd. T33S R8W S1 CS BT.

83

Clsing Corner Sections 1, T33-8W. & Sec. 6, T33-7W.

Found - Stone 20x14x10 with 6 notches.
24" D.Fir, now 26" Snag, S.58°W. 37.0 ft., found bark scribing.

Set - Brass Cap at Cor.Mkd: County Surveyor's Office 1968

R T32S R
8 S 1 | S 6 7
W CC W

New BT's: 14" D.Fir S.14°E. 65.7 ft. mkd. T33S R7W S6 CC CS BT.
6" Pine S.41°W. 45.7 ft. mkd. S1 CC CS BT.

Note - This corner lies 150' East of logging road.

John M. Powell
Frank Jones & W. Penley
March, 1968
C. S. File No. 54/36