

Douglas County Surveyor's Record of
Government Corners Renewed

T. 32 S. T. S. R. 7 W. R. W. W. M.

KOKE-CHAPMAN CO., EUGENE, ORE. 21881

84

Section Corner to Sections 5 - 6 - 7 - 8.
Found - Orig. 12", now 21" S. Pine, N. 68° E. 21.1 ft., shows scar.
Orig. 12", now 20" S. Pine, Face burnt, S. 15° W. 6.6 ft.
Orig. 15", now 26" S. Pine, S. 52° E. 17.2 ft., tree opened,
shows scribe "W" & parts of other marks.
Orig. 10", now 19" Laurel, N. 62° W. 25.1 ft., shows scar.
Set - Brass Cap at Cor. Mkd: County Surveyor's T32S R7W
Office, 1968 S 6 | S 5
S 7 | S 8

New BT's: Reblazed & Rescribed:
21" S. Pine N. 68° E. 21.1 ft. mkd. T32S R7W S5 CS BT.
20" S. Pine S. 15° W. 6.6 ft. mkd. T32S R7W S7 CS BT.
26" S. Pine S. 52° E. 17.2 ft. mkd. T32S R7W S8 CS BT.
19" Laurel N. 62° W. 25.1 ft. mkd. T32S R7W S6 CS BT.

*Fd. OK
9/89
M 108-69
C.S. 3/24
M.A. HULL*

85

Sec. Corner to Secs. 6 & 7, T32-7W. and Secs. 1 & 12, T32-8W.
Found - Unrecorded 3/4" I. Pipe at Sec. Cor.
Orig. 22" D. Fir, now down, S. 8° W. 43.5 ft., bark scribe visible.
Orig. Pine Stump N. 80° E. 4.0 ft., no evidence.
Set - Brass Cap at Cor. Mkd: County Surveyor's R T32S R
Office 8 S 1 | S 6 7
1968 W S 12 | S 7 W

New BT's: 8" Laurel S. 41° E. 4.4 ft. mkd. T32S R7W S7 CS BT.
12" D. Fir S. 42° W. 19.5 ft. mkd. T32S R8W S12 CS BT.
10" D. Fir N. 56° W. 14.0 ft. mkd. T32S R8W S1 CS BT.
12" D. Fir N. 64° E. 38.0 ft. mkd. T32S R7W S6 CS BT.

*Fd. OK 9/89
M 108-69
M.A. HULL
C.S. 5.9.83/24*

86

1/4 Corner to Sections 31 and 32.
Found - Orig. 40" Pine, now 54" Stump, N. 82° E. 19.8 ft., no trace
of scribing.
Orig. 24", now 32" D. Fir, S. 72° W. 52.8 ft., found bark
scribing.
Set - Brass Cap at Cor. Mkd: County Surveyor's T 32 S R 7 W
Office, 1968 1/4 S 31 | S 32
New BT's: 6" D. Fir N. 85° E. 31.8 ft. mkd. "1/4 S32 CS BT".
14" Cedar N. 84° W. 32.2 ft. mkd. "1/4 S31 CS BT."
Note - This 1/4 corner lies 10' E. of an old unused logging road
& approx. 100' E. of a ridge top.
5/27/68

John M. Powell
Frank Jones & W. Penley
April, 1968
C. S. File No. 54/36

87

Section Corner to Sections 31 and 32, only, T32-7W.
Found - 16", now 26" D. Fir, N. 1 1/2° E. 55.4 ft., open & show scribing.
18", now 28" D. Fir, N. 72° W. 72.6 ft., open & show scribing.
Set - Brass Cap at Cor. Mkd: County Surveyor's R7W T 32 S 31 | 32
Office, 1968 T 33 S S 6
New BT's: 6" D. Fir N. 17° E. 17.0 ft. mkd: T32S R7W S32 SC CS BT.
8" D. Fir N. 64° W. 11.4 ft. mkd: T32S R7W S31 SC CS BT.
Note - This corner lies 660 ft. E. of top of ridge running N & S.
and 603.9 ft. W. of C. C. of Sections 6 and 5. (See below).
5/27/68

88

Closing Corner to Sections 6 and 5, T33-7W.
Found - 1" Iron Pipe 24" long at corner. (No trace of corner stone)
15" D. Fir, now 24" Snag, S. 57° W. 66.0 ft., shows bark scribng.
32", now 42" Sugar Pine, S. 81° E. 51.5 ft., shows a scar.
Set - Brass Cap at Cor. Mkd: County Surveyor's R7W T 32 S S 32
Office, 1968 T 33 S S 6 | S 5
Rescribed: 42" S. Pine S. 81° E. 51.5 ft., scribed T33S R7WS5CC CS BT.
New BT: 10" D. Fir N. 69° W. 71.0 ft. mkd. T32S R7W S32 CS BT.
No other trees for scribing.
Note - This corner lies 603.9' East of S.C. of S81/S32, see above.
5/27/68