

Douglas County Surveyor's Record of
Government Corners Renewed

T. 32 S. T. S. R. 7 W. R.W.W.M.

KOKE-CHAPMAN CO., EUGENE, ORE. 21881

Howard W. Johnstone
For: Roseburg Lumber Co.
February, 1969
Map File M 33 - 49

John M. Powell
Frank Jones & W. Penley
June & July, 1969
C. S. File No's. 54/36 and 54/53

Howard W. Johnstone
For: Roseburg Lumber Co.
Feb. 1970 M 39 - 14

Township Corner R T 31 S R
7 S 36 S 31 6
W S 1 S 6 W

RE-RENEWED SEE CORNER NO. #116

Set - 5/8" x 30" Rod & Alum. Cap for Cor. by double proportionate distance.
Scribed: 16" D.F. S. 28° W. 42.3 ft. 8" D.F. S. 43° E. 44.6 ft.
9" D.F. N. 57° W. 10.2 ft. 9" D.F. N. 72° E. 56.2 ft.

89

1/4 Corner to Sec. 1, T32-7 and Sec. 6, T32-6.
Found - Original Bearing Trees.

Set - 1" x 30" I. Pipe and Scribed: 5" D.F. N. 88 1/2° E. 26.7 ft.
5" D.F. N. 81° W. 42.7 ft.

90

RE-RENEWED SEE CORNER NO. 130

1/4 Corner to Sec. 1, T32-7W, and Sec. 36, T31-7W
Set - 1 1/2" x 24" I. Pipe by proportionate measurement.
Scribed: 20" I.C. N. 25° E. 34.5 ft. and 21" Y.P. S. 24° E. 28.2 ft.

90 A

1/4 Corner to Sections 1 and 2.

Found - Orig. BT's.: 6" Laurel S. 32° E. 7.9 ft. scribe visible.
8" D.F. S. 5° W. 19.0 ft., no scribe.
30" D.F. S. 11° E. 14.5 ft., scribe visible.
(Assume Orig. Surv. took bear. to 8" D.F. & measured
and scribed the 30" D.F.)

Set - 1" x 36" I. Pipe and Scribed: 20" D.F. S. 63° E. 48.1 ft.

91

1/4 Corner to Sec. 36, R7W and Sec. 31, R6W.

Found - 1" Iron Rod (unrecorded) 1.0 ft. south of Brass Cap.
Also "+" on log for 1/4 corner.
10" Pine, now 34" Stob, N. 70° E. 16.5 ft., opened at a different
time for scribe and found "S 1/".
36" D. Fir, now burnt stump, N. 52° W. 17.2 ft.

Set - Brass Cap at Cor. Mkd: County Surveyor's R T 32 S R
Office, 1969 7W S 36 S 31 6W

New BT's: 11" Laurel N. 16° W. 10.9 ft. mkd: 1/4 S36 CS BT.
17" S. Pine N. 78° E. 34.6 ft. mkd: 1/4 S31 CS BT.

This corner lies about 50 ft. south of Robert Dollar Road. 6/25/69
C.S. File 54/53

92

1/4 Corner to Sec. 5, T32-7W and Sec. 32, T31-7W.

Found - 35" D. Fir Corner Tree, now Snag, "1/4 S" faint bark scribe on
south side of tree.
32", now 38" D. Fir N. 80° W. 23.8 ft., no scribe found.
36", now 38" Cedar, S. 85° E. 29.0 ft., faint bark scribe "1/4 S".

Good dist. for call on top of ridge, about 660 ft.

Set - Brass Cap at Cor. Mkd: County Surveyor's T 31 S R7W 1/4 S 32
Office, 1969 T 32 S S 5

New BT's: 19" Cedar S. 55° W. 17.7 ft. mkd: 1/4 S5 CS BT".
13" D. Fir N. 20 1/2° E. 26.8 ft. mkd: 1/4 S32 CS BT".

7/1/69
C.S. File 54/36

93

Section Corner to Sections 11 - 12 - 13 - 14.

Found - 1 Original Bearing Tree.

Set - 5/8" Iron Rod & Alum. Cap.
11" D. Fir N. 59 1/2° E. 18.8 feet
16" D. Fir S. 61° E. 4.1 feet
20" D. Fir S. 62° W. 3.1 feet
16" D. Fir N. 21° W. 27.2 feet.

94

1/4 Corner to Sections 12 and 13.

Set Corner at proportionate distance.

Set - 5/8" Iron Rod & Alum. Cap
Bearing Trees: 9" D. Fir S. 39 1/2° W. 19.3 feet
7" Chinquapin N. 69 3/4° W. 12.2 feet

95