

**Douglas County Surveyor's Record of  
Government Corners Renewed**

T 32

T. S.

R 7

R. W. W. M.

KOKE-CHAPMAN CO., EUGENE, ORE. 21881

Gary L. Langlitz  
M. W. Cline  
Doug. Co. Surveyors Office  
Aug. 22, 1977  
C.S. 59/38

State of Oregon-Department of Forestry  
Lloyd D. Smith  
Restored by James M. McIntosh, Engineer  
Witnesses: David B. Buchholz & Christopher Hughes  
March 13, 1978  
C.S. 58/164

Section Corner for Secs. 28, 27, 33 and 34.

Found - No trace of orig. post or 2" I.P. set by Larsen in 1954. Ren. #1  
No trace of orig. bearing trees.

A 30" Fir now 32" stump with scribing "BT" and other illegible scribing visible on an unhealed double blaze. Ren. #1

Found "PK" nail in above mentioned stump.

Found 5/8" I. Rod firmly set, 10.3 ft. N.42°W., of the BT stump.

(this corner was referenced out for road construction in 1972 by J. M.

Powell, Doug. Co. Surveyors Office.)

We establish the corner at N.42°W., 106.8 ft. from the found 5/8" I. Rod.

Also found:

A 32" D. Fir stump previously described bears S.42°E., 117.1 ft.

A 6" Tan oak now an 8" snag with scribing "3642 BT" visible on unhealed blaze bears S.54 1/2°W., 120.9 ft. (Rec. S.54 1/2°W., 119.6 ft.) Ren. #1

A 5" now 10" tanoak with scribing "3642 BT" visible on unhealed blaze bears N.42°W., 87.0 ft. (Rec. N.42°W., 86.1 ft.)

At the corner point we set:

A 1" x 30" I. Pipe, 20" in the ground with mound of stone to top, with brass cap attached marked: Douglas County Surveyor 1977

T 32 S R 7 W

S 28 | S 27

S 33 | S 34

New BT's - A 16" D. Fir scribed "T32S R7W S33 CS BT" on a double blaze bears S.44°W., 97.8 ft.

An 18" Live oak, scribed "T32S R7W S34 CS BT" on a double blaze, bears S.81°E., 76.6 ft.

Note: Corner located 31 ft. west of the centerline of Cow Creek access Road and one foot east of a steel fence post with survey marker witness sign attached.

8/22/77

Section Corner common to Secs. 13 and 24; and Secs. 18, 19 of T.32-6

Original: Fir Post (missing) from which a:

8" Laurel bears N.85°E., 30 lks.; now 14" x 3" high hollow root crown in Laurel clump N.81°E., 20.0 ft.

6" Laurel bears S.30°E., 61 lks.; now Laurel clump S.14 1/2°E., 37.2 ft.

24" Pine bears S.70°W., 100 lks.; now 28" x 50 ft. high snag S.70°W., 60.3 ft. horz. measurement, slope measurement is 100 lks. to pre-determined face and 103 lks. to center of tree. Only Pine in area on steep and rocky SE. slope.

5" Live Oak bears N.45°W., 31 lks.; now Live Oak clump in place.

Set - 1 1/2" x 36" Gal. I.P. with 3" bronze cap mkd. "Oregon State Board of Forestry T32S R7W R6W S13 S18 S24 S19 1978 RS1101", 20 ins. in ground, in mound of rock, and from which a:

14" Fir bears S.62°W., 10.9 ft. to face; scribed T32S R7W S24 BT, BLM face on SE side of tree; marked T32S R7W S13 BT.

38" Fir bears N.01°W., 59.9 ft. to face; scribed T32S R7W S13 BT.

28" Fir bears N.74 1/2°E., 85.9 ft. to face; scribed T32S R6W S18 BT. RS1101.

19" Fir bears S.25°E., 48.7 ft. to face, on BLM scribed tree; marked T32S R6W S19 BT.

Set 4" x 4" x 72" white painted Cedar Post N.73°W., 3.6 ft. from corner pipe. Oregon State Forestry Dept. metal location poster on 14" Fir, S.62°W., 10.9 ft. BLM pipe and cap S.3°21'W., 23.6 ft. to be obliterated by BLM.

3/13/78

1/4 Corner for Sec. 24; and Sec. 19 of T.32-6.

Original - Laurel Post (Remains of point found) from which a:

32" Fir bears S.48°E., 45 lks.; now 52" x 25 ft. high burnt & shattered snag in place, 48 lks. to center, exposed axe work at top of face & chaining notch at bottom of face.

38" Fir bears N.52°W., 30 lks. now stump hole with portions of roots remaining.

Set - 1 1/2" x 36" Gal. I.P. with 3" bronze cap mkd. "Oregon State Board of Forestry T32S 1/4 R7W R6W S24 S19 1978 RS1101", 34" in ground, & from which a:

27" Fir bears S.35°W., 23.8 ft. to face; scribed 1/4 S24 BT RS1101.

10" Madrone bears S.72°E., 21.1 ft. to face; scribed 1/4 S19 BT RS1101.

Set -4"x4"x72" White painted Cedar Post, N.58°E., 2.9 ft. from corner pipe. Oregon State Forestry Dept. metal location poster on 11" madrone N.40°W., 3.2 ft. BLM pipe and cap N.06°53'W., 21.3 ft. to be obliterated by BLM.

FD OK  
M. Smalley  
7/93 Mill-48

102

103

104