

Douglas County Surveyor's Record of
Government Corners Renewed

T 32 R 7 R.W.W.M.
T. S.

KOKE-CHAPMAN CO., EUGENE, ORE. 21881

105

Witness Corner for 1/4 Corner for Secs. 19 and 20.

- Found - An orig. Pine Corner tree (Rec. 60") now burnt, rotted and broken off at ground level. No scribing visible.
A 1" x 24" Iron bolt on west side of tree. Ren. #2.
An orig. 60" Pine, now a 43" stump, bears N.34°E., 52.3 ft. from center of cor. tree to center of brg. tree. (Rec. N.30°E., 49.5 ft.) rotted blaze, no scribing.
A root hole bears S.30°W., 6.0 ft. with orig. pine alongside. No scribing visible. Brg. & Dist. from center of cor. tree to center of root hole.
An 8" Laurel (madrone) now 11" bears N.22°W., 19.3 ft. (rec. N.24°W.) with visible scribing on partially healed blaze. Scribing not readable. Ren. #2
A 6" Laurel (madrone) now rotted with only face standing bears S.55°E., 15.3 ft. visible scribing "2968 BT". Laurel measures from ctr. of tree to I. Bolt.
- Set - Replace iron bolt with 1" x 36" I.P. with brass cap at brg. and dist. from BT's in Ren. #2. Set bolt on east side of cap west side of tree. Cap bears N.55°W., 2.5 ft. from ctr. of cor. tree. Stamped cap "Douglas Co. Surveyor"

T 32 S R 7 W
1/4 S 19 | S 20
1978

Returned to corner to find BLM added "WC 2.5 ft. c_{or}" to cap.

- New BT's- An 11" D. Fir bears S.40°E., 40.8 ft. scribed "1/4 S20 CS BT" on double blaze. Returned to add "WC" at top of blaze.
A 10" D. Fir bears S.71°W., 16.8 ft. scribed "WC 1/4 S19 CS BT" in a double blaze. This tree scribed on 2nd visit.

1-79

8/21/78 & 9/5/78

106

Section corner common for Sec. 36; and Sec. 31 of T.32-6 only.

Set - 1" x 30" Iron rod flush.

From which:

- 3" dwarf apple bears S.66°30'E., 4.41 ft.
4" peach, bears S.82°W., 14.50 ft. measured to trunk centers, not marked.

Fenceline 25 ft. north. An 1855 closing-corner re-set using single proportion measure

7/79

107

1/4 Corner for Sections 5 and 6

- Set- 5/8" x 30" Iron rod and alum. cap
BT's- 5" Chinquapin bears S.67°W., 8.9 feet.
5" Fir bears S.62°E., 4.2 feet.

Howard W. Johnstone
LS# 498
For: Rsbg. Lmbr. Co.
April 1980 M 83-25

108

1/4 Corner for Sections 35 and 36

- Set - 1" x 30" I. Pipe
BT's - 6" D. Fir bears S.36°W, 17.62 ft. mkd. "1/4 PS 841 BT".
24" Madrone stump bears East, 0.1 ft. mkd. "1/4 PS 841 BT".
8" D. Fir bears S.82°39'E., 36.40 ft., a reference tree from the Robert Dollar Co.'s 1954 staff compass survey.
16" D. Fir bears S.82°E., 33.73 ft. with scribe marks "3642 BT" visible on a previously opened face.

Note - This corner situated in an old burn area and could not find any evidence of original bearing trees. The 1/4 corner was re-established at the single proportion point.

Ronald Brandt
LS #841
For: Robert Dollar Co.
April 1980
M 83 - 29
C.S. 58/125N

109

Section Corner common to Secs. 26, 27, 34, & 35

- BTs fd- 26" pine stump bears S.79°E., 224.4-ft. w/axe work.
Dead madrone root cluster bears S.60°W., 15.2-ft.
Madrone root cluster bears N.32°E., 40.3-ft.

Set - 2-1/2" x 30" alum pipe, 24" in ground w/3" cap mkd: T32S R7W S27 S26 S34 S35 1983 RLS 1654.

- New BTs- 9" madrone bears S.70°E., 39.8-ft., faced & scribed: T32S R7W S35BT.
29" D. fir bears S.83°W., 84.6-ft., faced & scribed: T32S R7W S34 BT.
7" madrone bears N.64°W., 38.3-ft. faced & scribed: T32S R7W S27 BT.
6" live oak bears N.34°E., 5.9-ft. faced & scribed: T32S R7W S26 BT.

5/83

Karen Reed, Doug. Co. Surveyors Office
Frank C. Sliagy
Gary Langlitz (2nd visit)
Aug. 21, 1978 and Sept. 5, 1978
C.S. 60/17

Ronald Brandt #841
For: Ronald and Lind Brandt
July 1979
M 78 - 48