

Douglas County Surveyor's Record of
Government Corners Renewed

T. 32 S. T.S. R. 7 W. R.W.W.M.

KONE-CHAPMAN CO., EUGENE, ORE. 97301

Ronald Quimby, LS#1654
For: Boise Cascade Timberlands of OR
May, 1983
M 94 - 27

110

1/4 Section Corner common to Secs. 27 & 34.
Set - 2-1/2" x 30" alum. pipe, 26" in ground w/ 3" cap, mkd: T32S
R7W WM 1/4 S27 S34 1983 RLS 1654.
New BTs- 6" tan oak bears N.50°W., 5.4-ft. faced & scribed: 1/4 S27 BT.
14" D.fir bears S.3°E., 44.0-ft. faced & scribed: 1/4 S34 BT.
----- 5/83

111

1/4 Section Corner common to Secs. 27 & 26.
BTs Fd - 56" ponderosa pine (burned out face-no marks visible), bears
S.63°09'W., 97.7-ft. (Orig. BT).
28" ponderosa pine (sawn into-no marks visible), bears
N.27°09'E., 58.1-ft. (Orig. BT).
Set - 2-1/2" x 30" alum. pipe, 26" in ground w/3" cap mkd: T32S
R7W WM 1/4 S27 S26 1983 RLS 1654.
New BTs- 6" sugar pine bears S.84°W., 28.4-ft., faced & scribed: 1/4 S27 BT.
8" tan oak bears S.63°E., 6.1-ft., faced & scribed: 1/4 S26 BT.
----- 5/83

112

1/4 Section Corner common to Secs. 34 & 35.
Set - 2-1/2" x 30" alum. pipe, flush with ground w/3" cap mkd:
T32S R7W WM 1/4 S34 S35 1983 RLS 1654.
New BTs- 6" D.fir bears N.89°E., 19.5-ft., faced & scribed: 1/4 S35 BT.
8" tan oak bears N.12°W., 37.0-ft., faced & scbd: 1/4 S34 BT.
----- 5/83

113

Section corner for Secs. 3 and 4; and Secs. 33 & 34 of T.31-7.
Found - 1964 BLM brass cap properly marked, projecting 4" above ground.
Orig. 20" rotted and uprooted cedar snag, its root hole bears
N.50°E., 16.5 ft.
1964 BT, a 30" D. fir bears N.17 3/4°E., 39.6 ft. with a healed
blaze.
1964 BT, a 26" D. fir bears S.59 3/4°E., 49.5 ft. with a healed
blaze.
1964 BT, a 10" uprooted D. fir snag, its root hole bears S.59°W.,
54.1 ft.
New BTs -20" incense cedar bears S.82 1/2°W., 60.4 ft. scribed "T32S R7W
S4 BT" with a brass washer "LS 1941" nailed into lower blaze.
8" chinquapin bears N.15°W., 47.6 ft. scribed "T31S R7W S33 BT"
with a brass washer "LS 1941" nailed into -ower blaze.
Distances to new bearing trees are measured to a nail in the root crown at
the side and center of the tree. I painted 6" red bands around new BTs and
all bearing tree faces red and attached BT tags.

114

Section corner for Secs. 5 and 4; and Secs. 32 & 33 of T31-7.
Found - 1964 BLM brass cap properly mkd. on a 2 1/2" I.P. projecting
2" above ground.
Orig. BT, 34" D. fir stump bears S.36°E., 11.9 ft. with bark scribe
marks "T32S 7W S4 BT" visible.
Orig., 26" D. fir stump bears S.12°W., 37.8 ft. with bark scribe
marks "T32S R7W S5 BT" visible, (Rec. 39.8 ft.)
1964 BT, 19" D. fir stump bears N.79 1/2°E., 58.1 ft. with healed
blaze.
1964 BT, 18" D. fir stump bears N.54 1/2°W., 48.8 ft. with healed
blaze.
1982 BLM BTs in a survey not yet approved:
20" D. fir tump bears S.40°E., 51.0 ft. with scribe marks "T32S
R7W S4 BT" visible (Rec. 52.8 ft. from BT tag.)
8" cedar bears N.58°W., 54.8 ft. with scribe marks "T31S R7W S32
BT" visible.
New BT - 8" tan oak bears N.45 1/2°E., 120.9 ft. scribed "T31S R7W S33
BT" with a brass washer stamped "LS 1941" nailed into lower
blaze.
I painted 6" red bands around new bearing trees and all bearing tree faces
red and attached BT tags. Distance to new BT measured to a nail in root
crown at the side and center of the tree.

Kristian De Groot LS 1941
For: Allen & Gibbons Logging, Canyonville, OR
November 28, 1983
C.S. 58/229