

**Douglas County Surveyor's Record of  
Government Corners Renewed**

T 32                      T. S.                      R 7                      R. W. W. M.

FOKE-CHAPMAN CO., EUGENE, ORE. 97401

Max Hull L.S. 901  
For: Gregory Forest  
Products  
Aug. 1989  
108 - 69  
S. 63/24

1/4 Corner for Sections 7 and 8  
Found - 1978 BLM brass cap, out of position, N.72°43'32"W., 7.58 ft.  
Set - (by proportion) a 5/8" x 30" iron rod with cap mkd. "HULL RS 901"  
Used BLM BTs;  
15" Fir, S.26°E., 34.35 ft. B.H.  
14" Fir, S.46°W., 55.72 ft. B.H.

119

8/89

Max Hull L.S. 901  
For: Gregory For.  
Products  
Oct. 1990  
M 111 - 4  
C.S. 63/115

Section corner for sec's 19 & 30 T.32 S. R.7 W. & sec's 24 & 25  
T.32 S. R.8 W.  
Set - 5/8 X 30" I.R. with cap mkd. "HULL RS 901"  
B.T.s - 8" fir, S.62°W., 7.20 ft.  
6" fir, S.54°E., 6.90 ft.  
7" madrone N.16°E 17.90 ft.  
10" fir N.04°W., 45.60 ft.  
Note - Corner falls on blazed line running west and north/south,  
blazed line bears east 15 ft.

120

10/90

1/4 Corner for Sections 19 and 30  
Set - 5/8" I.R. with cap mkd. "HULL RS 901"  
B.T.s - 5" live oak, S.65°W., 12.20 ft.  
8" madrone, N.71°W., 12.20 ft.  
12" knob cone pine, N.79°E., 23.40  
5" live oak, S.50°E., 26.30 ft.  
Note - East/west blazed line bears north 12 ft.

121

10/90

1/4 Corner for sections 19 and 30  
Found - 5/8" dia. I. Rod with a yellow plastic cap mkd. Hull  
RS 901, is firmly set and protrudes 8" above ground. (I.R.  
is found to be 30" long when replaced with B.C. monument)  
Ren. No. 121

122

(Hull's 1990 survey proportioned in the corner position. The area of the  
corner position was burned in the past, when area is searched, no evidence  
of original bearing trees is found. All BTs from Hull are found.)  
A 12" knob cone Pine now a 14" DBH with a partially healed pitch  
over double blaze bears N.77°E., 23.4 ft. (Rec. N.79°E., 23.4)  
A 5" live Oak now a 6" DBH, with illegible scribing in a  
partially healed double blaze bears S.51°E., 26.9 ft. (Rec.  
S.50°E., 26.3 ft.)  
5" Live Oak now 5" DBH, with illegible scribing visible in a  
partially healed double blaze bears S.65°W., 11.5 ft. (Rec.  
S.65°W., 12.2 ft.)  
An 8" Madrone now 9" DBH, with a healed double blaze bears  
N.71°W., 12.6 ft. (Rec. N.71°W., 12.2 ft.)

Record distances to bearing trees agree when measured to large nails in  
bearing tree trunks but not when measured to center of root crown (as per  
Manual of Instructions)

Set- Position of found Iron rod w/plastic cap is referenced out, the  
monument is removed from the ground and replaced with a 2 3/8"  
dia. brass cap mkd: Douglas County Surveyors Office

	T 32	S	R
1/4	S 19		7
	S 30		W
	1992		

on a 1 1/4" O.D. 32" long Iron pipe. New brass cap monument is  
firmly set and protrudes approx. 7" above ground. Found Iron  
rod and plastic cap monument is reset on West edge of BC/IP  
monument and protrudes approx. 6" above ground.

No new accessories. BT tags changed to reflect difference in measured  
bearings and distances from record.

Monument is 20 ft. lower than and on the Western slope of a high North-South  
running ridge forming the East slope of the Skull Creek drainage

10/22/92

Douglas County  
Surveyors Office  
R. W. Smith, Deputy  
Stephen Flause  
T.R. Franssen  
Oct. 22, 1992  
C.S. File 64/32