

Douglas County Surveyor's Record of  
Government Corners Renewed

T 32 T. S. R 7 R. W. W. M.

KOHN-CHAPMAN CO., EUGENE, ORE. 91881

Douglas County  
Surveyors Office  
Randall Smith  
Stephen J. Fluase  
Dec. 10, 1992  
C.S. File 64/35

Section Cor. for 30 & 31; 25 & 36 of T.32-8

Found - A 2½" dia 1967 DCSO brass cap on a 1½" O D Iron pipe protruding 18" above ground Ren #47  
Orig. 18" now 20" dia D Fir stob with illegible bark scribing bears S 10°W, 44.8 ft (Rec S 10°W., 47.5 ft )  
8" now 13" dia D Fir with a fully healed double blaze bears S 85½°E, 13.4 ft. (Rec East 13.4 ft )  
8" now 9" dia. D.Fir with a partially healed double blaze scribe marks visible bears S.78°E., 15.0 ft. (Rec. S.78°E., 16.1 ft.)  
9" now 13" dia., D.Fir with a fully healed double blaze, bears N.34°W., 3.5 ft. (agrees w/rec)  
10" now 10" dia. Madrone with a partially healed double blaze scribing visible "32S R8W S36 CS BT" bears S.4°W., 24.1 ft. (Rec. S.4°W., 25.2 ft.)  
Set - A mound of stone is added around base of DCSO BC/IP. Brass Cap protrudes 3" above 3 ft. x 2 ft. by 15 ft. deep mound of stone.  
No new Accessories.

12/10/92

1/4 COR. SECS. 23 & 26

Mark Smalley  
L.S. #2354  
For: Roseburg Resources  
April 1993  
M 117-43

Found - Original Stone monument, mark ¼ on North side, metal tag set by Robert Dollars Survey Crew in 1957  
BTs - 18" Fir, S.74°W., 52.2', "¼ S26 BT"  
16" Fir, S.50°E., 3.8', "¼ S26 BT"  
7" Fir, N.85°E., 80.3', "¼ S23 BT"  
8" Fir, North, 32.0', "S 23 BT"

1/4 COR. SECS. 21 & 28

(Ren # 23)

Found - 1978 Cadastral BCIP  
BTs - 12" Fir, S.13°E., 28.4', bark scribed faced and rescribed "¼ S28 BT"  
28" Pine, N.45°W., 11.2' - Dead.  
5" Tan Oak, N.60°E., 12.2' - Dead, scribe visible.  
5" Tan Oak, S.5°W., 17.2' - Dead, scribe visible.  
Scribed - 7" Fir, S.53°W., 20.2', "¼ S28 BT"  
6" Fir, N.10°W., 12.0', "¼ S21 BT"  
7" Fir, S.46°E., 21.5', "¼ S28 BT"

1/4 COR. SECS 28|29

(Ren # 21)

Found - 1½" Iron Pipe  
14" Chinquapin, N.72°W., 4.0', scribe visible.  
10" Chinquapin, S.72°E., 7.3', scribe visible.  
New BTs- 9" Chinquapin, N.44°E., 15.6' "¼ S28 BT"  
8" Fir, S.14°W., 28.0', "¼ S29 BT"

CENTER 1/4 COR. SEC. 28

Ren # 24

Found - 1½" Iron Pipe  
BTs - 14" Fir, N.27°E., 62.7', snag, scribe visible.  
14" Cedar, S.26°E., 137.9', down & rotten.  
Scribed- 12" Cedar S.30°E., 100.6', "C ¼ S BT".  
14" Fir, S.26°W., 48.4', "C ¼ S BT".  
8" Fir, N.46°E., 18.7', "¼ S BT".  
14" Fir, N.8°W., 52.0', "C ¼ S BT".

1/4 COR. SECS. 27 & 28

Found - 1½" Iron Pipe tagged "RS 233" Ren # 20 : 69  
BTs - 30" Madrone N.15°W., 13.2', Part. healed.  
7" Chinquapin, N.60°E., 19.8', Part. healed.  
16" Madrone, S.73°W., 25.7', Dead - healed face.  
Scribed - 7" Fir, S.13°E., 10.0', "¼ S27 BT"  
5" Fir, S.42°W., 13.0', "¼ S28 BT"

Mark Smalley  
For: Roseburg Resources  
July 1993  
M 117-48

123

124

125

126

127

128