

Douglas County Surveyor's Record of
Government Corners Renewed

32

T. S.

8

R. W. W. M.

ROYE-CHAPMAN CO., EUGENE, ORE. 97199

Milner L. Larson, Reg. Prof. Engineer No. 3642
August 11, 1954
See C. S. file No. 41/289

Milner L. Larson, Reg. Prof. Engineer No. 3642.
November 22, 1954.
See C. S. File No. 41/320.

Milner L. Larson, Reg. Prof. Engineer No. 3642.
August 31, 1955.
See C. S. File No. 42/16.

Section corner to secs. 14, 15, 22, and 23.

I find a Sugar Pine, 50" diam., bears N.42°W., 163 lks. dist. marked as described (this tree was cut for a logging landing) a Chinquapin sprout, bears S.70°W., 29 lks. dist., a Laurel sprout, bears S.60°E., 14 lks. dist., a Laurel Sprout, bears N.35°E., 95 lks, dist. from these trees I drive a 1 inch iron bolt 30 inches in length, 24 inches in the ground, from which a Fir, 17" Diam., bears N.35½°E., 42.6 ft. dist. marked 3642 B.T.

A Fir, 12" diam., bears S.79½°E., 47.0 ft., marked 3642 B. T.

A Sugar Pine, 22" diam., bears S.57½°W., 86.1 ft., marked 3642 B. T.

A Fir, 12" diam., bears N.57½°W., 46.9 ft., marked 3642 B. T.

Va. 19°30' E.
4/23/68 - FOUND O.K. J.M.P. - C.S. 54/65
10/24/92 - FD. OK DC 20 - C.S. 64/29

1

Standard corner of secs. 35 & 36.

No evidence of the cor. post remains. True point for corner established from original bearing trees:

A Fir stump 30 ins. in diam., bears N.31°46'E., 9.4 feet dist., an old notch and a (B.T. carved with knife) are all that remain.

A Fir stump, 21 ins. diam., bears N.49°08'W., 23.2 ft. dist., this stump badly rotted out.

A Fir, 26 ins. diam., bears S.9°39'E., 12.6 feet dist., parts of original scribing visible.

At point for the corner, I drive a 1½ inch iron pipe 30 inches long, 24 inches in the ground, and take new bearing trees as follows:

A Fir, 11 ins. diam., bears N.27°24'E., 14.7 feet dist. marked 3642 B. T.

A Fir, 14 ins. diam., bears N.33°27'W., 17.4 feet dist. marked 3642 B. T.

A Live Oak, 17 ins. diam., bears S.0°13'W., 31.4 feet dist., marked 3642 B. T.

Section corner to secs. 25, 26, 35, & 36.

At the true point for the corner, established from the four original bearing trees, drive a 1½ inch iron pipe, 30 inches long, 24 ins. in the ground.

¼ section corner to secs. 35 and 36.

At 2548.1 feet from the sec. cor. to secs. 25, 26, 35, and 36, I drive a 1½ inch iron pipe 30 inches long 24 inches in the ground.

From which:

A Fir, 8 ins. diam., bears S.82°39'E., 36.4 feet dist.

A Fir, 15 ins. diam., bears S.76°59'W., 36.2 feet dist.

4/5/68 SEARCHED FOR, NOT FOUND - C.S. 54/65 J.M.P.

Section corner to 9, 10, 15 and 16.

Set corner marker from Old B. T.

RE-RENEWED #66

¼ corner to secs 16 and 21.

Set corner marker from old B. Ts.

RE-RENEWED SEE CORNER NO. 20

¼ corner to secs. 15 and 16.

At the point for the corner a cross is made on the bedrock for the marker. (By proportionate measurement). Point falls on the South side of Bear Creek.

Marked two trees:

A 10 inch Maple, N.16°49'W., 36.3 feet.

A 30 inch D. Fir, N.70°19'E., 28.4 feet.

SEARCHED FOR NOT FOUND
4/11/68 J.M.P. C.S. 54/65

Section corner to secs. 15, 16, 21 and 22.

Corner set by proportionate measurement.

At point for corner set a 1½ inch by 36 inch iron pipe for corner marker.

Marked four trees:

A 13 inch Madrone bears N.61°25'W., 27.4 feet.

A 5 inch Madrone bears S.56°08'W., 28.3 feet.

An 11 inch Live Oak bears N.75°39'E., 45.9 feet.

A 13 inch Madrone bears S.8°17'E., 40.0 feet.

DC30
FO. OK 10/92
C.S. 64/39

2

3

4

5

6

7

8