

Douglas County Surveyor's Record of
Government Corners Renewed

32

T. S.

8

R. W. W. M.

ROSE-CHAPMAN CO., EUGENE, ORE. 97195

Section corner to secs. 5 & 6, T 32 S., R 8 W., and secs. 31 & 32, T 31 S., R 8 W.

The original corner could not be found after intensive search had been made, so corner set by single proportionate measurement.

Set a $\frac{1}{2}$ inch iron pipe at corner point.

Scribed four trees:

- 5 inch Tan Oak, N.59°30'E., 6.3 feet.
- 12 inch Tan Oak, S.10°00'E., 11.1 feet.
- 6 inch Tan Oak, S.29°00'W., 28.6 feet.
- 6 inch Tan Oak, N.81°30'W., 21.8 feet.

9

Wilner L. Larson
July, 1956
C. S. File No. 42/167.
Map File No. M 3 - 3.

$\frac{1}{4}$ sec. corner to sec. 5, T 32 S., R 8 W., and sec. 32, T 31 S., R 8 W.

Found 2 original B. T.s.

Set $\frac{1}{2}$ inch iron pipe for corner.

Scribed 1 new B. T.:

- 14 inch Madrone, N.15°00'W., 8.1 feet.

10

Section corner to secs. 7, 8, 17 and 18.

Could not find any trace of corner after intensive search, so set corner by double proportionate measurement.

Set $\frac{1}{2}$ inch iron pipe for corner.

Scribed new B. T.s:

- 8 inch Madrone, N.62°00'E., 01 feet.
- 8 inch Madrone, S.39°30'E., 4.2 feet.
- 18 inch Fir, S.10°00'W., 25.4 feet.
- 10 inch Madrone, N.24°00'W., 12.4 feet.

Found O.K.
4/19/67 J.M.P.

11

Wilner L. Larson
June, 1956
C. S. File No. 42/169.
Map File M 3 - 5.

$\frac{1}{4}$ sec. corner to secs. 7 & 8.

Original corner could not be found.

Set $\frac{1}{2}$ inch iron pipe for corner at proportionate distance.

Scribed two new trees:

- 8 inch Madrone, N.66°30'W., 19.5 feet.
- 20 inch Madrone, N.64°30'E., 19.1 feet.

12

$\frac{1}{4}$ sec. corner to secs. 17 & 18.

Set a $\frac{1}{2}$ inch iron pipe for $\frac{1}{4}$ sec. corner at proportionate measurement. Original corner could not be found.

Scribed two new trees:

- 5 inch Madrone, N.36°44'W., 6.4 feet.
- 8 inch Live Oak, N.28°17'E., 15.8 feet.

Found O.K. 4/19/67 J.M.P.

13

$\frac{1}{4}$ sec. corner to secs. 7 & 18.

Original corner could not be found.

Set $\frac{1}{2}$ inch iron pipe at proportionate measurement.

Scribed 2 trees:

- 6 inch Fir, N.48°31'W., 11.9 feet.
- 8 inch Fir, S.63°13'E., 12.5 feet.

14

Section Corner to Sections 4, 5, 8, & 9.

Found - Orig. 48", now 42" R. Fir S.65°E. 14.5 ft. Good bark scribing "T32S".

Now 24" R. Fir that checks bearing & distance for Orig. N. W. BT.

Note - This Corner & All BT's are in fill slope of road. I uncover fill material to find scribing.

Find 1" Drill Steel at Corner.

I do not set Brass Cap.

New BT's: I rescribe (Bark)::

- 42" R. Fir S.65°E. 14.5 ft. S9 T32S R8W CS BT.
- 24" R. Fir N.54°W. 16.2 ft. scribed S5 T32S R8W CS BT.
- 36" R. Fir N.58°E. 27.8 ft. scribed S4 T32S R8W CS BT.

15

James W. Byron, Deputy
M. Godfrey
S. A. Blouw
August, 1958
C. S. File No. 49/110