

Douglas County Surveyor's Record of
Government Corners Renewed

T. 32 S. T. S. R. 8 W. R. W. W. M.

KOKE-CHAPMAN CO., EUGENE, ORE. 21881

30

Sec. Cor. to Secs. 4 and 3, T32-8W. & Secs. 33 & 34, T31-8W.
Found - Iron Pipe at Corner - Stone 3 v on E. & W. faces.
Orig. 30", now 51" D. Fir S. 23° W. 23.8 ft., faint bark
scribe "32 8 B".
Orig. 22", now " D. Fir, N. 70° W. 27.9 ft., has been
rescribed, but pitched over.
Orig. 20", now " S. Pine S. 75° E. 70.6 ft., shows good scar.
Orig. 20" S. Pine, now dead, N. 78° E. 36.3 ft., scribe visible.
Set - Brass Cap at Cor. Mkd: County Surveyor's T 31 S R 8 W
(Set B.C. alongside Office S 33 S 34
I.P. & Stone) 1967 S 4 S 3
No trees in Section 34. T 32 S
Reblzd. & Rescrbd: 51" D. Fir S. 23° W. 23.8 ft., mkd. T32S R8W S4 CS BT.

31

$\frac{1}{4}$ Corner to Sec. 4, T32-8W. & Sec. 33, T31-8W.
Found - Iron Pipe at $\frac{1}{4}$ Corner, See Ren. #16.
Orig. 14", now 17" Laurel, N. 65° E. 15.2 ft., opened for
scribing, rotten.
Orig. 14", now 18" Laurel, S. 15° W. 16.5 ft., opened for
scribing, "T".
13" Fir, now down, S. 39 $\frac{1}{2}$ ° E. 45.3 ft., scribed, pitched over.
Set - Brass Cap at $\frac{1}{4}$ Cor. Mkd: County Surveyor's T 31 S R 8 W
Office $\frac{1}{4}$ S 33
1967 S 4
Reblzed & Rescribed: T 32 S
38" Double Laurel S. 15° W. 16.5 ft., mkd. $\frac{1}{4}$ S 4 CS BT.
New BT: 15" Laurel N. 68° E. 22.8 ft. mkd. $\frac{1}{4}$ S 33 CS BT.
Note - As in original notes, corner lies about 33.0 ft. west of
ridge top.

32

$\frac{1}{4}$ Corner to Sec. 3, T32-8W. & Sec. 34, T31-8W.
Found - 44", now 50" D. Fir, S. 2° E. 39.6 ft., faint "BT" visible,
Also notch below main face.
No trace of 7" Fir N. 20° W. 19.8 ft.
Iron Pipe at $\frac{1}{4}$ Corner, (unrecorded)
Tree with face but no scribing at N. 10° E. 16.1 ft.
Set - Brass Cap at Cor. Mkd. County Surveyor's T 31 S R 8 W
Office $\frac{1}{4}$ S 34
1967 S 3
New BT's: 10" D. Fir S. 37° E. 18.4 ft. mkd. $\frac{1}{4}$ S 3 CS BT.
10" D. Fir N. 10° E. 16.1 ft. mkd. $\frac{1}{4}$ S 34 CS BT.
Note - As in original notes, spring branch 132.0 ft. E. of $\frac{1}{4}$ corner.

33

Sec. Cor. to Secs. 3 & 2, T32-8W. & Secs. 34 & 35, T31-8W.
Found - Pieces of Stone at Section Corner.
14", now 27" D. Fir N. 82° E. 34.2 ft. (recorded 32.6')
Old axe work, no scribe visible.
14", now 21" D. Fir S. 65° E. 27.1 ft., shows good scar.
16", now 36" D. Fir, S. 23° W. 19.8 ft., bark scribe visible.
13", now 30" D. Fir N. 35° W. 27.1 ft., bark scribe visible.
Set - Brass Cap at Cor. Mkd: County Surveyor's T 31 S R 8 W
Office S 34 S 35
1967 S 3 S 2
Reblazed & Rescribed: T 32 S
27" D. Fir N. 82° E. 34.2 ft. mkd. T31S R8W S35 CS BT.
36" D. Fir S. 28° W. 19.8 ft. mkd. T32S R8W S 3 CS BT.
30" D. Fir N. 35° W. 27.1 ft. mkd. T31S R8W S34
Note - Best way to reach corner is north on railroad to yellow
tag on small fir.

John M. Powell
Frank Jones & Cliff Stone
January, 1967
C. S. File No. 54/36