

Douglas County Surveyor's Record of
Government Corners Renewed

T. 32 S. T. S. R. 8 W. R. W. W. M.

KOKE-CHAPMAN CO., EUGENE, ORE. 21891

41

$\frac{1}{4}$ Corner to Section 36 only, T32-9W.
Found - Orig. 20" D.Fir, now stump, S. 72° W. 44.2 ft. scribe visible.
Orig. 8" D.Fir, now down, N. 35° W. 21.8 ft.
G.L.O. Brass Cap at $\frac{1}{4}$ Cor. properly marked in 1917
6" D. Fir, now dead, S. 67° W. 28.4 ft. scribe visible/.) Ren.
6" D.Fir, now dead, North 9.6 ft. scribe visible.) No. 24.
Note - Not having any bearing trees to mark, I tie this corner to
the $\frac{1}{4}$ Corner to Section 31, T32-8W. which is south 29.0 ft. (See Corner below)
All original trees tagged.
This corner lies 145.0 ft. S. of spur. Location tag approx.
495 ft. north of corner on Dutch Henry Trail Road.

42

$\frac{1}{4}$ Corner to Section 31 only, T32-8W.
Found - G.L.O. Brass Cap at $\frac{1}{4}$ Cor. properly marked in 1917.
Orig. 18" D.Fir, now snag, N. 72° E. 38.3 ft., shows scar.
12" D. Fir, now stump, S. 86° E. 48.8 ft.) Ren. #25.
9" D. Fir, now dead, N. 35° E. 18.5 ft. scribe visible.)
New BT: 6" D.Fir N. 51° E. 52.6 ft. mkd. $\frac{1}{4}$ S31 CS BT.
Note - This corner lies in clear cut area, approx. 30 ft. N. of ravine
on west edge of skid road. (Also lies S. of $\frac{1}{4}$ Corner above)

43

Corner to Sections 30 and 31 only, T32-8W.
Found - G.L.O. Brass Cap, properly marked in 1917.
48" D. Fir, N. 57° E. 42.9 ft., shows good scar, Snag Top.
No trace of S.E. BT., falls in skid road.
New BT's: 8" D.Fir S. 54 $\frac{1}{2}$ ° E. 7.6 ft. mkd. T32S R8W S31 CS BT.
7" D.Fir N. 69° E. 18.7 ft. mkd. T32S R8W S30 CS BT.

44

Corner to Sections 25 and 36 only, T32-9W.
Found - 36", now 40" D.Fir, S. 40° W. 42.9 ft., shows good scar.
14" Laurel, now Dead Stob, N. 15° W. 51.5 ft., scribe visible.
G.L.O. Brass Cap, properly marked in 1917.
New BT: 8" D.Fir N. 47° W. 19.0 ft. mkd. T32S R9W S25 CS BT.

45

~~$\frac{1}{4}$ Corner to Sections 25 and 36, T.32S. R.9W. (Wrong Range)
Found - G.L.O. Brass Cap for $\frac{1}{4}$ Corner, properly marked in 1917.
10", now 14" Chinquapin, N. 9° E. 9.9 ft., scribe visible,
face rotten.
20" D.Fir, now 28" Stump, S. 12° W. 35.4 ft. (record 22.4 ft.)
opened for scribe, "S25 BT".
New BT's: 10" D.Fir S. 67 $\frac{1}{2}$ ° W. 23.3 ft. mkd. $\frac{1}{4}$ S36 CS BT.
16" D.Fir N. 43° E. 25.0 ft. mkd. $\frac{1}{4}$ S25 CS BT.
Note - Ring County places trees at proper time. Calls are good.~~

46

Corner to Sec. 6, T33-8W. & Sec. 1, T33-9W.
Found - Orig. 5x8x8 Stone at Corner with 4 notches on W. side.
10", now 11" D.Fir, S. 78° E. 30.4 ft., opened & found scribe.
30", now 36" Pine, S. 30° W. 19.1 ft., shows good face.
Set - Brass Cap at Cor. Mkd: County Surveyor's R T 32 S RDougl Co.
Office 9 S 1 T S 6 8
1967 W Dosp. Co. W
Rescribed 11" D. Fir S. 78° E. 30.4 ft. mkd. T33S R8W S6 CS BT.

47

$\frac{1}{4}$ Corner to Sec. 25 only, T32-9W.
Found - 36", now 39" D.Fir, S. 32° W. 67.3 ft., shows good scar.
8" Chinquapin, now down, N. 18° W. 37.0 ft., rotten face, shows scribing.
G.L.O. Brass Cap at $\frac{1}{4}$ Corner, properly marked in 1917
New BT: 8" Chinquapin N. 89° W. 20.0 ft. mkd. $\frac{1}{4}$ S25 CS BT.

John M. Powell
Frank Jones
June, 1967
C.S. File No. 54/44