

Douglas County Surveyor's Record of  
Government Corners Renewed

T. 32 S. T. S. R. 8 W. R. W. W. M.

KOKE-CHAPMAN CO., EUGENE, ORE. 21881

55

$\frac{1}{4}$  Corner to Sec. 12, T32-8W. and Sec. 7, T32-7W.  
Found - Orig. 44" Pine, now S.4°W. 67.3 ft., reblazed &  
scribed " $\frac{1}{4}$  S12 RS33 BT."  
46" Pine, now down & burnt, S. 85° E. 63.4 ft.  
Wooden Post at Corner, Corner hits very good for call 2 chns.  
Set - Brass Cap at Cor. Mkd: County Surveyor's R T 32 S R  
Office 8 S 12 | S 7 7  
W 1967 W  
New BT: 6" Pine N. 45° E. 18.6 ft. mkd. " $\frac{1}{4}$  S7 CS BT.  
Nov. 6, 1967

56

Section Corner to Secs. 25 & 36, T32-8W. and  
Secs. 30 & 31, T32-7W.  
Found - Original 28" Corner Tree, now rotten Stob.  
Orig. 20" Fir, now Stob, S.70°E. 48.8 ft., no scribing  
Orig. 18" Fir, now burnt stub, S.10°W. 47.5 ft., bark scribe fd.  
Orig. 10" Fir, now stob, N.82°W. 66.0 ft., scribe marks found  
but not legible.  
Distances to bearing trees appear to be slope distance. #122  
Set - Brass Cap at S. edge of Cor. Tree Stob. Mkd: R T 32 S R  
County Surveyor's Office 8 S 25 | S 30 7  
1967 W S 36 | S 31 W  
New BT's: 8" D. Fir East 13.4 ft. mkd. T32S R7W S30 CS BT.  
8" B. Fir S.78°E. 16.1 ft. mkd. T32S R7W S31 CS BT.  
9" D. Fir N.34°W. 3.5 ft. mkd. T32S R8W S25 CS BT.  
10" Laurel S.4°W. 25.2 ft. mkd. T32S R8W S36 CS BT.  
Note - This corner lies approx. 30 ft. south of high rock point.

FD 10/90  
M111-4

57

$\frac{1}{4}$  Corner to Sec. 30, T32-7W. and Sec. 25, T32-8W.  
Found - 38" D. Fir Corner Tree, now 43", faint bark scribe visible  
on west side.  
No trace of Laurel or Chinquapin BT.  
Set - Brass Cap on W. side of Cor. Tree mkd: R T 32 S R  
County Surveyor's Office 8  $\frac{1}{4}$  S 25 | S 30 7  
W 1967 W  
New BT's: 12" D. Fir N. 7° W. 56.4 ft. mkd.  $\frac{1}{4}$  S25 CS BT  
13" D. Fir N.35°E. 84.5 ft. mkd.  $\frac{1}{4}$  S30 CS BT.  
11/7/67

58

$\frac{1}{4}$  Corner to Sec. 19, T32-7W. and Sec. 24, T32-8W.  
Found - Orig. 38" Pine, now dead stob, S.70°E. 46.2 ft., old  
axe work, no scribing.  
Orig. 30", now 40" D. Fir, N. 85° W. 28.4 ft., bark scribe  
visible, " $\frac{1}{4}$ S BT".  
Set - Brass Cap at  $\frac{1}{4}$  Cor. Mkd: County Surveyor's R T 32 S R  
Office 8  $\frac{1}{4}$  S 24 | S 19 7  
W 1967 W  
New BT's: 12" D. Fir N. 24 $\frac{1}{2}$ ° E. 27.7 ft. mkd.  $\frac{1}{4}$  S19 CS BT.  
6" Y. Pine S. 78° W. 26.2 ft. mkd.  $\frac{1}{4}$  S24 CS BT.  
Note - This corner lies approx. 250 ft. south of old dead-end  
logging road, location tag on road.  
12/15/67

FD 10/90 M111-4

59

Section Corner to Sec. 36, T32-8W. & Sec. 31, T32-7W.  
Found - Orig. 28" Pine, now stob, N.57°E. 33.9 ft.  
Orig. 36" Pine, now stob, N.20°W. 52.8 ft.  
Orig. 34" Fir, now stob, S.15°E. (Rec.S.20°E.) 40.9 ft.  
Old Stone, set with 6 grooves on the N-E-W faces. (Orig. ??)  
Find no good orig. evidence of this corner. However by carefully  
chaining btwn. the CC. of Secs. 1 & 6, T33S.R's. 8 & 7 W., which is  
417.1 ft. and find the trees of the right type & size, hitting good  
for bearings and distances, I renew: R T 32 S R  
Set - Brass Cap at Cor. Mkd: County Surveyor's Office 8 S 36 | S 31 7  
1968 W S 1 W  
New BT's: 6" S. Pine W. 2.0 ft. mkd. S36 CS BT. T 33 S  
6" S. Pine N.60°E. 17.5 ft. mks. S31 CS BT.  
10" Y. Pine S13°E. 37.5 ft. mkd. T33S R8W S1 CS BT.

EDOK 1/6/66 Shaner M123-77

3/22/68

John M. Powell  
Frank Jones & Joe Brady  
November, 1967  
C. S. File No. 54/36